





NOTES:

MATERIALS:

- 1. BODY = STAINLESS STEEL PER ASTM A582, ALLOY 303, CONDITION "A".
 2. INSULATOR = VIRGIN WHITE TEFLON PER ASTM D1710, GRADE 1, TYPE I, CLASS "B".
 3. CONTACT = BERYLLIUM COPPER PER ASTM B196, ALLOY C17300, TEMPER TD04.

FINISHES:

- 1. BODY = GOLD PLATE PER ASTM B488-11, TYPE II, 30µin MIN, GRADE C, OVER 50 TO 100µin STRESS FREE NICKEL PER AMS-QQ-N-290.
 2. CONTACT = GOLD PLATE PER ASTM B488-11, TYPE II, 50µin MIN, GRADE C, OVER 100 TO 200µin STRESS FREE SULFAMATE NICKEL PER AMS-QQ-N-290.

UNLESS OTHERWISE SPECIFIED DIMENSIONS ARE IN INCHES TOLERANCES ON		D.N. 03/)ATE 15/18)ATE	Property of Radiall This document cannot be reproduced or communicated to a third party without prior a RADIALL company written permission of RADIALL.				
DECIMAL	ANGLE	APVD: C	15/18 DATE	SMA STRAIGHT JACK KNURL MOUNT				
		,	15/18					
REFERENCE: ORIGINATED: D.N.		MATERIALS & FINISHES: SEE NOTES		A A	FSCM NO. 19505	DWG NO. 9433—1113	-000	REV A
DATE: 03/15/18				SCALE 6:1		THIRD ANGLE PROJECTION	SHEET 1 O)F 1

Mouser Electronics

Authorized Distributor

Click to View Pricing, Inventory, Delivery & Lifecycle Information:

Radiall:

9433-1113-000