

3. RECOMMENDED MOUNTING TORQUE 0.9-1.3 INCH-POUNDS.

BEAD: ULTEM 1000


BUSHING, CONTACT: BERYLLIUM COPPER

GPPC-PX-1-2-EP-ST-CMM-X

c:\enterprisevault\DWG\MISC\MKTG\GPPC-PX-1-2-EP-ST-CMM-X-MKT.SLDDRW

BY: MATT M.

01/24/2022 | SHEET 1 OF 3



PHONE: 812-944-6733 FAX: 812-948-5047 e-Mail info@SAMTEC.com code 55322

DO NOT SCALE DRAWING

RECEPTACLE, SMPM, COMPRESSION MOUNT


GPPC-PX-1-2-EP-ST-CMM-X BY: MATT M. 01/24/2022 SHEET 2 OF 3

c:\enterprisevault\DWG\MISC\MKTG\GPPC-PX-1-2-EP-ST-CMM-X-MKT.SLDDRW


SHEET SCALE: 12:1

OTHER PROJECT IN ANY MANNER WITHOUT THE EXPRESS

REVISION C



RECOMMENDED FOOTPRINT (STRIPLINE SHOWN)



c:\enterprisevault\DWG\MISC\MKTG\GPPC-PX-1-2-EP-ST-CMM-X-MKT.SLDDRW

Mouser Electronics

Authorized Distributor

Click to View Pricing, Inventory, Delivery & Lifecycle Information:

Samtec:

GPPC-PF-1-2-EP-ST-CMM GPPC-PS-1-2-EP-ST-CMM