

HIGH-SPEED EDGE CARD SYSTEMS

0.60 mm, 0.80 mm and 1.00 mm PITCH





FEATURES & BENEFITS

- · Maximum Design Flexibility
- Up to 64 Gbps PAM4 performance
- PCI Express® 3.0, 4.0, 5.0 and 6.0
- Edge Rate® contacts optimized for signal integrity performance and high-cycle life
- Up to 200 positions available
- Vertical, right-angle, edge mount, pass-through orientations
- Power/signal combo, press-fit tails, rugged weld tabs, locks and latches
- Mating cable assemblies available

The PCI Express* design marks are registered trademarks and/or service marks of PCI-SIG.



Rugged tucked beam technology (HTEC8)



Differential pair for increased speed (HSEC8-DP)



Custom designs allow for misalignment in the X-Y axes (HSEC1)

KEY SPECIFICATIONS

| SERIES | PITCH | TOTAL POSITIONS | INSULATOR MATERIAL | CONTACT MATERIAL | OPERATING TEMP RANGE | CURRENT RATING | VOLTAGE RATING | LEAD-FREE SOLDERABLE |
|----------|---------|--------------------|-----------------------|---------------------|-------------------------|-------------------|-------------------|-------------------------|
| HSEC6 | 0.60 mm | 56-168 | Black LCP | Copper Alloy | -55 °C to +125 °C | 1.9 A (2 pins) | 240 VAC/339 VDC | Yes |
| HTEC8 | 0.80 mm | 20-200 | Black LCP | Copper Alloy | -55 °C to +125 °C | 3.0 A (2 pins) | 215 VAC/304 VDC | Yes |
| HSEC8-DV | 0.80 mm | 18-200 | Black LCP | BeCu | -55 °C to +125 °C | 2.8 A (2 pins) | 240 VAC/339 VDC | Yes |
| HSEC8-RA | 0.80 mm | 18-120 | Black LCP | BeCu | -55 °C to +125 °C | 2.6 A (2 pins) | 175 VAC/247 VDC | Yes |
| HSEC8-EM | 0.80 mm | 20-120 | Black LCP | BeCu | -55 °C to +125 °C | 2.8 A (2 pins) | 240 VAC/339 VDC | Yes |
| HSEC8-PE | 0.80 mm | 20-40 | Black LCP | BeCu | -55 °C to +125 °C | 2.8 A (2 pins) | 240 VAC/339 VDC | Yes |
| HSEC8-PV | 0.80 mm | 40-80 | Black LCP | BeCu | -55 °C to +125 °C | 3.2 A (2 pins) | 215 VAC/304 VDC | Yes |
| HSEC8-DP | 0.80 mm | 16-112 | Black LCP | BeCu | -55 °C to +125 °C | 2.7 A (2 pins) | 235 VAC/332 VDC | Yes |
| HSEC1 | 1.00 mm | 20-140 | Black LCP | Phosphor Bronze | -55 °C to +125 °C | 2.2 A (2 pins) | 215 VAC/304 VDC | Yes |







(0.80 mm) .0315" PITCH • VERTICAL EDGE CARD SOCKET

HSEC8

POSITIONS PER ROW

CARD **THICKNESS** **PLATING** OPTION

OTHER OPTIONS

"X"R

09, 10, 13, 20, 25, 30, 37, 40, 49, 50, 60,

70, 80, 100 (13, 25, 49 only available with -L or -L2 latching option; 09 only available with -L2 option; 37 only available with -L latching

option)

-01 = (1.60 mm).062" thick card

-03 = (2.36 mm) .093" thick card

= 10 µ" (0.25 µm) Gold on contact area, Matte Tin on tail

-S = 30 µ" (0.76 µm) Gold on contact area, Matte Tin on tail

-K = Polyimide Pick & Place Pad

-BI = Board Locks; -01 card only (Weld tab standard)

= Latching Option; -01 card only (13, 25, 37, 49 only) (Weld tab standard)

= ECDP Latching; -01 card only (09, 13, 25, 49 only) (For use with ECDP (Weld tab standard)

> -WT = Weld tab

Leave blank for Tray Packaging

-TR = Tape & Reel (09 - 70 only)

-FR = Full Reel Tape & Reel (must order max. quantities per reel; contact Samtec for quantity breaks) (09-70 only)


HSEC8-DV

Card Mates:


(1.60 mm) .062" card, (2.36 mm) .093" card, HSC8

Cable Mates: **ECDP**





10, 20, & 30 POSITIONS



OTHER SOLUTIONS

For complete edge card system with cards and sockets. visit samtec.com?RU8

> For a card to mate with an HSEC8 socket, visit samtec.com?HSC8



Note:

Some sizes, styles and options are non-standard, non-returnable.

| POSITIONS PER ROW | A | В |
|----------------------|---------------|---------------|
| 09*† | (4.50) .177 | (11.80) .465 |
| 13*† | (6.10) .240 | (15.00) .591 |
| 25*† | (6.10) .240 | (24.60) .969 |
| 37† | (18.10) .713 | (34.20) 1.346 |
| 40 | (18.90) .744 | (36.60) 1.441 |
| 49*† | (22.90) .902 | (43.80) 1.724 |
| 50 | (22.90) .902 | (44.60) 1.756 |
| 60 | (26.90) 1.059 | (52.60) 2.071 |
| 70† | (26.90) 1.059 | (60.60) 2.386 |
| 80† | (26.90) 1.059 | (68.60) 2.701 |
| 100† | (26.90) 1.059 | (84.60) 3.331 |

Positions where no dimensions are given do not have keying feature.

- * Mates with ECDP Series
- † Available with -01 Card Only

| CABLE | CONNECTOR |
|---------|--------------|
| ECDP-04 | HSEC8-109-L2 |
| ECDP-08 | HSEC8-113-L2 |
| ECDP-16 | HSEC8-125-L2 |
| ECDP-32 | HSEC8-149-L2 |

View complete specifications at: samtec.com?HSEC8-DV

Mouser Electronics

Authorized Distributor

Click to View Pricing, Inventory, Delivery & Lifecycle Information:

Samtec:

HSEC8-113-01-S-DV-L2 HSEC8-120-03-S-DV-A-TR