



or www.samtec.com?TC114 Plating: 10 μ" (0.25 μm) Gold on contact

TOOLING

- Hand Tool: CAT-HT-393-2430-13
- Mini Applicator (28-30 AWG): CAT-MC-393-2830-XX-01
- Extraction Tool: CAT-EX-MCX-8-01

2830 -S CC393 = 28 to 30 AWG = Strip = Contact (15 contacts or terminals) TC114 -M= Terminal = Mini Reel (1,000 - 5,000 contacts or terminals) ·R = Reel (15.00) (30,000 contacts or terminals) (1.75) .069 .590 (4.20) .165 (3.50) 0 0 \bigcirc Ð Ð Ð .138 (4.20)(1.50).165 (15.00) .590 059 DÍA 2 (1.75) -CC393 .069 (3.50) \oplus Ð 0 \bigcirc \bigcirc \bigcirc .138 (1.50) .059 DIA -TC114

WWW.SAMTEC.COM

Unless otherwise approved in writing by Samtec, all parts and components are designed and built according to Samtec's specifications which are subject to change without notice.

Mouser Electronics

Authorized Distributor

Click to View Pricing, Inventory, Delivery & Lifecycle Information:

Samtec: <u>MCPK-8-S</u> <u>MCPK-8-T</u>