


NOTES:

1. $\textcircled{Q}$ REPRESENTS A CRITICAL DIMENSION.
2. ASSEMBLE GOLD PLATED END AS SHOWN.
3. TERMINAL PUSHOUT FORCE: 2 lbs BEFORE HEAT.
4. TERMINALS TO BE FLUSH TO .010[.25] BELOW TOP OF SHROUD.

DO NOT
SCALE FROM
THIS PRINT



HTST-1XX-01-XX-DV-XX

NO OF POSITIONS
-02 THRU -36
(PER ROW)

LEAD STYLE
-01: SURFACE MOUNT
(USE T-1S6-08-X-2)

PLATING SPECIFICATION

- $\textcircled{Q}$ -T: TIN (USE T-1S6-08-T-2)
 $\textcircled{Q}$ -S: SELECTIVE GOLD (USE T-1S6-08-S-2)
 $\textcircled{Q}$ -L: LIGHT SELECTIVE GOLD (USE T-1S6-08-L-2)
-TM: MATTE TIN (USE T-1S6-08-T-2)
-SM: HEAVY SELECTIVE GOLD, MATTE TIN TAIL
(USE T-1S6-08-S-2)
-LM: LIGHT SELECTIVE GOLD, MATTE TIN TAIL
(USE T-1S6-08-L-2)

OPTION

- A: ALIGNMENT PIN (* ASO OPTION)
(SEE FIG. 3 SHT. 2)
-P: PICK & PLACE PAD
(USE PPP-22)
-TR: TAPE & REEL
(POSITIONS -02 THRU -25 ONLY)

ROW SPECIFICATION

- DV: DOUBLE VERTICAL
(USE HTST-XX-D)







FIG. 1
HTST-120-01-X-DV SHOWN

TABLE 1	
POSITIONS	COPLANARITY
-02 THRU -15	.0040[.102]
-16 THRU -36	.0060[.152]

**IN-PROCESS VIEW 1****IN-PROCESS VIEW 2**

UNLESS OTHERWISE SPECIFIED,
DIMENSIONS ARE IN INCHES.

TOLERANCES ARE:

DECIMALS ANGLES
.XX: $\pm .01$ [.3] 2°
.XXX: $\pm .005$ [.13]
.XXXX: $\pm .0020$ [.051]

PROPRIETARY NOTE

THIS DOCUMENT CONTAINS INFORMATION
CONFIDENTIAL AND PROPRIETARY TO
SAMTEC, INC. AND SHALL NOT BE REPRODUCED
OR TRANSFERRED TO OTHER DOCUMENTS OR
DISCLOSED TO OTHERS OR USED FOR ANY
PURPOSE OTHER THAN THAT WHICH IT WAS
OBTAINED WITHOUT THE EXPRESSED WRITTEN
CONSENT OF SAMTEC, INC.

MATERIAL:

DO NOT SCALE DRAWING
INSULATOR: ZYTEL HTNFR52G30NH, COLOR: NATURAL
ALTERNATE MATERIAL: THERMAX CG933
TERMINAL: PHOS BRONZE



F:\DWG\MISC\MKTG\HTST-1XX-01-XX-DV-XX-MKT.SLDDRW

SAMTEC

520 PARK EAST BLVD, NEW ALBANY, IN 47150
* PHONE: 812.944.6733 FAX: 812.948.5047
e-Mail: INFO@SAMTEC.COM CODE: 55322

DESCRIPTION:

HIGH TEMP TOP SHROUD

DWG. NO.

HTST-1XX-01-XX-DV-XX

BY: T. WERNE 07/11/2001 SHEET 1 OF 3




FIG. 2
-P: PICK & PLACE PAD OPTION
(SAME AS FIG. 1 UNLESS OTHERWISE STATED)






FIG. 3
-A: ALIGNMENT PIN OPTION
(SAME AS FIG. 1 UNLESS OTHERWISE STATED)

PROPRIETARY NOTE THIS DOCUMENT CONTAINS INFORMATION CONFIDENTIAL AND PROPRIETARY TO SAMTEC, INC. AND SHALL NOT BE REPRODUCED OR TRANSFERRED TO OTHER DOCUMENTS OR DISCLOSED TO OTHERS OR USED FOR ANY PURPOSE OTHER THAN THAT WHICH IT WAS OBTAINED WITHOUT THE EXPRESSED WRITTEN CONSENT OF SAMTEC, INC. DO NOT SCALE DRAWING SHEET SCALE: 2:1	SAMTEC 520 Park East Blvd. New Albany, IN 47151 Phone (812) 944-6733 Fax (812) 948-5047 e-Mail: INFO@SAMTEC.COM CODE: 55322	
	DESCRIPTION: HIGH TEMP TOP SHROUD	
	DWG. NO. HTST-1XX-01-XX-DV-XX	
	BY: T. WERNE 07/11/2001 SHEET 2 OF 3	




SECTION "B"-B"
SCALE 1:1

USER DIRECTION OF REELING
POCKET NOT DETAILED

TAPE & REEL VIEW

TUBE VIEW



TUBE: PT-1-24-02-08
PLUG: TP-13

PROPRIETARY NOTE

THIS DOCUMENT CONTAINS INFORMATION
CONFIDENTIAL AND PROPRIETARY TO
SAMTEC, INC. AND SHALL NOT BE REPRODUCED
OR TRANSFERRED TO OTHER DOCUMENTS OR
DISCLOSED TO OTHERS OR USED FOR ANY
PURPOSE OTHER THAN THAT WHICH IT WAS
OBTAINED WITHOUT THE EXPRESSED WRITTEN
CONSENT OF SAMTEC, INC.

DO NOT SCALE DRAWING

SHEET SCALE: 2:1

SAMTEC

520 Park East Blvd, New Albany, IN 47151
Phone (812) 944-6733 Fax (812) 948-5047
e-Mail: INFO@SAMTEC.COM CODE: 55322

DESCRIPTION: HIGH TEMP TOP SHROUD

DWG. NO. HTST-1XX-01-XX-DV-XX

BY: T. WERNE 07/11/2001 SHEET 3 OF 3

Mouser Electronics

Authorized Distributor

Click to View Pricing, Inventory, Delivery & Lifecycle Information:

[Samtec:](#)

[HTST-104-01-L-DV-TR](#)