

REVISION Z

DO NOT
SCALE FROM
THIS PRINT

NOTES:

- 1. REPRESENTS A CRITICAL DIMENSION.
- 2. ASSEMBLE GOLD PLATED END AS SHOWN.
- 3. TERMINAL PUSHOUT FORCE: 2 LBS BEFORE HEAT.
- 4. TERMINALS TO BE FLUSH TO .010[.25] BELOW TOP OF SHROUD.
- 5. MATES ONLY WITH SSW, SSQ, SSM, BCS, ESW, ESQ.

TABLE 1	
POSITIONS	COPLANARITY
-02 THRU -15	.0040[.102]
-16 THRU -36	.0060[.152]

HTSS-1XX-01-XX-DV-X-XX-X-XX

No OF POSITIONS
-02 THRU -36
(PER ROW)

LEAD STYLE
-01: SURFACE MOUNT
(USE T-1S6-08-XX-2)

PLATING SPECIFICATION
-T: MATTE TIN ON CONTACT AND TAIL
-S: 30μ" SELECTIVE GOLD IN CONTACT AREA, MATTE TIN ON TAIL
-L: 10μ" SELECTIVE GOLD IN CONTACT AREA, MATTE TIN ON TAIL
-H: 30μ" HEAVY GOLD IN CONTACT AREA, 3μ" ON TAIL
-TM: MATTE TIN ON CONTACT AREA AND TAIL
-SM: 30μ" SELECTIVE GOLD IN CONTACT AREA, MATTE TIN ON TAIL
-LM: 10μ" LIGHT SELECTIVE IN CONTACT AREA, MATTE TIN ON TAIL
-SS: 30μ" STRIP SELECTIVE ON CONTACT, MATTE TIN ON TAIL (SEE NOTE 5).




-TR: TAPE & REEL
(POSITIONS -02 THRU -25 ONLY)

-P: PICK & PLACE PAD
(USE PPP-22)


POLARIZATION OPTION
-XX: INDICATES POSITION OMITTED

-A: ALIGNMENT PIN (* ASO OPTION)
(FIG 3 SHT 2)


ROW SPECIFICATION
-DV: DOUBLE VERTICAL
(USE HTSS-XX-D)



IN-PROCESS 1



IN-PROCESS 2
HTSS-120-01-X-DV SHOWN





UNLESS OTHERWISE SPECIFIED,
DIMENSIONS ARE IN INCHES.
TOLERANCES ARE:
DECIMALS ANGLES
.XX: ±.01 [.3] 2°
.XXX: ±.005 [.13]
.XXXX: ±.0020 [.051]

PROPRIETARY NOTE
THIS DOCUMENT CONTAINS INFORMATION
CONFIDENTIAL AND PROPRIETARY TO
SAMTEC, INC. AND SHALL NOT BE REPRODUCED
OR TRANSFERRED TO OTHER DOCUMENTS OR
DISCLOSED TO OTHERS OR USED FOR ANY
PURPOSE OTHER THAN THAT WHICH IT WAS
OBTAINED WITHOUT THE EXPRESSED WRITTEN
CONSENT OF SAMTEC, INC.


MATERIAL: DO NOT SCALE DRAWING SHEET SCALE: 1:0.6666666666666667
INSULATOR:
LCP, UL 94 VO
COLOR: NATURAL
TERMINAL: PHOS BRONZE
F:\DWG\MISC\MKTG\HTSS-1XX-01-XX-DV-X-XX-X-XX-MKT.SLDDRW

samtec
520 PARK EAST BLVD, NEW ALBANY, IN 47150
PHONE: 812-944-6733 FAX: 812-948-5047
e-Mail: info@SAMTEC.com code: 55322

DESCRIPTION: HIGH TEMP TOP SHROUD
DWG. NO. HTSS-1XX-01-XX-DV-X-XX-X-XX
BY: T. WERNE 07/14/2001 SHEET 1 OF 2



PACKAGING VIEW



TUBE: PT-1-24-02-08
PLUG: TP-13

PROPRIETARY NOTE

THIS DOCUMENT CONTAINS INFORMATION
CONFIDENTIAL AND PROPRIETARY TO
SAMTEC, INC. AND SHALL NOT BE REPRODUCED
OR TRANSFERRED TO OTHER DOCUMENTS OR
DISCLOSED TO OTHERS OR USED FOR ANY
PURPOSE OTHER THAN THAT WHICH IT WAS
OBTAINED WITHOUT THE EXPRESSED WRITTEN
CONSENT OF SAMTEC, INC.

DO NOT SCALE DRAWING

SHEET SCALE: 1.5:1

samtec

520 PARK EAST BLVD, NEW ALBANY, IN 47150
PHONE: 812-944-6733 FAX: 812-948-5047
e-Mail: info@SAMTEC.com code: 55322

DESCRIPTION:

HIGH TEMP TOP SHROUD

DWG. NO.

HTSS-1XX-01-XX-DV-X-XX-X-XX

BY: T. WERNE

07/14/2001

SHEET 2 OF 2

Mouser Electronics

Authorized Distributor

Click to View Pricing, Inventory, Delivery & Lifecycle Information:

[Samtec:](#)

[HTSS-112-01-T-DV-P-TR](#) [HTSS-104-01-L-DV-P](#) [HTSS-112-01-T-DV-TR](#) [HTSS-120-01-S-DV-A-P](#)