# **OW-PROFILE** .025" SQ POST HEADER

(2.54 mm) .100" PITCH • TLW/MTLW SERIES

MTLW



BSW, CES, SLW, HLE

#### **FEATURES**

These headers provide the ultimate low-profile (0.64 mm) .025" square post board stacking system. The high quality Phosphor Bronze terminals are available with a standard short post height (TLW Series) for mating with low-profile sockets, or the post height can be Modified (MTLW Series) to accommodate IDC assemblies and other applications.

#### **SPECIFICATIONS**

Insulator Material: Black Liquid Crystal Polymer
Terminal Material: Phosphor Bronze

Phosphor Bronze
Plating:
Au or Sn over
50 µ" (1.27 µm) Ni
Current Rating (TLW/SLW): 5.2 A per pin (2 pins powered) **Operating Temp Range:** -55 °C to +105 °C with Tin -55 °C to +125 °C with Gold

#### **PROCESSING**

Lead-Free Solderable:

## **ALSO AVAILABLE**

Other platings Notch option


Some lengths, styles and options are non-standard, non-returnable. MTLW Series is non-standard, nonreturnable.





NO. PINS **PER ROW** 

> 01 thru 40 = Single Row

01 thru 36 = Double Row









#### **PLATING** STYLE OPTION

Specify LEAD **STYLE** from chart

> -G  $= 10 \mu''$  $(0.25 \ \mu m)$ Gold on post, Gold flash on tail

> > -T = Matte Tin

### ROW **OPTION**


**-** S = Single Gold flash Row on post, Matte Tin on tail

– D = Double Row

#### **OTHER OPTION**

-RA = Right-angle (-01 Lead Style only)

**-"XX"**= Polarized Position
Specify position for
omitted pin.



# NO. PINS PER ROW

01 thru 40

(2.54) .100 x No. of Positions

**◊** 

= Single Row

01 thru 36 = Double Row

#### **LEAD** STYLE

Specify LEAD **STYLE** from chart

## **PLATING**

-01


(1.52)

= Gold flash on post, Matte Tin on tail

= 10 µ" (0.25 µm) Gold on post, Matte Tin on tail

= 10 μ" (0.25 μm) Gold on post, Gold flash on tail

> -Т = Matte Tin



### **ROW** OPTION

**-** S

= Single Row – D = Double Row

# POST HEIGHT

-"XXX" = Post Height Dimension (In inches)

LEAD STYLE	OAL
-05	(8.51) .335
-06	(7.62) .300
-07	(10.92) .430
-08	(13.46) .530
-09	(18.54) .730
-10	(21.08) .830
-22	(16.00) .630
-23	(11.30) .445
-24	(12.19) .480

(2.48)

(1.52) .060

# **Mouser Electronics**

**Authorized Distributor** 

Click to View Pricing, Inventory, Delivery & Lifecycle Information:

Samtec:

TLW-107-05-T-D