



GSD



1.14 D.
REF.



GSD

REVISIONS		
ISSUE	CHANGES	
0	ER 35428 KH 04/13/95	
1	CN 39531 C AM 07/12/06	
2	CN 39576 E AM 08/16/06	
SCALE 2:1		
APPROX SURFACE AREA		
USED ON		
REF: KP-8012-737-400		
PLUG, BULKHEAD, TRI-LOC SERIAL DIGITAL		
DRAWN	KH	04/13/95
DESIGN	DW	08/17/95
APPR.	DATE	
 ROCK HILL, SOUTH CAROLINA 29730		
7702-2		

6. FINISHES:
 CENTER CONTACT-GOLD PLATE PER MIL-G-45204
 LOCKWASHER
 NUTS
 COLLET
 OUTER BODIES
 BODY RING
 ALL OTHER METAL PARTS-SILVER PLATE PER QQ-S-365
 } KINGS TARNISH RESISTANT NICKEL FINISH (TR-5)

7. ELECTRICAL CHARACTERISTICS:
 NOMINAL IMPEDANCE: 75 OHMS
 FREQUENCY RANGE: DC-500 MHZ
 VOLTAGE BREAKDOWN: CENTER CONDUCTOR/INNER GROUND: 1500 VRMS
 INNER GROUND/OUTER GROUND: 500 VRMS

MAY 2007 THIS DRAWING BECAME THE PROPERTY OF PROPERTY OF
WINCHESTER ELECTRONICS CORPORATION, WALLINGFORD, CT 06492

Mouser Electronics

Authorized Distributor

Click to View Pricing, Inventory, Delivery & Lifecycle Information:

[Winchester Interconnect:](#)

[7702-2](#)