

Weidmüller Interface GmbH & Co. KG Klingenbergstraße 26 D-32758 Detmold Germany

www.weidmueller.com

## **Product image**









Weidmüller's range of products includes end brackets that guarantee a permanent, reliable mounting on the terminal rail and prevent sliding. Versions with and without screws are available. The end brackets include marking options, also for group markers, and also a test plug holder.

### **General ordering data**

| Version    | W-Series, End bracket |
|------------|-----------------------|
| Order No.  | <u>1059000000</u>     |
| Туре       | WEW 35/1              |
| GTIN (EAN) | 4008190172282         |
| Qty.       | 50 pc(s).             |



Weidmüller Interface GmbH & Co. KG

Klingenbergstraße 26 D-32758 Detmold Germany

www.weidmueller.com

# **Technical data**

| -   |         |     |         |
|-----|---------|-----|---------|
| Dım | ensions | and | weights |
|     |         |     |         |

| Depth                            | 62.5 mm           | Depth (inches)                   | 2.461 inch       |
|----------------------------------|-------------------|----------------------------------|------------------|
| Height                           | 56 mm             | Height (inches)                  | 2.205 inch       |
| Width                            | 12 mm             | Width (inches)                   | 0.472 inch       |
| Net weight                       | 36.3 g            |                                  |                  |
| Temperatures                     |                   |                                  |                  |
|                                  |                   |                                  |                  |
| Continuous operating temp., min. | -50 °C            | Continuous operating temp., max. | 100 ℃            |
| Material data                    |                   |                                  |                  |
| Material                         | Wemid             | Colour                           | dark beige       |
| UL 94 flammability rating        | V-2               |                                  | dank bolge       |
| System specifications            |                   |                                  |                  |
| Version                          | For the terminals | Rail                             | TS 35            |
| Additional technical data        |                   |                                  |                  |
|                                  |                   |                                  |                  |
| Installation advice              | Direct mounting   | Interlock                        | for screw fixing |
| Type of mounting                 | when screwed in   |                                  |                  |
| Conductors for clamping (ra      | ated connection)  |                                  |                  |
| Tightening torque, max.          | 2.4 Nm            | Tightening torque, min.          | 1.2 Nm           |
| Dimensions                       |                   |                                  |                  |
| TS 35 offset                     | 28 mm             |                                  |                  |
| General                          |                   |                                  |                  |
| Installation advice              | Direct requestion | Rail                             | TS 35            |
| Classifications                  | Direct mounting   | ndii                             | 15 55            |
| Classifications                  |                   |                                  |                  |
| ETIM 6.0                         | EC001041          | ETIM 7.0                         | EC001041         |
| ETIM 8.0                         | EC001041          | ECLASS 9.0                       | 27-14-11-35      |
| ECLASS 9.1                       | 27-14-11-35       | ECLASS 10.0                      | 27-14-11-35      |
| ECLASS 11.0                      | 27-14-11-35       |                                  |                  |
| Approvals                        |                   |                                  |                  |
| ROHS                             | Conform           |                                  |                  |
| Downloads                        |                   |                                  |                  |
|                                  |                   |                                  |                  |
| Engineering Data                 | CAD data – STEP   |                                  |                  |
| F : D :                          | EDIANIAMONAD 7 I  | E0.0                             |                  |

Engineering Data
User Documentation

Catalogues

Brochures

EPLAN, WSCAD, Zuken E3.S

Catalogues in PDF-format

 $\underline{Storage Conditions Terminal Blocks}$ 



Weidmüller Interface GmbH & Co. KG

Klingenbergstraße 26 D-32758 Detmold Germany

www.weidmueller.com

# Accessories

#### **Blank**



The Dekafix (DEK) marker is the universal marker for all conductor and plug-in connectors as well as for electronic sub-assemblies. The system is ideal for short number sequences and covers a wide range of ready-printed markers.

Strips for fast installation in only one work step. The printing is easy to read, rich in contrast and available in various widths.

- · Large range of ready-to-use markers
- Strips for fast installation
- Terminal markers, suitable for all Weidmüller cable connectors
- Available as blank MultiCard or with standard printing

**For custom printing:** Please send us a file of our labeling software M-Print PRO or M-Print PRO Online (without installation) for your labeling specifications.

#### **General ordering data**

| Туре       | DEK 5/5 MC NE WS |
|------------|------------------|
| Order No.  | 1609801044       |
| GTIN (EAN) | 4008190397111    |
| Qty.       | 1,000 pc(s).     |

Version

Dekafix, Terminal marker, 5 x 5 mm, Pitch in mm (P): 5.00

Weidmueller, white

#### SchT group marker carrier



The SchT 5 S group tag carriers are clipped directly onto the TS 32 mounting rail (G-rail) or the TS 35 mounting rail (top-hat rail). It is therefore possible to label the terminal strip irrespective of the terminal and the type of terminal. SchT 5 and SchT 5 S are fitted with ESO 5, STR 5 protective strips.

The SchT 7 is a hinged group tag carrier for inlay tags which enables easy access to the clamping screw. The SchT 7 is fitted with ESO 7, STR 7 protective strips or DFK 5.

Inlay tags and protective strips can be found under "Accessories".

### **General ordering data**

 Type
 SCHT 7
 Version

 Order No.
 0517960000
 SCHT, Terminal marker, 39.3 x 8 mm, Pitch in mm (P): 7.00

 GTIN (EAN)
 4008190001742
 Weidmueller, white

 Qty.
 20 pc(s).



Weidmüller Interface GmbH & Co. KG

Klingenbergstraße 26 D-32758 Detmold Germany

www.weidmueller.com

# Accessories

#### **Blank**



WS markers are the perfect match for the W-series connectors. Thanks to their system compatibility, the WS tags can also be used with the I-series and the Z-series. The large marking surfaces do not only permit long character strings but also multi-line text. WS markers are ideal for labels with long, customised character strings. Thanks to the proven MultiCard format, printing with PrintJet CONNECT oder/or Plotter is possible.

- · Can be fitted in strips or individually
- · Markers in proven MultiCard format

**For custom printing:** Please send us a file of our labeling software M-Print PRO or M-Print PRO Online (without installation) for your labeling specifications.

#### **General ordering data**

Type WS 12/5 MC NE WS
Order No. 1609860000
GTIN (EAN) 4008190203481
Oty. 720 pc(s).

Version

WS, Terminal marker, 12 x 5 mm, Pitch in mm (P): 5.00 Weidmueller,

Allen-Bradley, white

#### WS 12/5



#### WS/ DEK

MultiMark terminal markers use an innovative composite material made from two components. The hard base contour of the marker snaps securely into the connector. The elastic surface finish makes the marker easy to mount. This specially punched material enables the strips to be stretched to accommodate the slight variations in spacing that tend to add up, especially with long terminal blocks. Another advantage: the excellent printability of the surface material guarantees durable and wear-resistant labelling. A print resolution of 300 dpi also produces a very legible script.

#### Your benefits with MultiMark

- Firm hold and durable printing
- · Continuous strips save installation time
- Easy mounting thanks to an innovative composite material
- · Large label field for optimal legibility
- · High flexibility thanks to manufacturer independence

#### **General ordering data**

Type WS 12/5 MM WS
Order No. 2007190000
GTIN (EAN) 4050118392036
Qty. 800 pc(s).

Version

WS, Terminal marker, 12 x 5 mm, Weidmueller, white

# **Mouser Electronics**

**Authorized Distributor** 

Click to View Pricing, Inventory, Delivery & Lifecycle Information:

<u>Weidmuller</u>: 1059000000