

### Weidmüller Interface GmbH & Co. KG

Klingenbergstraße 26 D-32758 Detmold Germany

www.weidmueller.com

### **Product image**





Weidmüller's range of products includes end brackets that guarantee a permanent, reliable mounting on the terminal rail and prevent sliding. Versions with and without screws are available. The end brackets include marking options, also for group markers, and also a test plug holder.

Version	W-Series, End bracket
Order No.	<u>1061200000</u>
Туре	WEW 35/2
GTIN (EAN)	4008190030230
Qty.	50 pc(s).

# **Technical data**



### Weidmüller Interface GmbH & Co. KG

Klingenbergstraße 26 D-32758 Detmold Germany

www.weidmueller.com

ECLASS 11.0       27-14-11-35         Approvals       Conform         ROHS       Conform         Downloads       Engineering Data         Engineering Data       CAD data – STEP         Engineering Data       EPLAN, WSCAD, Zuken E3.S         User Documentation       StorageConditionsTerminalBlocks         Catalogues       Catalogues in PDF-format	Denth	40 5		1.001
Width     8 mm     Width (inches)     0.315 inch       Net weight     14.04 g     Width (inches)     0.315 inch       Temperatures     Continuous operating temp., min.     -50 °C     Continuous operating temp., max.     100 °C       Material     Wemid     Colour     dark beige       UL 94 flammability rating     HB     Colour     dark beige       System specifications     Version     For the terminals     Rail     TS 35       Additional technical data     Interlock     for screw fin       Installation advice     Direct mounting     Interlock     for screw fin       Snap-on     No     Type of mounting     when screw       With snapin pegs     No     Type of mounting     when screw       Conductors for clamping (rated connection)     Tightening torque, min.     0.5 Nm       Dimensions     28 mm     General     State       S13 offset     28 mm     Ecolo1041     ETIM 7.0     Ecol01041       ETIM 6.0     ECO01041     ECLASS 9.0     27-14-11-35       EcLASS 9.1     27-14-11-35     EcLASS 9.0     27-14-11-35       Approvals     Conform     EclASS 9.0     27-14-11-35       RoHS     Conform     Eplanewing Data     CAD data = STEP       Engineering Data     CAD data = S				
Net weight       14.04 g         Temperatures         Continuous operating temp,, min.       -50 °C       Continuous operating temp,, max.       100 °C         Material data       Material data       Colour       dark beige         UL 94 flammability rating       HB       Colour       dark beige         System specifications       For the terminals       Rail       TS 35         Additional technical data       Interlock       for screw.fn         Installation advice       Direct mounting       Interlock       for screw.fn         Snapon       No       Type of mounting       when screw         With snap-in pegs       No       Type of mounting       when screw         Conductors for clamping (rated connection)       Tightening torque, min.       0.5 Nm         Dimensions       Its 35 offset       28 mm       General         Sta 5 offset       28 mm       Ectass 9.0       2.7 14 11.3         Classifications       ECtASS 9.0       2.7 14 11.3       ECLASS 9.0       2.7 14 11.3         ECLASS 9.1       2.7 14 11.35       ECLASS 9.0       2.7 14 11.3       ECLASS 9.0       2.7 14 11.3         Material dation advice       Direct mounting       ECLASS 9.0       2.7 14 11.3       ECLASS 9.0       2.7				
Femperatures         Continuous operating temp,, min.       -50 °C       Continuous operating temp,, max.       100 °C         Material data       Wamid       Colour       dark beige         Material dy flammability rating       HB       Colour       dark beige         System specifications       HB       System specifications       ark beige         Version       For the terminals       Rail       TS 35         Additional technical data       Interlock       for screw finition advice       for screw finition advice         Shapon       No       Type of mounting       when screw         Additional technical data       Top of mounting       when screw         Shapon       No       Type of mounting       when screw         Conductors for clamping (rated connection)       Tightening torque, min.       0.5 Nm         Dimensions       E       28 mm       E         Sta offset       28 mm       E       E         General       E       E       E       E         Installation advice       Direct mounting       Rail       TS 35       E         Class 9.1       2.714.11.35       E       CLASS 9.0       2.714.11.35         Approvals       E       E			Width (inches)	0.315 inch
Continuous operating temp., min.       -50 °C       Continuous operating temp., max.       100 °C         Waterial data       Wamid       Colour       dark beige         JL 94 flammability rating       HB       Colour       dark beige         System specifications       HB       Colour       dark beige         Version       For the terminals       Rail       TS 35         Additional technical data       Interlock       for screw fis         Installation advice       Direct mounting       Interlock       for screw fis         Snap-on       No       Type of mounting       when screw         Vith snap-in pegs       No       Type of mounting       when screw         Conductors for clamping (rated connection)       Conductors for clamping (rated connection)       Conductors for clamping (rated connection)         Fightening torque, max.       1 Nm       Tightening torque, min.       0.5 Nm         Dimensions       ES 35 offset       28 mm       Classifications         ETIM 6.0       EC001041       ETIM 7.0       EC001041         ETIM 8.0       EClass 9.0       27-14-11-35       CLASS 9.0       27-14-11-35         CLASS 9.1       27-14-11-35       ECLASS 9.0       27-14-11-35       CLASS 9.0       27-14-11-35	Net weight	14.04 g		
Atterial data         Atterial data         Atterial data         Atterial L 94 flammability rating       HB         System specifications         Version       For the terminals         Fersion       For the terminals         Rail       TS 35         Additional technical data         Installation advice       Direct mounting         Interlock       for screw fining-on         No       Type of mounting         when screw       Type of mounting         With snap-in pegs       No         Conductors for clamping (rated connection)       Tightening torque, min.       0.5 Nm         Dimensions       S 35 offset       28 mm       Signeral         Sisteneral       Sisteneral       Sisteneral       Sisteneral         TIM 6.0       EC001041       ETIM 7.0       EC001041         TIM 6.0       EC001041       ECLASS 9.0       27.14-11-35         CLASS 9.1       27.14-11-35       ECLASS 10.0       27.14-11-35         Approvals       Conform       Some Size Size Size Size Size Size Size Siz	emperatures			
Material Wemid dark beige JL 94 flammability rating HB System specifications Version For the terminals Rail TS 35 Additional technical data Installation advice Direct mounting Interlock for screw for Snap-on No Type of mounting when screw With snap-in pegs No Conductors for clamping (rated connection) Tightening torque, max. 1 Nm Tightening torque, min. 0.5 Nm Dimensions TS 35 offset 28 mm General Installation advice Direct mounting Rail TS 35 Classifications ETIM 6.0 EC001041 ECLASS 9.0 27-14-11-3 ECLASS 9.1 27-14-11-35 ECLASS 9.1 27-14-11-35 ECLASS 9.1 27-14-11-35 Approvals Approvals Conform Downloads Engineering Data CAD data – STEP Engineering Data EPLAN, WSCAD, Zuken E3.5 Joar Documentation StorageConditionsTerminalBlocks Satalogues Catalogues in PO-format	Continuous operating temp., min.	-50 °C	Continuous operating temp., max.	100 °C
JL 94 flammability rating     HB       System specifications     For the terminals     Rail     TS 35       Additional technical data     Interlock     for screw file       installation advice     Direct mounting     Interlock     for screw file       installation advice     Direct mounting     Interlock     for screw file       installation advice     Direct mounting     Interlock     for screw file       Conductors for clamping (rated connection)     Tightening torque, min.     0.5 Nm       Dimensions     28 mm     Seneral	Naterial data			
JL 94 flammability rating       HB         System specifications         Version       For the terminals       Rail       TS 35         Additional technical data       Interlock       for screw file         Installation advice       Direct mounting       Interlock       for screw file         Installation advice       Direct mounting       Interlock       for screw file         Snap-on       No       Type of mounting       when screw         Conductors for clamping (rated connection)       Interlock       for screw file         Dimensions       28 mm       Secondational technical for screw       for screw file         Signeperal       28 mm       Secondational technical for screw       for screw file         General       Direct mounting       Rail       TS 35         Classifications       ETIM 5.0       EC001041       ETIM 7.0       EC001041         ETIM 8.0       EC001041       ECLASS 9.0       27-14-11-35         Class 11.0       27-14-11-35       ECLASS 9.0       27-14-11-35         Approvals       Canform       Sonform       Sonform         Downloads       Canform       Sonform       Sonform         Sonform       Conform       Sonform       Sonform       Sonform	Material	Wemid	Colour	dark beige
System specifications         Version       For the terminals       Rail       TS 35         Additional technical data         Installation advice       Direct mounting       Interlock       for screw fb         Snap-on       No       Type of mounting       when screw         With snap-in pegs       No       Type of mounting       when screw         Conductors for clamping (rated connection)       Tightening torque, min.       0.5 Nm         Dimensions       1 Nm       Tightening torque, min.       0.5 Nm         Dimensions       28 mm       General       State       28 mm         Installation advice       Direct mounting       Rail       TS 35         Classifications       ETIM 6.0       EC001041       ETIM 7.0       EC001041         ETIM 6.0       EC001041       ECLASS 9.0       27-14-11-35         CLASS 9.1       27-14-11-35       ECLASS 9.0       27-14-11-35         Approvals       RoHs       Conform       ECLASS 10.0       27-14-11-35         BOHS       Conform       Engineering Data       CAD data – STEP       Engineering Data       EPLAN, WSCAD, Zuken E3.S       User Documentation       StorageConditionsTerminalBlocks       User Documentation       StorageConditionsTerminalBlocks <td></td> <td></td> <td></td> <td>uark beige</td>				uark beige
Version       For the terminals       Rail       TS 35         Additional technical data       Interlock       for screw fit         installation advice       Direct mounting       Interlock       for screw fit         Snap-on       No       Type of mounting       when screw         With snap-in pegs       No       Type of mounting       when screw         Conductors for clamping (rated connection)       Tightening torque, min.       0.5 Nm         Dimensions       INM       Tightening torque, min.       0.5 Nm         Dimensions       28 mm       General       Sister 28 mm         General       Direct mounting       Rail       TS 35         Classifications       EC001041       ETIM 7.0       EC001041         ETIM 6.0       EC001041       ECLASS 9.0       27-14-11-35         Class 9.1       27-14-11-35       ECLASS 9.0       27-14-11-35         Approvals       Conform       Conform       Conform         Downloads       Conform       Engineering Data       CAD data – STEP         Engineering Data       CAD data – STEP       Engineering Data       StorageConditionsTerminalBlocks         Sate Documentation       StorageConditionsTerminalBlocks       Jaetalogues       Catalogues in DeF-format <td></td> <td></td> <td></td> <td></td>				
Additional technical data       Direct mounting       Interlock       for screw fib         inap-on       No       Type of mounting       when screw         With snap-in pegs       No       Conductors for clamping (rated connection)       when screw         Conductors for clamping (rated connection)       Tightening torque, min.       0.5 Nm         Dimensions       1 Nm       Tightening torque, min.       0.5 Nm         Dimensions       28 mm       Seneral       Seneral         General       Direct mounting       Rail       TS 35         Classifications       ETIM 7.0       EC001041       EC045S 9.0       27-14-11-35         Class 9.1       27-14-11-35       ECLASS 10.0       27-14-11-35         Approvals       Conform       Seneral       Seneral       Seneral         NOH       Conform       Colondu1       ECLASS 9.0       27-14-11-35         Class 11.0       27-14-11-35       ECLASS 10.0       27-14-11-35         Approvals       Conform       Sonform       Sonform         Downloads       Catalogues in PDE-format       SitrageConditionsTerminalBlocks       SitrageConditionsTerminalBlocks         Satalogues       Catalogues in PDE-format       SitrageConditionsTerminalBlocks       SitrageConditionsTerminalBlo	System specifications			
Installation advice Direct mounting No Vortice for screw fix Snap-on No Vortice for clamping (rated connection) Type of mounting when screw fix Snap-in pegs No Conductors for clamping (rated connection) Tightening torque, max. 1 Nm Tightening torque, min. 0.5 Nm Dimensions TS 35 offset 28 mm General Installation advice Direct mounting Rail TS 35 Classifications ETIM 6.0 EC001041 ETIM 7.0 EC001041 ETIM 8.0 EC001041 ETIM 7.0 EC001041 ETIM 8.0 EC001041 ECLASS 9.0 27-14-11-3 ECLASS 9.1 27-14-11-35 ECLASS 11.0 27-14-11-35 Approvals R0HS Conform Downloads Engineering Data CAD data – STEP Engineering Data EPLAN, WSCAD, Zuken E3.S User Documentation StorageConditionsTerminalBlocks Catalogues Catalogues in PDF-format	Version	For the terminals	Rail	TS 35
Snap-on       No       Type of mounting       when screw         With snap-in pegs       No       Tightening torque, min.       0.5 Nm         Conductors for clamping (rated connection)       Tightening torque, min.       0.5 Nm         Tightening torque, max.       1 Nm       Tightening torque, min.       0.5 Nm         Dimensions       State 28 mm       State 28 mm       State 28 mm         General       Direct mounting       Rail       TS 35         Classifications       ETIM 7.0       EC001041       ETIM 7.0       EC001041         ETIM 8.0       EC001041       ETIM 7.0       EC001041         ECLASS 9.1       27-14-11-35       ECLASS 9.0       27-14-11-35         Approvals       Conform       StrageConform       StrageConform         Downloads       Catalogues in PDF-format       User Documentation       StorageConditionsTerminalBlocks	Additional technical data			
Snap-on       No       Type of mounting       when screw         With snap-in pegs       No       Tightening torque, min.       0.5 Nm         Conductors for clamping (rated connection)       Tightening torque, min.       0.5 Nm         Tightening torque, max.       1 Nm       Tightening torque, min.       0.5 Nm         Dimensions       State       28 mm       State       State       State         General       Direct mounting       Rail       TS 35       State       State       State         ETIM 6.0       EC001041       ETIM 7.0       EC001041       ECLASS 9.0       27-14-11-35         ECLASS 9.1       27-14-11-35       ECLASS 10.0       27-14-11-35       ECLASS 10.0       27-14-11-35         Approvals       Conform       Conform       Engineering Data       CAD data – STEP       Engineering Data       EPLAN, WSCAD, Zuken E3.S       User Documentation       StorageConditionsTerminalBlocks       Catalogues       Catalogues       Catalogues in PDF-format	ha she lla ki su sa ki sa	Direct as constinue	laste also also	fan a successfin in s
With snap-in pegs       No         Conductors for clamping (rated connection)         Tightening torque, max.       1 Nm       Tightening torque, min.       0.5 Nm         Dimensions       TS 35 offset       28 mm         General       Installation advice       Direct mounting       Rail       TS 35         Classifications       ETIM 7.0       EC001041       EC001041         ETIM 8.0       EC001041       ECLASS 9.0       27-14-11-35         ECLASS 9.1       27-14-11-35       ECLASS 9.0       27-14-11-35         Approvals       ROHS       Conform       Conform         Downloads       Conform       Engineering Data       CAD data – STEP         Engineering Data       CAD data – STEP       Engineering Data       EPLAN, VISCAD, Zuken E3.S         User Documentation       StorageConditionsTerminalBlocks       Catalogues in PDF-format				
Conductors for clamping (rated connection)         Tightening torque, max.       1 Nm       Tightening torque, min.       0.5 Nm         Dimensions         IS 35 offset       28 mm         General         Installation advice       Direct mounting       Rail       TS 35         Classifications         ETIM 6.0       EC001041       ETIM 7.0       EC001041         ETIM 8.0       EC001041       ECLASS 9.0       27-14-11-35         ECLASS 9.1       27-14-11-35       ECLASS 10.0       27-14-11-35         Approvals       Conform       ECMS       Conform         BOWNloads       Conform       Engineering Data       CAD. data – STEP       Engineering Data       EPLAN, VWSCAD, Zuken E3.S       User Documentation       StorageConditionsTerminalBlocks       Catalogues in PDF-format				when screwed i
Fightening torque, max.       1 Nm       Tightening torque, min.       0.5 Nm         Dimensions       28 mm	vititi shap-iti pegs	INO		
Dimensions TS 35 offset 28 mm General Installation advice Direct mounting Rail TS 35 Classifications ETIM 6.0 EC001041 ETIM 7.0 EC001041 ETIM 8.0 EC001041 ECLASS 9.0 27-14-11-3 ECLASS 9.1 27-14-11-35 ECLASS 11.0 27-14-11-35 Approvals R0HS Conform Downloads Engineering Data CAD data – STEP Engineering Data EPLAN, WSCAD, Zuken E3.5 User Documentation StorageConditionsTerminalBlocks Catalogues Catalogues in PDF-format	Conductors for clamping (ra	ated connection)		
TS 35 offset 28 mm  General  Installation advice Direct mounting Rail TS 35  Classifications  ETIM 6.0 EC001041 ETIM 7.0 EC001041 ETIM 8.0 EC001041 ETIM 7.0 EC001041 ETIM 8.0 EC001041 ECLASS 9.0 27-14-11-3 ECLASS 9.1 27-14-11-35 ECLASS 11.0 27-14-11-35  Approvals  ROHS Conform  Downloads  Engineering Data CAD data – STEP Engineering Data EPLAN, WSCAD, Zuken E3.S User Documentation StorageConditionsTerminalBlocks Catalogues Catalogues in PDE-format	Tightening torque, max.	1 Nm	Tightening torque, min.	0.5 Nm
General         Installation advice       Direct mounting       Rail       TS 35         Classifications       EC001041       ETIM 7.0       EC001041         ETIM 6.0       EC001041       ECLASS 9.0       27-14-11-3         ECLASS 9.1       27-14-11-35       ECLASS 10.0       27-14-11-3         ECLASS 11.0       27-14-11-35       ECLASS 10.0       27-14-11-3         Approvals       Conform       Engineering Data       CAD data – STEP         Engineering Data       EPLAN, WSCAD, Zuken E3.S       User Documentation       StorageConditionsTerminalBlocks         Catalogues       Catalogues in PDF-format       Engineering Data       Engineering Data       Engineering Data	Dimensions			
Installation advice Direct mounting Rail TS 35 Classifications ETIM 6.0 EC001041 ETIM 8.0 EC001041 ETIM 8.0 EC001041 ETIM 8.0 EC001041 ECLASS 9.0 27-14-11-35 ECLASS 9.1 27-14-11-35 ECLASS 10.0 27-14-11-3 EC	TS 35 offset	28 mm		
Classifications         ETIM 6.0       EC001041       ETIM 7.0       EC001041         ETIM 8.0       EC001041       ECLASS 9.0       27-14-11-3         ECLASS 9.1       27-14-11-35       ECLASS 10.0       27-14-11-3         ECLASS 11.0       27-14-11-35       ECLASS 10.0       27-14-11-3         Approvals       Conform       Conform       Conform         Downloads         Engineering Data       CAD data – STEP         Engineering Data       EPLAN, WSCAD, Zuken E3.S       User Documentation         StorageConditionsTerminalBlocks       Catalogues in PDF-format	General			
ETIM 6.0EC001041ETIM 7.0EC001041ETIM 8.0EC001041ECLASS 9.027-14-11-3ECLASS 9.127-14-11-35ECLASS 10.027-14-11-3ECLASS 11.027-14-11-35ECLASS 10.027-14-11-3ApprovalsROHSConformDovvnloadsEngineering DataCAD data - STEPEngineering DataEPLAN, WSCAD, Zuken E3.SUser DocumentationStorageConditionsTerminalBlocksCataloguesCatalogues in PDF-format	Installation advice	Direct mounting	Rail	TS 35
ETIM 8.0       EC001041       ECLASS 9.0       27-14-11-3         ECLASS 9.1       27-14-11-35       ECLASS 10.0       27-14-11-3         ECLASS 11.0       27-14-11-35       ECLASS 10.0       27-14-11-3         Approvals       Conform       Engineering Data       CAD data – STEP         Engineering Data       EPLAN, WSCAD, Zuken E3.S       User Documentation       StorageConditionsTerminalBlocks         Catalogues       Catalogues in PDF-format       Catalogues in PDF-format       Context and c	Classifications			
ETIM 8.0       EC001041       ECLASS 9.0       27-14-11-3         ECLASS 9.1       27-14-11-35       ECLASS 10.0       27-14-11-3         ECLASS 11.0       27-14-11-35       ECLASS 10.0       27-14-11-3         Approvals       Conform       Engineering Data       CAD data – STEP         Engineering Data       EPLAN, WSCAD, Zuken E3.S       User Documentation       StorageConditionsTerminalBlocks         Catalogues       Catalogues in PDF-format       Catalogues in PDF-format       Conformat				
ECLASS 9.1       27-14-11-35       ECLASS 10.0       27-14-11-3         ECLASS 11.0       27-14-11-35       Approvals       Image: Conform       Image: Conform         ROHS       Conform       Image: Co				
ECLASS 11.0       27-14-11-35         Approvals       Conform         ROHS       Conform         Downloads       Engineering Data         Engineering Data       CAD data – STEP         Engineering Data       EPLAN, WSCAD, Zuken E3.S         Jser Documentation       StorageConditionsTerminalBlocks         Catalogues       Catalogues in PDF-format			FCLASS 9.0	27-14-11-35
Approvals         ROHS       Conform         Downloads         Engineering Data       CAD data – STEP         Engineering Data       EPLAN, WSCAD, Zuken E3.S         Jser Documentation       StorageConditionsTerminalBlocks         Catalogues       Catalogues in PDF-format	ETIM 8.0			07 4 4 4 4 05
ROHS     Conform       Downloads       Engineering Data     CAD data – STEP       Engineering Data     EPLAN, WSCAD, Zuken E3.S       Jser Documentation     StorageConditionsTerminalBlocks       Catalogues     Catalogues in PDF-format	ETIM 8.0 ECLASS 9.1	27-14-11-35		27-14-11-35
Downloads         Engineering Data       CAD data – STEP         Engineering Data       EPLAN, WSCAD, Zuken E3.S         Jser Documentation       StorageConditionsTerminalBlocks         Catalogues       Catalogues in PDF-format	ETIM 8.0 ECLASS 9.1	27-14-11-35		27-14-11-35
Engineering Data       CAD data – STEP         Engineering Data       EPLAN, WSCAD, Zuken E3.S         User Documentation       StorageConditionsTerminalBlocks         Catalogues       Catalogues in PDF-format	ETIM 8.0 ECLASS 9.1 ECLASS 11.0	27-14-11-35		27-14-11-35
Engineering Data         EPLAN, WSCAD, Zuken E3.S           User Documentation         StorageConditionsTerminalBlocks           Catalogues         Catalogues in PDF-format	ETIM 8.0 ECLASS 9.1 ECLASS 11.0 <b>Approvals</b>	27-14-11-35 27-14-11-35		27-14-11-35
Engineering Data         EPLAN, WSCAD, Zuken E3.S           User Documentation         StorageConditionsTerminalBlocks           Catalogues         Catalogues in PDF-format	ETIM 8.0 ECLASS 9.1 ECLASS 11.0 Approvals	27-14-11-35 27-14-11-35		27-14-11-35
User Documentation         StorageConditionsTerminalBlocks           Catalogues         Catalogues in PDF-format	ETIM 8.0 ECLASS 9.1 ECLASS 11.0 Approvals ROHS Downloads	27-14-11-35 27-14-11-35 Conform		27-14-11-35
Catalogues Catalogues in PDF-format	ETIM 8.0 ECLASS 9.1 ECLASS 11.0 Approvals ROHS Downloads Engineering Data	27-14-11-35 27-14-11-35 Conform <u>CAD data – STEP</u>	ECLASS 10.0	27-14-11-35
	ETIM 8.0 ECLASS 9.1 ECLASS 11.0 Approvals ROHS Downloads Engineering Data Engineering Data	27-14-11-35 27-14-11-35 Conform <u>CAD data – STEP</u> EPLAN, WSCAD, Zuken	ECLASS 10.0	27-14-11-35
Brochures	ETIM 8.0 ECLASS 9.1 ECLASS 11.0 Approvals ROHS Downloads Engineering Data Engineering Data User Documentation	27-14-11-35 27-14-11-35 Conform <u>CAD data – STEP</u> <u>EPLAN, WSCAD, Zuken</u> StorageConditionsTerm	ECLASS 10.0	27-14-11-35

Creation date January 12, 2022 4:09:56 PM CET

Catalogue status 17.12.2021 / We reserve the right to make technical changes.

# Accessories

### SchT group marker carrier



Weidmüller 🔀

### Weidmüller Interface GmbH & Co. KG

Klingenbergstraße 26 D-32758 Detmold Germany

www.weidmueller.com

The SchT 5 S group tag carriers are clipped directly onto the TS 32 mounting rail (G-rail) or the TS 35 mounting rail (top-hat rail). It is therefore possible to label the terminal strip irrespective of the terminal and the type of terminal. SchT 5 and SchT 5 S are fitted with ESO 5, STR 5 protective strips.

The SchT 7 is a hinged group tag carrier for inlay tags which enables easy access to the clamping screw. The SchT 7 is fitted with ESO 7, STR 7 protective strips or DEK 5.

Inlay tags and protective strips can be found under "Accessories".

### **General ordering data**

Туре	SCHT 7	Version
Order No.	<u>0517960000</u>	SCHT, Terminal marker, 39.3 x 8 mm, Pitch in mm (P): 7.00
GTIN (EAN)	4008190001742	Weidmueller, white
Qty.	20 pc(s).	

### Blank



WS markers are the perfect match for the W-series connectors. Thanks to their system compatibility, the WS tags can also be used with the I-series and the Zseries. The large marking surfaces do not only permit long character strings but also multi-line text. WS markers are ideal for labels with long, customised character strings. Thanks to the proven MultiCard format, printing with PrintJet CONNECT oder/or Plotter is possible.

- Can be fitted in strips or individually
- Markers in proven MultiCard format

**For custom printing:** Please send us a file of our labeling software M-Print PRO or M-Print PRO Online (without installation) for your labeling specifications.

Туре	WS 12/5 MC NE WS	Version
Order No.	<u>1609860000</u>	WS, Terminal marker, 12 x 5 mm, Pitch in mm (P): 5.00 Weidmueller,
GTIN (EAN)	4008190203481	Allen-Bradley, white
Qty.	720 pc(s).	

# Accessories

### Blank

12	LL	EI		L	L	1
E	LL	Ŀ		L	L	
	T.T	1.1	.1	1.	1	1
E	TT	11	1	1		1
1	TT	L	1	1.	E	1
E	TT	1.1	1	Т.	1	1
E	11	1.1	1	1.	1	1
	TT	1.1	T	1	1	1
E	11	11		Т	1	
10	TT	II	1	T	Γ	1



### Weidmüller Interface GmbH & Co. KG

Klingenbergstraße 26 D-32758 Detmold Germany

www.weidmueller.com

The Dekafix (DEK) marker is the universal marker for all conductor and plug-in connectors as well as for electronic sub-assemblies. The system is ideal for short number sequences and covers a wide range of ready-printed markers.

Strips for fast installation in only one work step. The printing is easy to read, rich in contrast and available in various widths.

- Large range of ready-to-use markers
- Strips for fast installation
- Terminal markers, suitable for all Weidmüller cable connectors
- · Available as blank MultiCard or with standard printing

**For custom printing:** Please send us a file of our labeling software M-Print PRO or M-Print PRO Online (without installation) for your labeling specifications.

### **General ordering data**

	0	
Туре	DEK 5/8 MC NE WS	Version
Order No.	<u>1856740000</u>	Dekafix, Terminal marker, 5 x 8 mm, Pitch in mm (P): 8.00
GTIN (EAN)	4032248400850	Weidmueller, white
Qty.	800 pc(s).	

### Blank



The WAD connector marker is suitable for W-series terminals and for the WEW 35/2 and ZEW 35/2 end brackets. The markers are available as blank markers, with custom printing or standard print with lightning symbol. The WAD MultiCard markers are suitable for labelling with PrintJet CONNECT printers.

**For custom printing:** Please send us a file of our labeling software M-Print PRO or M-Print PRO Online (without installation) for your labeling specifications.

### **General ordering data**

Туре	WAD 8 MC NE WS	Version
Order No.	<u>1112940000</u>	Group markers, Cover, 33.3 x 8 mm, Pitch in mm (P): 8.00 white
GTIN (EAN)	4032248891825	
Qty.	48 pc(s).	

Creation date January 12, 2022 4:09:56 PM CET

## Accessories

WS 12/5





### Weidmüller Interface GmbH & Co. KG

Klingenbergstraße 26 D-32758 Detmold Germany

www.weidmueller.com

### WS/ DEK

MultiMark terminal markers use an innovative composite material made from two components. The hard base contour of the marker snaps securely into the connector. The elastic surface finish makes the marker easy to mount. This specially punched material enables the strips to be stretched to accommodate the slight variations in spacing that tend to add up, especially with long terminal blocks. Another advantage: the excellent printability of the surface material guarantees durable and wearresistant labelling. A print resolution of 300 dpi also produces a very legible script. **Your benefits with MultiMark** 

# • Firm hold and durable printing

- Continuous strips save installation time
- Easy mounting thanks to an innovative composite material
- Large label field for optimal legibility
- · High flexibility thanks to manufacturer independence

### General ordering data

Туре	WS 12/5 MM WS	Version
Order No.	<u>2007190000</u>	WS, Terminal marker, 12 x 5 mm, Weidmueller, white
GTIN (EAN)	4050118392036	
Qty.	800 pc(s).	

### With lightning flash



The WAD connector marker is suitable for W-series terminals and for the WEW 35/2 and ZEW 35/2 end brackets. The markers are available as blank markers, with custom printing or standard print with lightning symbol. The WAD MultiCard markers are suitable for labelling with PrintJet CONNECT printers.

**For custom printing:** Please send us a file of our labeling software M-Print PRO or M-Print PRO Online (without installation) for your labeling specifications.

Туре	WAD 8 MC B GE/SW	Version
Order No.	<u>1120470000</u>	Group markers, Cover, 33.3 x 8 mm, Pitch in mm (P): 8.00 yellow
GTIN (EAN)	4032248901289	
Qty.	48 pc(s).	

## Accessories

Accessories





### Weidmüller Interface GmbH & Co. KG Klingenbergstraße 26

D-32758 Detmold Germany

www.weidmueller.com

### Potential-distribution modules; system accessory

A wide range of accessory modules is available for individual requirements of machine and plant engineering. Various potential distribution modules are available for the supply of sensors with 2- to 4-wire connection technology directly from the remote I/O system. These offer 16 "PUSH IN" potential points and supply your application with any auxiliary potential available. An empty module, where the system bus and voltage supply are looped through, allows you to plan expansion slots in a system and to start these up without any interruptions if required.

### **General ordering data**

 Type
 EM 8/30

 Order No.
 1806120000

 GTIN (EAN)
 4032248275298

 Qty.
 50 pc(s).

Version EM, Terminal marker, 32.4 x 7.2 mm, Pitch in mm (P): 7.20 Weidmueller, Transparent

### **DEK 5/8**



### WS/ DEK

MultiMark terminal markers use an innovative composite material made from two components. The hard base contour of the marker snaps securely into the connector. The elastic surface finish makes the marker easy to mount. This specially punched material enables the strips to be stretched to accommodate the slight variations in spacing that tend to add up, especially with long terminal blocks. Another advantage: the excellent printability of the surface material guarantees durable and wearresistant labelling. A print resolution of 300 dpi also produces a very legible script.

# Your benefits with MultiMark

- Firm hold and durable printing
- Continuous strips save installation time
- Easy mounting thanks to an innovative composite material
- Large label field for optimal legibility
- High flexibility thanks to manufacturer independence

Туре	DEK 5/8 MM WS	Version
Order No.	2007130000	Dekafix, Terminal marker, 5 x 8 mm, Weidmueller, white
GTIN (EAN)	4050118392012	
Qty.	500 pc(s).	

# **Mouser Electronics**

Authorized Distributor

Click to View Pricing, Inventory, Delivery & Lifecycle Information:

Weidmuller: <u>1061200000</u>