

SSR 24VDC/MAX.240VAC 1A**Weidmüller Interface GmbH & Co. KG**

Klingenbergstraße 26

D-32758 Detmold

Germany

www.weidmueller.com

Individual relays for TERMSERIES

- Solid-state relays
- Different output versions

General ordering data

Version	TERMSERIES, Solid-state relay, Rated control voltage: 10...32 V DC , Rated switching voltage: 12...275 V AC, Continuous current: 1 A, Plug-in connection
Order No.	1132290000
Type	SSR 24VDC/MAX.240VAC 1A
GTIN (EAN)	4050118049381
Qty.	20 pc(s).

Creation date January 21, 2022 1:48:57 AM CET

Catalogue status 14.01.2022 / We reserve the right to make technical changes.

SSR 24VDC/MAX.240VAC 1A

Weidmüller Interface GmbH & Co. KG

Klingenbergstraße 26

D-32758 Detmold

Germany

www.weidmueller.com

Technical data

Dimensions and weights

Depth	15 mm	Depth (inches)	0.591 inch
Height	29 mm	Height (inches)	1.142 inch
Width	12.7 mm	Width (inches)	0.5 inch
Net weight	5.2 g		

Temperatures

Storage temperature	-40 °C...70 °C	Operating temperature	-20 °C...60 °C
---------------------	----------------	-----------------------	----------------

Probability of failure

MTTF	1,150 Years
------	-------------

Control side

Rated control voltage	10...32 V DC	Nominal control current	3...13 mA
Pull-in/drop-out voltage, typ.	10 V / 8 V DC	Status indicator	No

Load side

Rated switching voltage	12...275 V AC	Continuous current	1 A
Voltage drop at max. load	≤ 1 V	Min. switching current	50 mA
Inrush current	15 A / 10 ms	Leakage current	< 1.5 mA
Output voltage frequency range	50 / 60 Hz	Protective circuit, load side	RC element
Contact type	1 NO contact (Triac (zero-cross switch))		

General data

Colour	black
--------	-------

Insulation coordination

Dielectric strength for control side - load side	2.5 kV _{eff}
--	-----------------------

Connection data

Wire connection method	Plug-in connection	Pitch in mm (P)	5 mm
------------------------	--------------------	-----------------	------

Classifications

ETIM 6.0	EC001504	ETIM 7.0	EC001504
ETIM 8.0	EC001504	ECLASS 9.0	27-37-16-04
ECLASS 9.1	27-37-16-04	ECLASS 10.0	27-37-16-04
ECLASS 11.0	27-37-16-04		

Approvals

Approvals



ROHS

Conform

SSR 24VDC/MAX.240VAC 1A

Weidmüller Interface GmbH & Co. KG

Klingenbergstraße 26

D-32758 Detmold

Germany

www.weidmueller.com

Technical data

Downloads

Engineering Data	CAD data – STEP
Engineering Data	EPLAN, WSCAD
Catalogues	Catalogues in PDF-format
Brochures	


SSR 24VDC/MAX.240VAC 1A

Weidmüller Interface GmbH & Co. KG
Klingenbergstraße 26
D-32758 Detmold
Germany

www.weidmueller.com


Drawings

Wiring diagram




View of pins from below

Dimensional drawing



Graph

Signal characteristics of zero cross switching solid-state relays



Shown at an example with resistive load.

1. Switches on at first zero cross of mains voltage while control input gets signal.
2. Switches off at next zero cross of mains current after control input signal was switched off.

Switching DC voltages is not possible with this solid-state relays.

Mouser Electronics

Authorized Distributor

Click to View Pricing, Inventory, Delivery & Lifecycle Information:

[Weidmuller:](#)

[1132290000](#)