

# OSRAM GD JTLPS1.14

## Datasheet

Published by **ams-OSRAM AG**

Tobelbader Strasse 30, 8141 Premstaetten, Austria

Phone +43 3136 500-0

[ams-osram.com](http://ams-osram.com)

© All rights reserved



DURIS® E 2835

# GD JTLPS1.14

The DURIS® E 2835 color family provide excellent supreme efficacy in cost effective industry standard LED. DURIS® E 2835 never fails to impress with its performance on system level.



## Applications

- Agriculture & Horticulture
- Entertainment
- Indoor Lighting

## Features

- Package: white SMT package, colorless clear silicone resin
- Typ. Radiation: 120° (Lambertian emitter)
- ESD: 2 kV acc. to ANSI/ESDA/JEDEC JS-001 (HBM, Class 2)
- Radiant Flux: typ. 286 mW
- Radiant Efficiency: typ. 65 %
- Photosynthetic Photon Flux: typ. 1.07  $\mu\text{mol/s}$

Ordering Information

Type	Total radiant flux <sup>1)</sup> $I_F = 150\text{ mA}$ $\Phi_E$	Ordering Code
GD JTLPS1.14-MFN8-25-1	270 ... 360 mW	Q65113A1051

## Maximum Ratings

Parameter	Symbol		Values
Operating Temperature	$T_{op}$	min.	-40 °C
		max.	100 °C
Storage Temperature	$T_{stg}$	min.	-40 °C
		max.	100 °C
Junction Temperature	$T_j$	max.	125 °C
Forward current	$I_F$	min.	10 mA
		max.	250 mA
Surge Current $t \leq 10 \mu s$ ; $D = 0.005$ ; $T_j = 25 \text{ °C}$	$I_{FS}$	max.	350 mA
ESD withstand voltage acc. to ANSI/ESDA/JEDEC JS-001 (HBM, Class 2)	$V_{ESD}$		2 kV

Note: Ensure the appropriate derating current is being used in order to maintain a junction temperature which is lower than the maximum allowable limit.

## Characteristics

 $I_F = 150 \text{ mA}$ ;  $T_J = 25 \text{ °C}$ 

Parameter	Symbol	Values	
Dominant Wavelength <sup>2)</sup> $I_F = 150 \text{ mA}$	$\lambda_{\text{dom}}$	min. typ. max.	444 nm 455 nm 464 nm
Spectral Bandwidth at 50% $I_{\text{rel,max}}$	$\Delta\lambda$	typ.	16 nm
Viewing angle at 50% $I_V$	$2\phi$	typ.	120 °
Forward Voltage <sup>3)</sup> $I_F = 150 \text{ mA}$	$V_F$	min. typ. max.	2.8 V 3.0 V 3.1 V
Reverse current <sup>4)</sup>	$I_R$	Not designed for reverse operation	
Electrical thermal resistance junction/solderpoint with efficiency $\eta_e = 66 \text{ %}$	$R_{\text{thJS elec.}}$	typ.	12 K / W

## Brightness Groups

Group	Total radiant flux <sup>1)</sup> $I_F = 150$ mA min. $\Phi_E$	Total radiant flux <sup>1)</sup> $I_F = 150$ mA max. $\Phi_E$	PPF * min. $\Phi_p$	PPF * max. $\Phi_p$	PPF/W * typ.	PF ** min. $\Phi_{p,b}$	PF ** max. $\Phi_{p,b}$	PF/W ** typ.
MF	270 mW	280 mW	1.01 $\mu\text{mol/s}$	1.05 $\mu\text{mol/s}$	2.33 $\mu\text{mol/J}$	1.02 $\mu\text{mol/s}$	1.06 $\mu\text{mol/s}$	2.35 $\mu\text{mol/J}$
N1	280 mW	290 mW	1.05 $\mu\text{mol/s}$	1.09 $\mu\text{mol/s}$	2.42 $\mu\text{mol/J}$	1.06 $\mu\text{mol/s}$	1.09 $\mu\text{mol/s}$	2.43 $\mu\text{mol/J}$
N2	290 mW	300 mW	1.09 $\mu\text{mol/s}$	1.12 $\mu\text{mol/s}$	2.50 $\mu\text{mol/J}$	1.09 $\mu\text{mol/s}$	1.13 $\mu\text{mol/s}$	2.51 $\mu\text{mol/J}$
N3	300 mW	310 mW	1.12 $\mu\text{mol/s}$	1.16 $\mu\text{mol/s}$	2.58 $\mu\text{mol/J}$	1.13 $\mu\text{mol/s}$	1.17 $\mu\text{mol/s}$	2.60 $\mu\text{mol/J}$
N4	310 mW	320 mW	1.16 $\mu\text{mol/s}$	1.20 $\mu\text{mol/s}$	2.67 $\mu\text{mol/J}$	1.17 $\mu\text{mol/s}$	1.21 $\mu\text{mol/s}$	2.69 $\mu\text{mol/J}$
N5	320 mW	330 mW	1.20 $\mu\text{mol/s}$	1.24 $\mu\text{mol/s}$	2.76 $\mu\text{mol/J}$	1.21 $\mu\text{mol/s}$	1.24 $\mu\text{mol/s}$	2.77 $\mu\text{mol/J}$
N6	330 mW	340 mW	1.24 $\mu\text{mol/s}$	1.27 $\mu\text{mol/s}$	2.84 $\mu\text{mol/J}$	1.24 $\mu\text{mol/s}$	1.28 $\mu\text{mol/s}$	2.85 $\mu\text{mol/J}$
N7	340 mW	350 mW	1.27 $\mu\text{mol/s}$	1.31 $\mu\text{mol/s}$	2.92 $\mu\text{mol/J}$	1.28 $\mu\text{mol/s}$	1.32 $\mu\text{mol/s}$	2.94 $\mu\text{mol/J}$
N8	350 mW	360 mW	1.31 $\mu\text{mol/s}$	1.35 $\mu\text{mol/s}$	3.01 $\mu\text{mol/J}$	1.32 $\mu\text{mol/s}$	1.36 $\mu\text{mol/s}$	3.03 $\mu\text{mol/J}$

Note: [\*] Photosynthetic Photon Flux includes wavelengths between 400 and 700 nm

Note: [\*\*] Photon Flux includes wavelengths between 280 and 800 nm

Note: PPF and PF values are for reference only

## Forward Voltage Groups

Group	Forward Voltage <sup>3)</sup> $I_F = 150$ mA min. $V_F$	Forward Voltage <sup>3)</sup> $I_F = 150$ mA max. $V_F$
L1	2.8 V	2.9 V
L2	2.9 V	3.0 V
M1	3.0 V	3.1 V

Wavelength Groups

Group	Dominant Wavelength <sup>2)</sup>	Dominant Wavelength <sup>2)</sup>
	$I_F = 150\text{ mA}$ min. $\lambda_{\text{dom}}$	$I_F = 150\text{ mA}$ max. $\lambda_{\text{dom}}$
2	444 nm	450 nm
3	450 nm	455 nm
4	455 nm	460 nm
5	460 nm	464 nm

Group Name on Label


Example: MF-2-L1

Brightness	Wavelength	Forward Voltage
MF	2	L1




## Relative Spectral Emission <sup>5)</sup>

$I_{\text{rel}} = f(\lambda)$ ;  $I_F = 150 \text{ mA}$ ;  $T_J = 25 \text{ }^\circ\text{C}$




## Radiation Characteristics <sup>5)</sup>

$I_{\text{rel}} = f(\phi)$ ;  $T_J = 25 \text{ }^\circ\text{C}$




## Forward current <sup>5)</sup>

$$I_F = f(V_F); T_J = 25\text{ °C}$$




## Relative Radiant Power <sup>5), 6)</sup>

$$\Phi_E / \Phi_E(150\text{ mA}) = f(I_F); T_J = 25\text{ °C}$$




## Dominant Wavelength <sup>5)</sup>

$$\Delta\lambda_{\text{dom}} = f(I_F); T_J = 25\text{ °C}$$




**Forward Voltage** <sup>5)</sup>


$$\Delta V_F = V_F - V_F(25^\circ\text{C}) = f(T_j); I_F = 150\text{ mA}$$

**Relative Radiant Power** <sup>5)</sup>

$$\Phi_E / \Phi_E(25^\circ\text{C}) = f(T_j); I_F = 150\text{ mA}$$


**Dominant Wavelength** <sup>5)</sup>

$$\Delta \lambda_{\text{dom}} = \lambda_{\text{dom}} - \lambda_{\text{dom}}(25^\circ\text{C}) = f(T_j); I_F = 150\text{ mA}$$




Max. Permissible Forward Current

$I_F = f(T)$



## Dimensional Drawing <sup>7)</sup>



general tolerance  $\pm 0.1$

lead finish Ag 


C67062-A0354-A2-01

## Further Information:

**Approximate Weight:** 20.0 mg

**Package marking:** Cathode

## Recommended Solder Pad <sup>7)</sup>




E067.0346.04-01

For superior solder joint connectivity results we recommend soldering under standard nitrogen atmosphere. Package not suitable for ultra sonic cleaning.

## Reflow Soldering Profile

Product complies to MSL Level 3 acc. to JEDEC J-STD-020E



Profile Feature	Symbol	Pb-Free (SnAgCu) Assembly			Unit
		Minimum	Recommendation	Maximum	
Ramp-up rate to preheat <sup>*)</sup> 25 °C to 150 °C			2	3	K/s
Time $t_s$ $T_{Smin}$ to $T_{Smax}$	$t_s$	60	100	120	s
Ramp-up rate to peak <sup>*)</sup> $T_{Smax}$ to $T_p$			2	3	K/s
Liquidus temperature	$T_L$		217		°C
Time above liquidus temperature	$t_L$		80	100	s
Peak temperature	$T_p$		245	260	°C
Time within 5 °C of the specified peak temperature $T_p - 5$ K	$t_p$	10	20	30	s
Ramp-down rate* $T_p$ to 100 °C			3	6	K/s
Time 25 °C to $T_p$				480	s

All temperatures refer to the center of the package, measured on the top of the component

\* slope calculation  $DT/Dt$ :  $Dt$  max. 5 s; fulfillment for the whole T-range

cathode side

8

4

4


3.5

1.75

$\phi 1.50$

$\phi 1.1$

3.16



16 | Version 1.4 | 2023-02-23








Tape and Reel <sup>8)</sup>



Reel Dimensions


A	W	N <sub>min</sub>	W <sub>1</sub>	W <sub>2 max</sub>	Pieces per PU
330 mm	8 + 0.3 / - 0.1 mm	60 mm	8.4 + 2 mm	14.4 mm	10000

## Barcode-Product-Label (BPL)

OSRAM		LX XXXX	BIN1: XX-XX-X-XXX-X
(6P) BATCH NO: 1234567890		RoHS Compliant	
			ML Temp ST X XXX °C X
(1T) LOT NO: 1234567890	(9D) D/C: 1234		
		Pack: RXX DEMY XXX X_X123_1234.1234 X	
(X) PROD NO: 123456789		(Q) QTY: 9999	(G) GROUP: XX-XX-X-X
			

OHA04563

## Dry Packing Process and Materials <sup>7)</sup>



OH A00539

Moisture-sensitive product is packed in a dry bag containing desiccant and a humidity card according JEDEC-STD-033.

---

## Notes

The evaluation of eye safety occurs according to the standard IEC 62471:2006 (photo biological safety of lamps and lamp systems). Within the risk grouping system of this IEC standard, the device specified in this data sheet fall into the class **moderate risk (exposure time 0.25 s)**. Under real circumstances (for exposure time, conditions of the eye pupils, observation distance), it is assumed that no endangerment to the eye exists from these devices. As a matter of principle, however, it should be mentioned that intense light sources have a high secondary exposure potential due to their blinding effect. When looking at bright light sources (e.g. headlights), temporary reduction in visual acuity and afterimages can occur, leading to irritation, annoyance, visual impairment, and even accidents, depending on the situation.

Subcomponents of this device contain, in addition to other substances, metal filled materials including silver. Metal filled materials can be affected by environments that contain traces of aggressive substances. Therefore, we recommend that customers minimize device exposure to aggressive substances during storage, production, and use. Devices that showed visible discoloration when tested using the described tests above did show no performance deviations within failure limits during the stated test duration. Respective failure limits are described in the IEC60810.

This device is designed for specific/recommended applications only. Please consult OSRAM Opto Semiconductors Sales Staff in advance for detailed information on other non-recommended applications (e.g. automotive).

Change management for this component is aligned with the requirements of the lighting market.

For further application related information please visit [www.osram-os.com/appnotes](http://www.osram-os.com/appnotes)

---

## Disclaimer

### Attention please!

The information describes the type of component and shall not be considered as assured characteristics. Terms of delivery and rights to change design reserved. Due to technical requirements components may contain dangerous substances.

For information on the types in question please contact our Sales Organization.

If printed or downloaded, please find the latest version on our website.

### Packing

Please use the recycling operators known to you. We can also help you – get in touch with your nearest sales office. By agreement we will take packing material back, if it is sorted. You must bear the costs of transport. For packing material that is returned to us unsorted or which we are not obliged to accept, we shall have to invoice you for any costs incurred.

### Product and functional safety devices/applications or medical devices/applications

Our components are not developed, constructed or tested for the application as safety relevant component or for the application in medical devices.

Our products are not qualified at module and system level for such application.

In case buyer – or customer supplied by buyer – considers using our components in product safety devices/ applications or medical devices/applications, buyer and/or customer has to inform our local sales partner immediately and we and buyer and /or customer will analyze and coordinate the customer-specific request between us and buyer and/or customer.

---

## Glossary

- 1) **Brightness:** Brightness values are measured during a current pulse of typically 10 ms, with a tolerance of +/- 7%.
- 2) **Wavelength:** The wavelength is measured at a current pulse of typically 10 ms, with a tolerance of  $\pm 0.5$  nm.
- 3) **Forward Voltage:** The Forward voltage is measured during a current pulse duration of typically 1 ms with a tolerance of  $\pm 0.05$ V .
- 4) **Reverse Operation:** Not designed for reverse operation. Continuous reverse operation can cause migration and damage of the device.
- 5) **Typical Values:** Due to the special conditions of the manufacturing processes of semiconductor devices, the typical data or calculated correlations of technical parameters can only reflect statistical figures. These do not necessarily correspond to the actual parameters of each single product, which could differ from the typical data and calculated correlations or the typical characteristic line. If requested, e.g. because of technical improvements, these typ. data will be changed without any further notice.
- 6) **Characteristic curve:** In the range where the line of the graph is broken, you must expect higher differences between single devices within one packing unit.
- 7) **Tolerance of Measure:** Unless otherwise noted in drawing, tolerances are specified with  $\pm 0.1$  and dimensions are specified in mm.
- 8) **Tape and Reel:** All dimensions and tolerances are specified acc. IEC 60286-3 and specified in mm.

Revision History

Version	Date	Change
1.0	2020-04-30	Initial Version
1.1	2020-07-17	Initial Version Description
1.1	2020-08-13	Wavelength Groups
1.2	2020-09-02	Dimensional Drawing
1.3	2021-08-11	Brightness Groups
1.4	2023-02-23	Features New Layout Applications Maximum Ratings Derating (Diagrams)



EU RoHS and China RoHS compliant product

此产品符合欧盟 RoHS 指令的要求；  
按照中国的相关法规和标准，  
不含有毒有害物质或元素。

**Published by ams-OSRAM AG**

Tobelbader Strasse 30, 8141 Premstaetten, Austria

Phone +43 3136 500-0

[ams-osram.com](http://ams-osram.com)

© All rights reserved

**am** **OSRAM**

# Mouser Electronics

Authorized Distributor

Click to View Pricing, Inventory, Delivery & Lifecycle Information:

[ams OSRAM:](#)

[GD JTLPS1.14-MFN8-25-1](#)