## BGA Heat Sink (High Aspect Ratio Ext.) Straight Fin





ATS Part#:

#### ATS024024024-SF-8W

Description: 24.00 x

24.00 x 24.00 x 24.00 mm BGA Heat Sink (High Aspect Ratio Ext.) Straight Fin

| Heat Sink Type:         | Straight Fin |
|-------------------------|--------------|
| Heat Sink Attachment:   | N/A          |
| Equivalent Part Number: | N/A          |

\*Image above is for illustration purpose only.

#### **Features & Benefits**

- High aspect ratio, straight fin heat sinks that are ideal for compact PCB environments
- · Fabricated from extruded aluminum, which minimizes thermal resistance from the base to the fins, reduces weight and keeps costs low
- Higher performance helps ensure reliable product life at a lower cost than other extruded heat sinks
- · Comes standard without interface material or with most common pressure sensitive thermal tapes as a custom option

#### **Thermal Performance**

| AIR VELOCITY       |               | @200 LFM<br>1.0 M/S | @300 LFM<br>1.5 M/S | @400 LFM<br>2.0 M/S | @500 LFM<br>2.5 M/S | @600 LFM<br>3.0 M/S | @700 LFM<br>3.5 M/S | @800 LFM<br>4.0 M/S |
|--------------------|---------------|---------------------|---------------------|---------------------|---------------------|---------------------|---------------------|---------------------|
| THERMAL RESISTANCE | Unducted Flow | 4.21 °C/W           | 3 °C/W              | 2.5 °C/W            | 2.2 °C/W            | 2 °C/W              | 1.9 °C/W            | 1.7 °C/W            |
|                    | Ducted Flow   | 2.3                 | 2                   | 1.8                 | 1.6                 | 1.5                 | 1.4                 | 1.4                 |

### **Product Detail**

| Schematic Image                               | Dimension A   | Dimension B | Dimension C | Dimension D | тім | Finish         |  |  |
|---|---|-------------|-------------|-------------|-----|----------------|--|--|
|   | 24.00 mm  | 24.00 mm    | 24.00 mm    | 24 mm       | N/A | BLACK-ANODIZED |  |  |
| Image above is for illustration purpose only. | 24.00 mm 24.00 mm 24 mm N/A BLACK-ANODIZITY   Notes:   • Dimension A and B refer to component size.   • Dimension C is the heat sink height from the bottom of the base to the top of the fin field.   • Dimension D is fin tip to fin tip.   • Thermal performance data are provided for reference only. Actual performance may vary by application.   • ATS reserves the right to update or change its products without notice to improve the design or performance.   • ATS certifies that this heat sink assembly is RoHS-6 and REACH compliant.   • Contact ATS to learn about custom options available. |             |             |             |     |                |  |  |

For more information, to find a distributor or to place an order, please contact us at 781-769-2800 (North America), sales@qats.com or www.qats.com.



© 2013 Advanced Thermal Solutions, Inc. | 89-27 Access Road | Norwood MA | 02062 | USA

# **Mouser Electronics**

Authorized Distributor

Click to View Pricing, Inventory, Delivery & Lifecycle Information:

Advanced Thermal Solutions: ATS024024024-SF-8W