BGA Heat Sink - High Performance maxiFLOW w/Thermal Tape





ATS Part#:

Description:

ATS-52150B-C1-R0

15.00 x 15.00 x 7.50 mm BGA Heat Sink - High Performance maxiFLOW w/Thermal Tape

Heat Sink Type: maxiFLOW Heat Sink Attachment: **Thermal Tape** Equivalent Part Number: ATS-52150B-C2-R0

*Image above is for illustration purpose only.

Features & Benefits

- maxiFLOW™ design features a low profile, spread fin array that maximizes surface area for more effective convection (air) cooling .
- Fabricated from extruded aluminum, which minimizes thermal resistance from the base to the fins, reduces weight and keeps costs low .
- Higher performance helps ensure reliable product life at a lower cost than other extruded heat sinks •

Thermal Performance

		@200 LFM 1.0 M/S	@300 LFM 1.5 M/S	@400 LFM 2.0 M/S	@500 LFM 2.5 M/S	@600 LFM 3.0 M/S	@700 LFM 3.5 M/S	@800 LFM 4.0 M/S
THERMAL RESISTANCE	Unducted Flow	19.7 °C/W	15.9 °C/W	13.8 °C/W	12.3 °C/W	11.2 °C/W	10.4 °C/W	9.7 °C/W
	Ducted Flow	14.6	N/A	N/A	N/A	N/A	N/A	N/A

Product Detail

Schematic Image	Dimension A	Dimension B	Dimension C	Dimension D	ТІМ	Finish
	15.00 mm	15.00 mm	7.50 mm	27.94 mm	T412	BLUE-ANODIZED
	 Dimension ATS-5215 (Saint-Gol Thermal p application ATS reser performant ATS certification 	ves the right to upda	eight from the bottor act heat sink assemb provided for referer ate or change its proc k assembly is RoHS	ly with an equivalent nce only. Actual perfo ducts without notice -6 and REACH comp	t thermal ormance to improv	interface material may vary by
*Image above is for illustration purpose only.						

For more information, to find a distributor or to place an order, please contact us at 781-769-2800 (North America), sales@qats.com or www.qats.com.



Mouser Electronics

Authorized Distributor

Click to View Pricing, Inventory, Delivery & Lifecycle Information:

Advanced Thermal Solutions: ATS-52150B-C1-R0