BGA Heat Sink - High Performance Straight Fin w/maxiGRIP





ATS Part#:

Description:

ATS-53325D-C1-R0

32.50 x 32.50 x 9.50 mm BGA Heat Sink - High Performance Straight Fin w/maxiGRIP

Heat Sink Type:Straight FinHeat Sink Attachment:maxiGRIPEquivalent Part Number:ATS-53325D-C2-R0 Discontinued

*Image above is for illustration purpose only.

Features & Benefits

- High aspect ratio, straight fin heat sinks that are ideal for compact PCB environments
- maxiGRIP™ attachment applies steady, even pressure to the component and does not require holes in the PCB
- Designed specifically for BGAs and other surface mount packages
- Meets Telcordia GR-63-Core Office Vibration; ETSI 300 019 Transportation Vibration; and MIL-STD-810 Shock Testing and Unpackaged Drop Testing standards
- Comes preassembled with high performance, phase changing, thermal interface material

Thermal Performance

		@200 LFM 1.0 M/S	@300 LFM 1.5 M/S	@400 LFM 2.0 M/S	@500 LFM 2.5 M/S	@600 LFM 3.0 M/S	@700 LFM 3.5 M/S	@800 LFM 4.0 M/S
THERMAL RESISTANCE	Unducted Flow	11.3 °C/W	8.2 °C/W	6.8 °C/W	6 °C/W	5.5 °C/W	5.1 °C/W	4.7 °C/W
	Ducted Flow	5	N/A	N/A	N/A	N/A	N/A	N/A

Product Detail

Schematic Image	Dimension A	Dimension B	Dimension C	Dimension D	ТІМ	Finish
	32.50 mm	32.50 mm	9.50 mm	N/A mm	T766	BLACK-ANODIZED
Image above is for illustration purpose only.	 Dimension ATS-5332 (Saint Gol Thermal p application ATS resense performant ATS certif Optional r 	25D-C2-R0 is the ex bain C1100F). NOT performance data ar n. rves the right to upd nce. fies that this heat sir maxiGRIP™ Installa	neight from the botto	bly with an equivale 00F is discontinued ence only. Actual pe oducts without notice 6-6 and REACH cor Set P/N: MGT170	ent therma effective rformance e to impre	al interface material 12/31/10. e may vary by

For more information, to find a distributor or to place an order, please contact us at 781-769-2800 (North America), **sales@qats.com** or **www.qats.com**.



Mouser Electronics

Authorized Distributor

Click to View Pricing, Inventory, Delivery & Lifecycle Information:

Advanced Thermal Solutions: ATS-53325D-C1-R0