




Heat Sinks For Texas Instruments



ATS PART # ATS-TI10P-563-C1-R0

Features & Benefits

- » Optimized for natural convection air cooling
- » Black anodized for maximum heat dissipation
- » Designed specifically for TI's Module
#TAS5612, (#TAS5612LDDVEVM),
#TAS5614, (#TAS5614LDDVEVM)
- » Heat sinks come with two threaded mounting holes



**Images are for illustration purposes only.*

Thermal Performance

AIR VELOCITY		THERMAL RESISTANCE	
FT/MIN	M/S	°C/W (UNDUCTED FLOW)	°C/W (DUCTED FLOW)
200	1.0	2.7	2.0
300	1.5	2.3	n/a
400	2.0	2.0	n/a
500	2.5	1.8	n/a
600	3.0	1.7	n/a
700	3.5	1.6	n/a
800	4.0	1.5	n/a

Product Details

Dimension A	Dimension B	Dimension C	Dimension D	Thread Depth	Thread Type	Interface Material	Finish
54 mm	36 mm	35.6 mm	36.8 mm	6 mm	M3	N/A	Black Anodized

Notes:

- 1) Dimension A = heat sink length
- 2) Dimension B = heat sink width
- 3) Dimension C = heat sink height from bottom of the base to the top of the fin field (all in mm)
- 4) Dimension D = Hole distance center to center (mm)
- 5) Dimension E = Hole depth (mm)
- 6) Material AL-6063



ATS ADVANCED
THERMAL
SOLUTIONS, INC.
Innovations in Thermal Management®

For more information, to find a distributor or to place an order, visit www.qats.com or call: **781.769.2800**.

Mouser Electronics

Authorized Distributor

Click to View Pricing, Inventory, Delivery & Lifecycle Information:

[Advanced Thermal Solutions:](#)

[ATS-TI1OP-563-C1-R0](#)