


# Shielded Power Inductors – LPS3008



- Very low DCR; excellent current handling
- Only 0.8 mm tall; 3.0 × 3.0 mm footprint

**Core material** Ferrite

**Core and winding loss** See [www.coilcraft.com/coreloss](http://www.coilcraft.com/coreloss)

**Environmental** RoHS compliant, halogen free

**Terminations** RoHS compliant matte tin over nickel over silver. Other terminations available at additional cost.

**Weight** 22 – 25 mg

**Ambient temperature** –40°C to +85°C with (40°C rise) Irms current.

**Maximum part temperature** +125°C (ambient + temp rise). **Derating.**

**Storage temperature** Component: –40°C to +125°C.

Tape and reel packaging: –40°C to +80°C

**Resistance to soldering heat** Max three 40 second reflows at +260°C, parts cooled to room temperature between cycles

**Moisture Sensitivity Level (MSL)** 1 (unlimited floor life at <30°C / 85% relative humidity)

**Packaging** 1000/7" reel; 3500/13" reel; Plastic tape: 12 mm wide, 0.23 mm thick, 8 mm pocket spacing, 1.27 mm pocket depth

**Recommended pick and place nozzle** OD: 3 mm; ID: ≤ 1.5 mm

**PCB washing** Tested to MIL-STD-202 Method 215 plus an additional aqueous wash. See [Doc787\\_PCB\\_Washing.pdf](#).

Part number <sup>1</sup>	Inductance <sup>2</sup> ±20% (μH)	DCR max <sup>3</sup> (Ohms)	SRF typ <sup>4</sup> (MHz)	Isat (A) <sup>5</sup>			Irms (A) <sup>6</sup>	
				10% drop	20% drop	30% drop	20°C rise	40°C rise
LPS3008-561MR_	0.56	0.072	330	1.8	2.0	2.1	1.4	2.0
LPS3008-801MR_	0.80	0.092	255	1.6	1.7	1.8	1.1	1.6
LPS3008-102MR_	1.0	0.125	220	1.3	1.4	1.5	0.90	1.3
LPS3008-152MR_	1.5	0.134	170	1.1	1.3	1.3	0.87	1.2
LPS3008-222MR_	2.2	0.175	150	1.0	1.1	1.1	0.85	1.1
LPS3008-332MR_	3.3	0.285	114	0.81	0.86	0.88	0.74	0.95
LPS3008-472MR_	4.7	0.350	87	0.68	0.73	0.74	0.68	0.80
LPS3008-562MR_	5.6	0.450	78	0.62	0.67	0.70	0.58	0.73
LPS3008-682MR_	6.8	0.500	75	0.58	0.61	0.63	0.50	0.67
LPS3008-822MR_	8.2	0.600	61	0.52	0.56	0.58	0.45	0.60
LPS3008-103MR_	10	0.650	56	0.46	0.51	0.52	0.42	0.56
LPS3008-123MR_	12	0.790	49	0.45	0.48	0.50	0.38	0.50
LPS3008-183MR_	18	1.25	38	0.35	0.38	0.40	0.33	0.44
LPS3008-223MR_	22	1.50	35	0.29	0.33	0.34	0.29	0.38
LPS3008-333MR_	33	2.30	23	0.27	0.30	0.31	0.25	0.32
LPS3008-473MR_	47	3.00	21	0.22	0.23	0.24	0.21	0.27
LPS3008-683MR_	68	4.75	18	0.18	0.19	0.20	0.175	0.23
LPS3008-104MR_	100	6.85	14	0.15	0.16	0.16	0.160	0.21
LPS3008-124MR_	120	7.00	13	0.084	0.094	0.10	0.140	0.190
LPS3008-154MR_	150	8.00	11	0.080	0.088	0.092	0.130	0.175
LPS3008-184MR_	180	9.00	10	0.070	0.078	0.082	0.120	0.160

Coilcraft **Designer's Kit C392** contains samples of 0.56 μH to 33 μH parts (3 each) from LPS3008, LPS3010 and LPS3015. **Kit C401** contains samples of 0.56 μH to 33 μH parts (3 each) from LPS4012 and LPS4018. **Kit C402** contains samples of 220 μH to 2200 μH parts (3 each) from four series. For details of kit contents and to order, contact Coilcraft or visit <https://www.coilcraft.com/en-us/kits/>.

1. Please specify **termination** and **packaging** codes:

## LPS3008-184MRC

**Termination:** R= RoHS compliant matte tin over nickel over silver. Special order, added cost:  
Q = RoHS tin-silver-copper (95.5/4/0.5) or P = non-RoHS tin-lead (63/37).

**Packaging:** C= 7" machine-ready reel. EIA-481 embossed plastic tape (1000 parts per full reel). Quantities less than full reel available: in tape (not machine ready) or with leader and trailer (\$25 charge).

D= 13" machine-ready reel. EIA-481 embossed plastic tape. Factory order only, not stocked (3500 parts per full reel).

B= Less than full reel. In an effort to simplify our part numbering system, Coilcraft is eliminating the need for multiple packaging codes. When ordering, simply change the last letter of your part number from B to C.

2. Inductance tested at 100 kHz, 0.1 Vrms using an Agilent/HP 4192A. Inductance at 1 MHz is the same for parts with SRF ≥ 10 MHz.
3. DCR measured on a micro-ohmmeter.
4. SRF measured using an Agilent/HP 8753ES or equivalent.
5. DC current at 25°C that causes the specified inductance drop from its value without current. [link for temperature derating information.](#)
6. Current that causes the specified temperature rise from 25°C ambient. This information is for reference only and does not represent absolute maximum ratings. [Click for temperature derating information.](#)
7. Electrical specifications at 25°C. Refer to Doc 362 "Soldering Surface Mount Components" before soldering.



[www.coilcraft.com](http://www.coilcraft.com)

**US** +1-847-639-6400 [sales@coilcraft.com](mailto:sales@coilcraft.com)  
**UK** +44-1236-730595 [sales@coilcraft-europe.com](mailto:sales@coilcraft-europe.com)  
**Taiwan** +886-2-2264 3646 [sales@coilcraft.com.tw](mailto:sales@coilcraft.com.tw)  
**China** +86-21-6218 8074 [sales@coilcraft.com.cn](mailto:sales@coilcraft.com.cn)  
**Singapore** + 65-6484 8412 [sales@coilcraft.com.sg](mailto:sales@coilcraft.com.sg)

Document 438-1 Revised 10/21/21


© Coilcraft Inc. 2022

This product may not be used in medical or high risk applications without prior Coilcraft approval. Specification subject to change without notice. Please check web site for latest information.





# Shielded Power Inductors – LPS3008 Series

## Typical L vs Current



## Typical L vs Frequency




\* Dimensions are of the case not including the termination. For maximum overall dimensions including the termination, add 0.005 in / 0.13 mm.

For optional tin-lead and tin-silver-copper terminations, dimensions are for the mounted part. Dimensions before mounting can be an additional 0.005 inch / 0.13 mm).

Dimensions are in  $\frac{\text{inches}}{\text{mm}}$

**Packaging** 1000/7" reel; 3500/13" reel; Plastic tape: 12 mm wide, 0.23 mm thick, 8 mm pocket spacing, 1.27 mm pocket depth

**NOTE NEW PART ORIENTATION** Parts are rotated 90° in the packaging tape compared to previous versions of this product.



# Mouser Electronics

Authorized Distributor

Click to View Pricing, Inventory, Delivery & Lifecycle Information:

## Coilcraft:

[LPS3008-473MLC](#) [LPS3008-222MLC](#) [LPS3008-822MLB](#) [LPS3008-183MLB](#) [LPS3008-682MLB](#) [LPS3008-472MLB](#)  
[LPS3008-104MLC](#) [LPS3008-124MLC](#) [LPS3008-103MLB](#) [LPS3008-333MLB](#) [LPS3008-223MLC](#) [LPS3008-154MLC](#)  
[LPS3008-224MLC](#) [LPS3008-332MLC](#) [LPS3008-152MLC](#) [LPS3008-683MLC](#) [LPS3008-124MLB](#) [LPS3008-224MLB](#)  
[LPS3008-334MLB](#) [LPS3008-822MLC](#) [LPS3008-104MLB](#) [LPS3008-102MLC](#) [LPS3008-184MLC](#) [LPS3008-222MLB](#)  
[LPS3008-801MLC](#) [LPS3008-184MLB](#) [LPS3008-102MLB](#) [LPS3008-223MLB](#) [LPS3008-472MLC](#) [LPS3008-152MLB](#)  
[LPS3008-562MLB](#) [LPS3008-154MLB](#) [LPS3008-333MLC](#) [LPS3008-334MLC](#) [LPS3008-562MLC](#) [LPS3008-183MLC](#)  
[LPS3008-561MLC](#) [LPS3008-332MLB](#) [LPS3008-123MLC](#) [LPS3008-561MLB](#) [LPS3008-801MLB](#) [LPS3008-123MLB](#)  
[LPS3008-473MLB](#) [LPS3008-682MLC](#) [LPS3008-103MLC](#) [LPS3008-683MLB](#) [LPS3008-561MRB](#) [LPS3008-123MRC](#)  
[LPS3008-123MRB](#) [LPS3008-124MRB](#) [LPS3008-152MRB](#) [LPS3008-152MRC](#) [LPS3008-223MRC](#) [LPS3008-102MRB](#)  
[LPS3008-103MRB](#) [LPS3008-104MRB](#) [LPS3008-104MRC](#) [LPS3008-184MRC](#) [LPS3008-683MRB](#) [LPS3008-562MRB](#)  
[LPS3008-103MRC](#) [LPS3008-124MRC](#) [LPS3008-222MRB](#) [LPS3008-102MRC](#) [LPS3008-473MRC](#)  
[LPS3008-801MRB](#) [LPS3008-183MRB](#) [LPS3008-473MRB](#) [LPS3008-332MRB](#) [LPS3008-154MRC](#) [LPS3008-682MRB](#)  
[LPS3008-682MRC](#) [LPS3008-683MRC](#) [LPS3008-801MRC](#) [LPS3008-822MRB](#) [LPS3008-822MRC](#) [LPS3008-333MRB](#)  
[LPS3008-333MRC](#) [LPS3008-472MRB](#) [LPS3008-472MRC](#) [LPS3008-561MRC](#) [LPS3008-562MRC](#)  
[LPS3008-154MRB](#) [LPS3008-183MRC](#) [LPS3008-184MRB](#) [LPS3008-222MRC](#) [LPS3008-223MRB](#) [LPS3008-332MRC](#)