SDS Series Side Actuated Detect Switches

Features/Benefits

- Low profile package sits just 2mm off PCB
- 2mm overtravel ideal for detector applications
- Low actuation force (75 grams max.)
- Pick & place compatible, available in tape & reel packaging
- RoHS compliant and compatible

Typical Applications

- Medical devices
- Consumer electronics
- PCB lock cam detect
- IoT devices
- ATCA and MicroTCA



Specifications

CONTACT RATING: 100 mA @ 12 VDC.

MECHANICAL & ELECTRICAL LIFE: 50,000 cycles. CONTACT RESISTANCE: 100 m Ω max. initial.

INSULATION RESISTANCE: 10 M Ω min. @ 100 VDC.

OPERATING TEMPERATURE: -40°C to +85°C.

SOLDERABILITY: IR compatible, no wash. 260°C max.

PACKAGING: Bulk or tape & reel (3000 per reel).

Materials

BASE: Glass filled LCP (UL 94V-0). ACTUATOR: Glass Filled LCP (UL94V-0).

COVER: Nickel silver w/silver plate.


MOVABLE CONTACT: Phosphor bronze, see table for plating.

TERMINALS: Phosphor bronze, see table for plating.


NOTE: Specifications and materials listed above are for switches with standard options. For information on specific and custom switches, consult Customer Service Center.


How to Order

Complete part numbers for SDS Series Switches are shown below.




| PART NUMBER | HOUSING COLOR | PACKAGING | SCHEMATIC | Contact Plating | Terminal Plating |
|----------------|------------------|-------------|-----------|--------------------|---------------------|
| SDS001 | | Bulk | | | |
| SDS001R | Black | Tape & Reel | N.O. 2 1 | Silver | Silver |
| SDS002 | | Bulk | 2 1 | Clad | Plate |
| SDS002R | White | Tape & Reel | N.C. | | |
| SDS004 | | Bulk | | | |
| SDS004R | Black | Tape & Reel | N.O. 2 1 | Gold | Gold |
| SDS005 | | Bulk | 2 1 1 | Flash | Flash |
| SDS005R | White | Tape & Reel | N.C. | | |








SDS001











SDS Series Side Actuated Detect Switches

TAPE & REEL

TAPE & REEL PACKAGING NOTES:

- a. PACKAGE QUANTITY: 3,000 PCS/REEL.
- b. SPECIFICATION OF TAPING PACKAGE: THE REEL CARRIER TAPE WILL HAVE A LEAD OF 33 EMPTY COMPONENT POCKETS AND AN END OF 14EMPTY COMPONENT POCKETS ON EVERY REEL. ALL EMPTY COMPONENT POCKETS WILL BE SEALED WITH COVER TAPE.
- c. AFTER THE LEAD, NO REEL CARRIER TAPE SHALL HAVE TWO CONSECUTIVE EMPTY COMPONENT POCKETS.







Dimensions are shown: mm Specifications and dimensions subject to change



Mouser Electronics

Authorized Distributor

Click to View Pricing, Inventory, Delivery & Lifecycle Information:

C&K Switches:

SDS001 SDS005 SDS001R SDS002 SDS002R SDS004 SDS004R SDS005R