
HALL EFFECT PUSHBUTTON SWITCHES


10 MILLION CYCLES, CONTACTLESS HALL EFFECT TECHNOLOGY

The HP7C Hall effect momentary action pushbutton series shares similar characteristics to the HP7 series but is a lower cost version made with a thermoplastic case and a nylon button. With a 10 million cycle life, the HP7C works well in industrial joystick controls, remote controls and other applications requiring high reliability and high rates of actuation. PC pins or wire leads are standard with value-added connectors available to specification.

Features:


- 10 million cycles
- Hall effect technology for long life
- Stylish dome-shaped buttons in 9 colors
- Momentary action
- PC pin or wire lead termination styles
- RoHS compliant







WECHANICAL:					
Mechanical Life:	10 000 00	M avalaa			
Button Travel:	10,000,000 cycles 0.080 inches max				
241011 1141011					
Overtravel:	0.010 inches min				
Operating Force:	12 oz +/- 4 oz				
Operating Point:	0.040 inches +/- 0.012				
Electrical Life:	ectrical Life: 10,000,000 cycles				
ELECTRICAL RATINGS	: Rated a	t Vcc = 5V @ 2	5°C Load = 1mA	(4.7ΚΩ)	
Electrical		Units	Min	Max	
Supply Voltage		VDC	4.5	24.0	
Reverse Output Voltage		VDC	N/A	0.5	
Supply Current (B=0, Vcc	=5V, lo=0)	mA	2.3	4.2	
Continuous Output Curre	ent	mA	N/A	20.0	
Reverse Battery Protect	ion	VDC		-15.0	
ENVIRONMENTAL:			5°C		
ENVIRONMENTAL: Operating Temp Range:		-40°C to +8			
Operating Temp Range:		-40°C to +8	05°C		
Operating Temp Range: Storage Temp Range:	sign:		05°C		
	sign:	-40°C to +1	05°C		
Operating Temp Range: Storage Temp Range: Electronic Enclosure De	sign: Nylon	-40°C to +1	05°C		
Operating Temp Range: Storage Temp Range: Electronic Enclosure De MATERIALS:		-40°C to +1	05°C		



Mouser Electronics

Authorized Distributor

Click to View Pricing, Inventory, Delivery & Lifecycle Information:

OTTO:

HP7C-DR13122 HP7C-DR13121 HP7C-DR15122 HP7C-DR35122 HP7C-DR33122 HP7C-DR35121