

LARGE TRIM SWITCHES, 4 & 5-WAY

T4/T5
4-WAY
TOGGLES

4-WAY TOGGLE SWITCHES WITH OR WITHOUT CENTER PUSHBUTTON

T4-0010

Actuation: Center position maintained, all other positions momentary

Rating: 5 amps Resistive @ 30VDC sea level
3 amps Inductive @ 30VDC sea level
DMV: 1050Vrms @ sea level
400Vrms @ 70,000 feet

Electrical Life: 100,000 cycles

Enclosure: Dusttight per MIL-PRF-8805 Design 2

Button: Black thermoplastic

Case: Black anodized aluminum alloy



T5-0004

Actuation: Toggle & Pushbutton: center position maintained, all other positions momentary

Rating: 2 amps Resistive @ 28VDC or 115VAC/60Hz
DMV: 1050Vrms

Electrical Life: 50,000 cycles

Enclosure: Dusttight per MIL-PRF-8805 Design 2

Button: Black thermoplastic

Case: Anodized aluminum alloy



T4-0065

Actuation: Center position maintained, all other positions momentary

Rating: 5 amps Resistive @ 30VDC sea level
2.5 amps Resistive @ 70,000 feet
3 amps Inductive @ 30VDC sea level
1.5 amps Inductive @ 70,000 feet
DMV: 1050Vrms @ sea level
400Vrms @ 70,000 feet

Electrical Life: 100,000 cycles

Enclosure: Dusttight per MIL-PRF-8805 Design 2

Button: Black thermoplastic

Case: Black anodized aluminum alloy



T5-0015

Actuation: Toggle & Pushbutton: center position maintained, all other positions momentary

Rating: 2 amps Resistive @ 28VDC or 115VAC/60Hz
DMV: 1050Vrms

Electrical Life: 50,000 cycles

Enclosure: Dusttight per MIL-PRF-8805 Design 2

Button: Gray thermoplastic



T4-0082

Actuation: Toggle: center position maintained, all other positions momentary

Rating: 5 amps Resistive @ 30VDC sea level
3 amps Inductive @ 30VDC sea level
DMV: 1050Vrms @ sea level

Electrical Life: 50,000 cycles

Enclosure: Resilient per MIL-PRF-8805 Design 4

Button: Black thermoplastic

Case: Aluminum alloy



T5-0018

Actuation: Toggle & Pushbutton: center position maintained, all other positions momentary

Rating: 2 amps Resistive @ 28VDC or 115VAC/60Hz
DMV: 1050Vrms

Electrical Life: 50,000 cycles

Enclosure: Dusttight per MIL-PRF-8805 Design 2

Button: Black thermoplastic



T5-0028

Actuation: Toggle & Pushbutton: center position maintained, all other positions momentary

Rating: 2 amps Resistive @ 28VDC or 115VAC/60Hz
DMV: 1050Vrms

Electrical Life: 50,000 cycles

Enclosure: Dusttight per MIL-PRF-8805 Design 2

Button: Black thermoplastic

Case: Anodized aluminum alloy



T5-0035

Actuation: Toggle & Pushbutton: center position maintained, all other positions momentary

Rating: 2 amps Resistive @ 28VDC or 115VAC/60Hz
DMV: 1050Vrms

Electrical Life: 50,000 cycles

Enclosure: Dusttight per MIL-PRF-8805 Design 2

Button: Black thermoplastic

Case: Black chrome aluminum alloy



NOTE: Contact factory for additional configurations.

Mouser Electronics

Authorized Distributor

Click to View Pricing, Inventory, Delivery & Lifecycle Information:

[OTTO:](#)

[T5-0018](#) [T5-0004](#) [T4-0082](#) [T5-0028](#) [T4-0065](#)