The CM-BF527 is optimized for performance and functionality. The module integrates processor, RAM, flash, external peripheral controllers and power supply at a size of 31.5x36.5mm! It is based on the high performance ADSP-BF527 from Analog Devices. The Core Module is designed for commercial usage (commercial temperature range). It addresses up to 64MByte SDRAM via its 16bit wide SDRAM bus and has an onboard NOR-flash of 8MByte. The processor features a built in USB-OTG 2.0 unit and has the physical Ethernet transceiver onboard.

#### Features

CPU		Analog Devices BF527 @ 600MHz
RAM*		32/64MByte SDRAM up to 133MHz
FLASH		8MByte
INTERFACES	ETHERNET	1x10/100 Mbit Ethernet
	PPI	1
	SPI	1
	SPORT	2
	TWI/I <sup>2</sup> C	1
	UART	2
	USB 2.0	1 (OTG)
ADDITIONAL FEATURES		Single 3.3V supply voltage On-board core voltage regulator Low voltage reset circuit NAND Flash Interface
TEMP. RANGE		0°C to +70°C
VERSIONS		Connector
DIMENSIONS		31x36mm



\* depends on version - see ordering information

## **Development Support**

- » EVAL-BF5xx Evaluation Board
- » DEV-BF5xx Development Board
- » DEV-BF5xxDA-Lite Development Board
- » BLACKSheep® OS
- » uClinux Port available

## **Ordering Information**

Order No.	Info
100-1253-2	CM-BF527-C-C-Q50S32F8 (CM-BF527)
100-1254-2	CM-BF527-C-C-Q50S64F8 (CM-BF527-64SD)

# Applications

- » Mobile Embedded Device
- » Network connected embedded system
- » Industrial control
- » Voice over IP (VoIP)
- » Multi-media application processor
- » Multi-media accessories e.g. docks
- » Networked audio
- » Instrumentation
- » Imaging

### BLUETECHNIX MECHATRONISCHE SYSTEME GMBH

Lainzerstraße 162/3 1130 Wien, Austria www.bluetechnix.com Tel.: +43 (1) 9142091 x 0 Fax.: +43 (1) 9142091 x 99 Email: office@bluetechnix.at



# **Mouser Electronics**

Authorized Distributor

Click to View Pricing, Inventory, Delivery & Lifecycle Information:

BECOM: 100-1254-2