

Data Sheet

FEATURES

Amplitude settling: 200 ns typical Wideband rejection: ≥20 dB Single chip implementation 40-lead, 6 mm × 6 mm, RoHS compliant LFCSP

APPLICATIONS

Test and measurement equipment Military radar and electronic warfare (EW) systems Video satellite (VSAT) communications

6.3 GHz to 18 GHz, Tunable Band-Pass Filter

ADMV8416

FUNCTIONAL BLOCK DIAGRAM



GENERAL DESCRIPTION

The ADMV8416 is a monolithic microwave integrated circuit (MMIC), tunable band-pass filter that features a user selectable pass-band frequency. The 3 dB filter bandwidth is approximately 15% of the center frequency (f_{CENTER}), and the 20 dB filter bandwidth is 37%. Additionally, f_{CENTER} can be varied between 6.8 GHz to 16.8 GHz by applying an analog f_{CENTER} tuning

voltage between 0 V to 15 V. The usable pass band corner frequencies (f_{CORNER}) span from 6.3 GHz to 18 GHz. This tunable filter can be used as a much smaller alternative to large switched filter banks and cavity tuned filters. The filter has excellent microphonics due to the monolithic design and provides a dynamically adjustable solution.

Rev. A

Document Feedback

Information furnished by Analog Devices is believed to be accurate and reliable. However, no responsibility is assumed by Analog Devices for its use, nor for any infringements of patents or other rights of third parties that may result from its use. Specifications subject to change without notice. No license is granted by implication or otherwise under any patent or patent rights of Analog Devices. Trademarks and registered trademarks are the property of their respective owners.

TABLE OF CONTENTS

Features
Applications1
Functional Block Diagram1
General Description
Revision History
Specifications
High Band Specifications
Low Band Specifications4
DC Characteristics 4
Absolute Maximum Ratings 5
ESD Caution
Pin Configuration and Function Descriptions

REVISION HISTORY

10/2020-Rev. 0 to Rev. A

Changes to Product Title and General Description Section	. 1
Changes to Frequency Range Parameters, Table 1	. 3
Changes to Frequency Range Parameters, Table 2	. 4
Changes to Theory of Operation Section	16

7/2019—Revision 0: Initial Version

Interface Schematics	6
Typical Performance Characteristics	7
High Band, VCTL = 0 V	7
Low Band, VCTL = 2.5 V	10
Phase Sensitivity	13
Theory of Operation	14
Applications Information	15
Typical Application Circuit	15
Outline Dimensions	16
Ordering Guide	16

SPECIFICATIONS

HIGH BAND SPECIFICATIONS

 $T_A = 25^{\circ}$ C, VTUNE is swept from 0 V to 15 V, VDD = 5 V, VEE = -5 V, and VCTL = 0 V, unless otherwise noted.

Table 1.

Parameter	Min	Тур	Max	Unit	Test Conditions/Comments
FREQUENCY RANGE					
fcenter	12.6		16.8	GHz	
3 dB f _{CORNER}	11.6		18	GHz	
FILTER BANDWIDTH					
3 dB		16		%	
20 dB		37		%	
WIDEBAND REJECTION					
Low-Side		$0.8 \times f_{\text{Center}}$		dB	≥20 dB
High-Side		$1.17 \times f_{\text{CENTER}}$		dB	≥20 dB
Re-Entry		>40		GHz	≤30 dB
LOSS					
Insertion Loss		8		dB	
Return Loss		8.5		dB	
DYNAMIC PERFORMANCE					
Input Third-Order Intercept (IP3)		38		dBm	
Input Power at 5° Shift in Insertion		>20		dBm	VTUNE = 0 V
Phase					
Group Delay Flatness		0.1		ns	VTUNE = 0 V
Phase Sensitivity		0.7		Rad/V	
Amplitude Settling		200		ns	Time to settle to minimum insertion loss,
					within \leq 0.5 dB of static insertion loss
Drift Rate		-2.17		MHz/°C	
Tuning Sensitivity		417		MHz/V	
RESIDUAL PHASE NOISE					
1 MHz Offset		-160		dBc/Hz	

LOW BAND SPECIFICATIONS

 $T_A = 25^{\circ}$ C, VTUNE is swept from 0 V to 15 V, VDD = 5 V, VEE = -5 V, and VCTL = 2.5 V, unless otherwise noted.

Table 2.					
Parameter	Min	Тур	Мах	Unit	Test Conditions/Comments
FREQUENCY RANGE					
fcenter	6.8		12	GHz	
3 dB f _{corner}	6.3		12.8	GHz	
FILTER BANDWIDTH					
3 dB		15		%	
20 dB		37		%	
WIDEBAND REJECTION					
Low-Side		$0.8 imes f_{\text{CENTER}}$		dB	<u>≥</u> 20 dB
High-Side		$1.16 \times f_{\text{CENTER}}$		dB	<u>≥</u> 20 dB
Re-Entry		>40		GHz	≤30 dB
LOSS					
Insertion Loss		8		dB	
Return Loss		7.7		dB	
DYNAMIC PERFORMANCE					
Input IP3		34		dBm	
Input Power at 5° Shift in Insertion Phase		13		dBm	VTUNE = 0 V
Group Delay Flatness		0.20		ns	VTUNE = 0 V
Phase Sensitivity		1.21		Rad/V	
Amplitude Settling		200		ns	Time to settle to minimum insertion loss, within ≤0.5 dB of static insertion loss
Drift Rate		-0.71		MHz/°C	
Tuning Sensitivity		421		MHz/V	
RESIDUAL PHASE NOISE					
1 MHz Offset		-162		dBc/Hz	

DC CHARACTERISTICS

Table 3.

10010 01					
Parameter	Min	Тур	Мах	Unit	Test Conditions/Comments
f _{center} Tuning					
VTUNE Voltage	0		15	V	
Current (I _{TUNE})			±1	μA	
BAND CONTROL VOLTAGE (VCTL)					
Input Voltage					
Low	0		0.8	V	0 V for high band select
High	2	2.5	3	V	2.5 V for low band select
Current			1	μA	
SUPPLY VOLTAGES					
Negative (VEE)	-5.5	-5		V	
Positive (VDD)		5	5.5	V	
SUPPLY CURRENTS					
Negative (IEE)		0.7		mA	
Positive (I _{DD})			1	mA	

ABSOLUTE MAXIMUM RATINGS

Table 4.

Parameter	Rating
Tuning	
VTUNE	–0.5 V to +15 V
I _{TUNE}	±1 μA
Supply Voltages	
VEE	–5.6 V
VDD	5.6 V
VCTL	–0.5 V to VDD + 0.5 V
RF Input Power	
2 GHz to 50 GHz	27 dBm
0.5 GHz to 2 GHz	19 dBm
0 GHz to 0.5 GHz	6 dBm
Hot Switch Input Power	
2 GHz to 50 GHz	24 dBm
0.5 GHz to 2 GHz	16 dBm
0 GHz to 0.5 GHz	3 dBm
Temperature	
Operating	-40°C to +85°C
Storage Temperature	–65°C to +150°C
Junction for 1 Million Mean Times Between Failures (MTTF)	150°C
Nominal Junction ($T_{PADDLE} = 85^{\circ}C$, input power (P_{IN}) = 23 dBm)	150°C
Electrostatic Discharge (ESD) Rating	
Human Body Model (HBM)	250 V
Field Induced Charge Device Model (FICDM)	1250 V
Moisture Sensitivity Level (MSL) Rating	MSL3

Stresses at or above those listed under Absolute Maximum Ratings may cause permanent damage to the product. This is a stress rating only; functional operation of the product at these or any other conditions above those indicated in the operational section of this specification is not implied. Operation beyond the maximum operating conditions for extended periods may affect product reliability.

ESD CAUTION



ESD (electrostatic discharge) sensitive device. Charged devices and circuit boards can discharge without detection. Although this product features patented or proprietary protection circuitry, damage may occur on devices subjected to high energy ESD. Therefore, proper ESD precautions should be taken to avoid performance degradation or loss of functionality.

PIN CONFIGURATION AND FUNCTION DESCRIPTIONS



Figure 2. Pin Configuration

Table 5. Pin Function Descriptions

Pin No.	Mnemonic	Description
1 to 3, 7 to 10, 14, 17, 20,	NC	No Connect. These pins are not connected internally. All data shown within was measured with
21 to 24, 28 to 40		these pins connected to RF and dc ground externally.
4, 6, 12, 16, 18, 25, 27	GND	Ground. Connect these pins to RF and dc ground.
5	RFIN	RF Input. This pin is dc-coupled and matched to 50 Ω . Blocking capacitors are required if the RF line potential is not equal to 0 V.
11	VEE	Negative Supply Voltage. VEE is –5 V.
13	VDD	Positive Supply Voltage. VDD is 5 V.
15	VCTL	Control Voltage for Band Selection. The band-pass filter is in the high band when VCTL = 0 V and in the low band when VCTL = 2.5 V.
19	VTUNE	Center Frequency Control Voltage of the Band-Pass Filter. The voltage can vary from 0 V to 15 V.
26	RFOUT	RF Output. This pin is dc-coupled and matched to 50 Ω . Blocking capacitors are required if the RF line potential is not equal to 0 V.
	EPAD	Exposed Pad. Connect the EPAD to RF and dc ground.

INTERFACE SCHEMATICS



Figure 3. VCTL and VDD Interface Schematic



Figure 4. VTUNE Interface Schematic



Figure 5. VEE Interface Schematic



Figure 6. GND Interface Schematic



Figure 7. RFIN and RFOUT Interface Schematic

TYPICAL PERFORMANCE CHARACTERISTICS



Figure 8. Broadband Insertion Loss vs. RF Frequency at Various Voltages



Figure 9. Insertion Loss vs. RF Frequency at Various Voltages



Figure 10. Minimum Insertion Loss vs. RF Frequency at Various Temperatures, VTUNE = 7 V



Figure 11. Broadband Return Loss vs. RF Frequency at Various Voltages and S11 and S22



Figure 12. Return Loss vs. RF Frequency at Various Voltages and S11 and S22



Figure 13. Return Loss vs. RF Frequency at Various Temperatures and S11 and S22, VTUNE = 7 V







Figure 15. 3 dB Bandwidth vs. VTUNE at Various Temperatures



Figure 16. Insertion Loss vs. VTUNE at Various Temperatures



Figure 17. Maximum Return Loss in a 2 dB Bandwidth vs. VTUNE at Various Temperatures



Figure 18. High-Side Rejection Ratio vs. VTUNE at Various Temperatures and 20 dB and 35 dB



Figure 19. Low-Side Rejection Ratio vs. VTUNE at Various Temperatures and 20 dB and 35 dB

Data Sheet

600 500 TUNING SENSITIVITY (MHz/V) 400 300 200 100 -85°C +25°C -40°C 0 20365-018 1 2 3 10 11 12 13 14 15 0 4 5 6 7 8 9 VTUNE (V)

Figure 20. Tuning Sensitivity vs. VTUNE at Various Temperatures



Figure 21. Group Delay vs. VTUNE at Various Temperatures



Figure 22. Group Delay vs. RF Frequency at Various VTUNE



Figure 23. Input IP3 vs. VTUNE at Various Temperatures, Input Power = 20 dBm



Figure 24. Residual Phase Noise vs. Offset Frequency at Various VTUNE



ADMV8416

LOW BAND, VCTL = 2.5 V



Figure 26. Broadband Insertion Loss vs. RF Frequency at Various Voltages



Figure 27. Insertion Loss vs. RF Frequency at Various Voltages



Figure 28. Minimum Insertion Loss vs. RF Frequency at Various Temperatures, VTUNE = 7 V



Figure 29. Broadband Return Loss vs. RF Frequency at Various Voltages and S11 and S22



Figure 30. Return Loss vs. RF Frequency at Various Voltages and S11 and S22



Figure 31. Return Loss vs. RF Frequency at Various Temperatures and S11 and S22, VTUNE = 7 V

Data Sheet

f_{center} (GHz) +85°C +25°C -40°C 20365-030 10 11 12 13 14 15 VTUNE (V) Figure 32. f_{CENTER} vs. VTUNE at Various Temperatures 3dB BANDWIDTH (%) +85°C +25°C –40°C 10 11 12 13 14 15 20365-031 VTUNE (V)

Figure 33. 3 dB Bandwidth vs. VTUNE at Various Temperatures



Figure 34. Insertion Loss vs. VTUNE at Various Temperatures



Figure 35. Maximum Return Loss in a 2 dB Bandwidth vs. VTUNE at Various Temperatures



Figure 36. High-Side Rejection vs. VTUNE at Various Temperatures and 20 dB and 35 dB



Figure 37. Low-Side Rejection vs. VTUNE at Various Temperatures and 20 dB and 35 dB

ADMV8416





Figure 39. Group Delay vs. VTUNE at Various Temperatures



Figure 40. Group Delay vs. RF Frequency at Various VTUNE



Figure 41. Input IP3 vs. VTUNE at Various Temperatures, Input Power (P_{IN}) = 20 dBm



Figure 42. Residual Phase Noise vs. Offset Frequency at Various VTUNE



Figure 43. Phase Shift vs. Input Power at Various VTUNE

PHASE SENSITIVITY



Figure 44. f_{CENTER} and Phase Sensitivity vs. VTUNE, High Band



Figure 45. f_{CENTER} and Phase Sensitivity vs. VTUNE, Low Band

THEORY OF OPERATION

The ADMV8416 is a MMIC, band-pass filter that features a user-selectable pass-band frequency.

VCTL is control voltage for selecting low or high band-pass filtering. VCTL sets the switch positions for low and high band-pass operation. When VCTL = 0 V, the high band-pass filter is selected, which has an f_{CENTER} range from 12.6 GHz to 16.8 GHz. When VCTL = 2.5 V, the low band-pass filter is selected, which has an f_{CENTER} range from 6.8 GHz to 12 GHz.

The f_{CENTER} is adjustable by supplying VTUNE, which varies from 0 V to 15 V. In typical operation, turn on the level shifter by applying the correct voltage on the VDD pin and VEE pin, then control the switch by supplying the VCTL pin, and lastly, supply the VTUNE for the f_{CENTER} .

20365-042

APPLICATIONS INFORMATION



Figure 46. Typical Application Circuit

TYPICAL APPLICATION CIRCUIT

Figure 46 shows the typical application circuit for the ADMV8416. The RFIN pin and RFOUT pin are dc-coupled, and blocking capacitors are required if the RF line potential is not equal to 0 V.

OUTLINE DIMENSIONS



ORDERING GUIDE

Model ¹	Temperature Range	Package Description	Package Option
ADMV8416ACPZ	-40°C to +85°C	40-Lead Lead Frame Chip Scale Package [LFCSP]	CP-40-27
ADMV8416ACPZ-R5	-40°C to +85°C	40-Lead Lead Frame Chip Scale Package [LFCSP], 5" Tape and Reel	CP-40-27
ADMV8416-EVALZ		Evaluation Board	

 1 Z = RoHS Compliant Part.

©2019–2020 Analog Devices, Inc. All rights reserved. Trademarks and registered trademarks are the property of their respective owners. D20365-10/20(A)



www.analog.com

Rev. A | Page 16 of 16

Mouser Electronics

Authorized Distributor

Click to View Pricing, Inventory, Delivery & Lifecycle Information:

Analog Devices Inc.:

ADMV8416ACPZ ADMV8416ACPZ-R5 ADMV8416-EVALZ