

EVALUATION KIT
AVAILABLE

+3.3V, 2.5Gbps Low-Power Limiting Amplifiers

General Description

The MAX3272/MAX3272A 2.5Gbps limiting amplifiers accept a wide range of input voltages and provide a constant-level output voltage with controlled edge speeds. Additional features include power detectors with programmable loss-of-signal (LOS) indication, an optional squelch function that mutes the data output signal when the input voltage falls below a programmable threshold, and an output polarity selector. These parts exhibit excellent jitter performance and have low power dissipation.

The MAX3272/MAX3272A feature current-mode logic (CML) data outputs that are tolerant of inductive connectors, and are available in a 4mm × 4mm QFN package or in die form (MAX3272 only). Along with the MAX3271, the MAX3272/MAX3272A are ideal for low-power, compact optical receivers.

Applications

Gigabit Ethernet Optical Receivers
Fibre Channel Optical Receivers
System Interconnects
2.5Gbps Optical Receivers
SONET/SDH Receivers

Features

- ◆ Single +3.3V Power Supply
- ◆ 33mA Supply Current
- ◆ 5ps Deterministic Jitter
- ◆ 90ps Edge Speed
- ◆ Output Squelch Function
- ◆ Programmable Loss-of-Signal Function
- ◆ CML Output Interface
- ◆ 20-Pin 4mm × 4mm QFN or Thin QFN Package
- ◆ Selectable Output Polarity

Ordering Information


| PART | TEMP RANGE | PIN-PACKAGE | PACKAGE CODE |
|--------------|----------------|-------------|--------------|
| MAX3272EGP | -40°C to +85°C | 20 QFN | G2044-3 |
| MAX3272E/D | -40°C to +85°C | Dice* | — |
| MAX3272AETP+ | -40°C to +85°C | 20 Thin QFN | T2044-3 |
| MAX3272AEGP | -40°C to +85°C | 20 QFN | G2044-3 |

+ Denotes Lead-Free Package.

*Dice are designed and guaranteed to operate from -40°C to +85°C, but are tested only at $T_A = +25^\circ\text{C}$.

Pin Configuration appears at end of data sheet.

Typical Operating Circuit



+3.3V, 2.5Gbps Low-Power Limiting Amplifiers

ABSOLUTE MAXIMUM RATINGS

Power-Supply Voltage (V_{CC}) -0.5V to +6.0V
 Voltage at IN+, IN- ($V_{CC} - 2.4V$) to ($V_{CC} + 0.5V$)
 Voltage at SQUELCH, CAZ1, CAZ2, TH, CLOS -0.5V to ($V_{CC} + 0.5V$)
 Voltage at LOS, \overline{LOS} (MAX3272) -0.5V to +6.0V
 Voltage at LOS, \overline{LOS} (MAX3272A) -0.5V to ($V_{CC} + 0.5V$)
 Voltage at LEVEL -0.5V to +2.0V
 Voltage at OUTPOL -0.5V to +6.0V
 Current into LOS, \overline{LOS} -1mA to +9mA
 Differential Input Voltage (IN+ - IN-) 2.5V_{P-P}
 Continuous Current at IN+, IN- 50mA

Continuous Current at CML Outputs (OUT+, OUT-) -25mA to +25mA
 Continuous Power Dissipation at +85°C
 20-Pin Thin QFN (derate 16.9mW/°C above +85°C) 1.1W
 20-Pin QFN (derate 20mW/°C above +85°C) 1.3W
 Storage Ambient Temperature
 Range (T_{STG}) -55°C to +150°C
 Operating Junction Temperature
 Range (T_J) -55°C to +150°C
 Die Attach Temperature +400°C
 Lead Temperature (soldering, 10s) +300°C

Stresses beyond those listed under "Absolute Maximum Ratings" may cause permanent damage to the device. These are stress ratings only, and functional operation of the device at these or any other conditions beyond those indicated in the operational sections of the specifications is not implied. Exposure to absolute maximum rating conditions for extended periods may affect device reliability.

ELECTRICAL CHARACTERISTICS

($V_{CC} = +3.0V$ to +3.6V, $T_A = -40^\circ C$ to +85°C. Typical values are at $V_{CC} = +3.3V$ and $T_A = +25^\circ C$, unless otherwise noted.) (Note 1)

| PARAMETER | SYMBOL | CONDITIONS | MIN | TYP | MAX | UNITS |
|--|-----------|--|------|------|------|-------------------|
| Supply Current | I_{CC} | (Note 2) | | 33 | 44 | mA |
| Input Data Rate | | | | 2.5 | | Gbps |
| Input Voltage Range | V_{IN} | Differential | 15 | | 1200 | mV _{P-P} |
| Output Deterministic Jitter | | (Notes 3, 4, 5) | | 5 | 27 | ps _{P-P} |
| Random Jitter | | (Notes 4, 6) | | 3 | | ps _{RMS} |
| Data Output Edge Speed (20% to 80%) | | (Notes 3, 4) | | 90 | 130 | ps |
| | | $15mV_{P-P} < V_{IN} \leq 30mV_{P-P}$ | | 90 | 115 | |
| | | $30mV_{P-P} \leq V_{IN} \leq 1200mV_{P-P}$ | | 90 | 115 | |
| Differential Input Resistance | R_{IN} | IN+ to IN- | 95 | 100 | 105 | Ω |
| Input-Referred Noise | | | | 220 | | μV_{RMS} |
| CML Output Voltage | V_{OUT} | LEVEL open, $R_{LOAD} = 50\Omega$ | 550 | 750 | 1200 | mV _{P-P} |
| Output Signal when Squelched | | Outputs AC-coupled | | 2.2 | | mV _{P-P} |
| Power-Supply Noise Rejection | PSNR | $f \leq 2MHz$ (Note 7) | | 30 | | dB |
| Low Frequency Cutoff | f_{OC} | CAZ = open | | 0.9 | | MHz |
| | | CAZ = 0.1 μF | | 1.5 | | kHz |
| Output Resistance | R_{OUT} | Single ended to V_{CC} | 42.5 | 50 | 57.5 | Ω |
| Single-Ended Output Return Loss | | $\leq 2.5GHz$ | | 10 | | dB |
| | | 2.5GHz to 4.0GHz | | 9 | | |
| Differential Input Return Loss | | 4.0GHz | | 10 | | dB |
| OUTPOL Input Limits | V_{IL} | | | | 0.8 | V |
| | V_{IH} | | 2.4 | | | |
| LOS Hysteresis | | (Notes 3, 4, 8) | 2 | 3.3 | | dB |
| LOS Assert/Deassert Time | | $C_{CLOS} = \text{open}$ (Notes 3, 9, 10) | | 1 | | μs |
| | | $C_{CLOS} = 0.01\mu F$ (Notes 3, 9, 10) | 2.3 | 50 | 100 | |
| Low LOS Assert Level | | $R_{TH} = 20k\Omega$ (Notes 3, 10) | 4.5 | 6.5 | | mV _{P-P} |
| Low LOS Deassert Level | | $R_{TH} = 20k\Omega$ (Notes 3, 10) | | 9.5 | 12.7 | mV _{P-P} |
| Medium LOS Assert Level | | $R_{TH} = 1k\Omega$ (Notes 3, 10) | 7.8 | 12.9 | | mV _{P-P} |
| Medium LOS Deassert Level | | $R_{TH} = 1k\Omega$ (Notes 3, 10) | | 17.4 | 22.4 | mV _{P-P} |
| High LOS Assert Level | | $R_{TH} = 80\Omega$ (Notes 3, 10) | 24.3 | 48 | | mV _{P-P} |

+3.3V, 2.5Gbps Low-Power Limiting Amplifiers

ELECTRICAL CHARACTERISTICS (continued)


(V_{CC} = +3.0V to +3.6V, T_A = -40°C to +85°C. Typical values are at V_{CC} = +3.3V and T_A = +25°C, unless otherwise noted.)

| PARAMETER | SYMBOL | CONDITIONS | MIN | TYP | MAX | UNITS |
|-------------------------|--------|-------------------------------------|-----|-----|-------|-------------------|
| High LOS Deassert Level | | R _{TH} = 80Ω (Notes 3, 10) | | 73 | 124.7 | mV _{P-P} |
| LOS Output High Voltage | | Sinking 30μA | 2.4 | | | V |
| LOS Output Low Voltage | | Sourcing 1.2mA | | | 0.4 | V |
| Squelch Input Current | | | | | 400 | μA |

- Note 1:** Dice are designed and guaranteed from -40°C to +85°C but are tested only at T_A = +25°C.
- Note 2:** Supply current measurement excludes the current of the CML output stage (16mA typical). See Figure 1, *Power-Supply Current Measurement*.
- Note 3:** Guaranteed by design and characterization.
- Note 4:** Input edge speed is controlled using 4-pole, lowpass Bessel filters with bandwidth approximately 75% of the maximum data rate.
- Note 5:** Deterministic jitter is measured with a K28.5 pattern (0011 1110 1011 0000 0101). Deterministic jitter is the peak-to-peak deviation from ideal time crossings, measured at the zero-level crossings of the differential output per ANSI X3.230, Annex A.
- Note 6:** Random jitter is measured with the minimum input signal. For Fibre Channel and Gigabit Ethernet applications, the peak-to-peak random jitter is 14.1 times the RMS random jitter.
- Note 7:** Power-supply noise rejection (PSNR) is calculated by the equation $PSNR = 20\log(\Delta V_{CC}/(\Delta V_{OUT}))$, where ΔV_{OUT} is the change in differential output voltage due to the power-supply noise, ΔV_{CC} . See Power-Supply Noise Rejection vs. Frequency in the *Typical Operating Characteristics*.
- Note 8:** Hysteresis is defined as: $20 \times \log(V_{LOS-DEASSERT}/V_{LOS-ASSERT})$.
- Note 9:** Response time to a 10dB change in input power. For the specification guaranteed, the power is assumed to switch back and forth between two levels (separated by 10dB and equidistant from assert and deassert levels) outside of the two hysteresis thresholds.
- Note 10:** All power-detect AC parameters are guaranteed with a 2²³ - 1 PRBS, 2.5Gbps input, with the longest possible run of 80CID.

Typical Operating Characteristics










(V_{CC} = +3.3V, T_A = +25°C, unless otherwise noted.)



+3.3V, 2.5Gbps Low-Power Limiting Amplifiers

Typical Operating Characteristics (continued)



($V_{CC} = +3.3V$, $T_A = +25^\circ C$, unless otherwise noted.)



+3.3V, 2.5Gbps Low-Power Limiting Amplifiers

Typical Operating Characteristics (continued)

($V_{CC} = +3.3V$, $T_A = +25^\circ C$, unless otherwise noted.)



Pin Description

| PIN | NAME | FUNCTION |
|---------------|------------------|--|
| 1, 4, 17 | GND | Supply Ground |
| 2 | IN+ | Noninverted Input Signal |
| 3 | IN- | Inverted Input Signal |
| 5 | TH | Loss-of-Signal Threshold Pin. Resistor to ground sets the LOS threshold. |
| 6, 12, 15, 20 | V_{CC} | Power Supply |
| 7 | CLOS | LOS Time-Constant Capacitor Connection. For SONET applications, $C_{CLOS} = 0.01\mu F$ is recommended. |
| 8 | SQUELCH | Squelch Input. The squelch function is disabled when SQUELCH is not connected or set to TTL low level. When SQUELCH is set to TTL high level and LOS is asserted, the data outputs (OUT+, OUT-) are forced to static levels. |
| 9 | LOS | Noninverted Loss-of-Signal Output. LOS is asserted TTL high when the signal drops below the assert threshold set by the TH input. The MAX3272 does not have ESD protection on this pin. The MAX3272A has ESD protection on this pin. |
| 10 | \overline{LOS} | Inverted Loss-of-Signal Output. LOS is asserted TTL low when the signal drops below the assert threshold set by the TH input. The MAX3272 does not have ESD protection on this pin. The MAX3272A has ESD protection on this pin. |
| 11 | LEVEL | Output Current Level. When this pin is not connected, the CML output current is approximately 16mA. When this pin is connected to ground, the output current increases to about 20mA. |
| 13 | OUT- | Inverted Data Output |
| 14 | OUT+ | Noninverted Data Output |
| 16 | OUTPOL | Output Polarity Control Input. Connect to GND for an inversion of polarity through the limiting amplifier and connect to V_{CC} for normal operation. |
| 18 | CAZ2 | Offset-Correction-Loop Capacitor Connection. A capacitor connected between this pin and CAZ1 extends the time constant of the offset correction loop. Typical value of C_{AZ} is $0.1\mu F$. |
| 19 | CAZ1 | Offset-Correction-Loop Capacitor Connection. A capacitor connected between this pin and CAZ2 extends the time constant of the offset correction loop. Typical value of C_{AZ} is $0.1\mu F$. |
| EP | EXPOSED PAD | Connect the exposed paddle to board ground for optimal electrical and thermal performance. |

+3.3V, 2.5Gbps Low-Power Limiting Amplifiers




Figure 1. Power-Supply Current Measurement

Detailed Description

Figure 2 is a functional diagram of the MAX3272/MAX3272A, comprising a CML input buffer, power detector and loss-of-signal indicators, gain stage, offset-correction loop, and CML output buffer.

CML Input Buffer

The input buffer (Figure 3) provides 100Ω input impedance between IN+ and IN-. DC-coupling the inputs is not recommended; this prevents the DC offset-correction circuitry from functioning properly.

Power Detect and Loss-of-Signal Indicator

The MAX3272/MAX3272A are equipped with loss-of-signal (LOS) circuitry that indicates when the input signal is below a programmable threshold, set by resistor R_{TH} at the TH pin (see the *Typical Operating Characteristics* for appropriate resistor selection). An averaging peak-power detector compares the input signal amplitude with this threshold and feeds the signal-detect information to the LOS outputs, which are internally terminated to 8kΩ (Figure 4).




Figure 2. Functional Diagram

+3.3V, 2.5Gbps Low-Power Limiting Amplifiers

Interface Schematics




Figure 3. Input Circuit

Two control voltages V_{ASSERT} , and V_{DEASSERT} , define the LOS assert and deassert levels. To prevent LOS chatter in the region of the programmed threshold, approximately 3.3dB of hysteresis is built into the LOS assert/deassert function. Once asserted, LOS is not deasserted until the input amplitude rises to the required level (V_{DEASSERT}).

To facilitate interfacing with +5V modules, the LOS and $\overline{\text{LOS}}$ pins on the MAX3272 do not have internal ESD protection. If ESD protection is desired, a low-capacitance Schottky diode or diode array structure, such as the MAX3202E, is recommended (see the *Typical Operating Circuits*).

The LOS and $\overline{\text{LOS}}$ pins on the MAX3272A include ESD protection and, as a result, cannot be interfaced with +5V modules.

Gain Stage

The high-bandwidth gain stage provides approximately 42dB of gain.




Figure 4a. LOS Output Circuit for MAX3272




Figure 4b. LOS Output Circuit for MAX3272A

Offset-Correction Loop

Due to the high gain of the amplifier, the MAX3272/MAX3272A are susceptible to DC offsets in the signal path. In communications systems using NRZ data with a 50% duty cycle, pulse-width distortion present in the signal or generated by the transimpedance amplifier appears as input offset and is removed by the offset-cancellation loop. An external capacitor is required between CAZ1 and CAZ2 to decouple the offset-cancellation loop and determine the lower 3dB frequency of the signal path.

+3.3V, 2.5Gbps Low-Power Limiting Amplifiers




Figure 5. CML Output Circuit

CML Output Buffer

The MAX3272/MAX3272A CML output circuit (Figure 5) provides high tolerance to impedance mismatches and inductive connectors. The output current can be set to two levels using the LEVEL pin. When LEVEL is unconnected, the output current is approximately 16mA. Connecting LEVEL to ground sets the output current to approximately 20mA. The squelch function is enabled when the SQUELCH pin is set to a TTL high. This function holds OUT+ and OUT- to a static level whenever the input signal amplitude drops below the loss-of-signal threshold. This circuit is also equipped with a polarity selector, programmed by the OUTPOL pin. When this pin is connected to VCC, no inversion will occur. When connected to ground, the output signal will be inverted.

Design Procedure

Program the LOS Assert Threshold

External resistor R_{TH} programs the loss-of-signal threshold. See the LOS Threshold vs. R_{TH} graph in the *Typical Operating Characteristics* section to select the appropriate resistor.

Select the Coupling Capacitors

When AC-coupling, input and output coupling capacitors (C_{IN} and C_{OUT}) should be selected to minimize the receiver's deterministic jitter. Jitter is decreased as the input low-frequency cutoff (f_{IN}) is decreased:

$$f_{IN} = 1 / [2\pi(50)(C_{IN})]$$

For ATM/SONET or other applications using scrambled NRZ data, select (C_{IN} , C_{OUT}) $\geq 0.1\mu F$, which provides $f_{IN} < 32kHz$. For Fibre Channel, Gigabit Ethernet, or other applications using 8B/10B data coding, select (C_{IN} , C_{OUT}) $\geq 0.01\mu F$, which provides $f_{IN} < 320kHz$. Refer to application note HFAN-1.1: *Choosing AC-Coupling Capacitors*.

Select the Offset-Correction Capacitor

The capacitor between CAZ1 and CAZ2 determines the time constant of the signal path DC offset-cancellation loop. To maintain stability, it is important to keep a one-decade separation between f_{IN} and the low-frequency cutoff (f_{OC}) associated with the DC offset-cancellation circuit. For ATM/SONET or other applications using scrambled NRZ data, $f_{IN} < 32kHz$, so $f_{OCMAX} < 3.2kHz$. Therefore, $CAZ = 0.1\mu F$ ($f_{OC} = 2kHz$). For Fibre Channel or Gigabit Ethernet applications, leave pins CAZ1 and CAZ2 open.

Program the LOS Time Constant


External capacitor C_{CLOS} programs the LOS assert and deassert times. When inputting data with many consecutive identical digits (CIDs), a longer time constant may be advantageous, so LOS does not flag incorrectly. In this case, connect the CLOS pin to a $0.01\mu F$ capacitor to set the assert time in the range of $2\mu s$ to $100\mu s$. For scrambled data where the mark density is kept at 50%, a shorter time constant may be desirable. Leave the CLOS pin open for a shorter time constant of about $1\mu s$.

+3.3V, 2.5Gbps Low-Power Limiting Amplifiers

MAX3272/MAX3272A


Pin Configuration

TOP VIEW



QFN*

NOTE: EXPOSED PAD MUST BE CONNECTED TO SUPPLY GROUND.



THIN QFN*

NOTE: EXPOSED PAD MUST BE CONNECTED TO SUPPLY GROUND.

Pad Coordinates

| PAD | NAME | COORDINATES (μm) |
|-----|---------|------------------|
| 1 | GND | 47, 836 |
| 2 | IN+ | 47, 603 |
| 3 | IN- | 47, 425 |
| 4 | GND | 47, 237 |
| 5 | TH | 47, 47 |
| 6 | VCC | 255, -154 |
| 7 | CLOS | 436, -154 |
| 8 | SQUELCH | 645, -154 |
| 9 | LOS | 850, -154 |
| 10 | LOS | 1063, -154 |
| 11 | LEVEL | 1331, 37 |
| 12 | VCC | 1331, 212 |
| 13 | OUT- | 1331, 421 |
| 14 | OUT+ | 1331, 573 |
| 15 | VCC | 1331, 780 |
| 16 | OUTPOL | 1119, 1042 |
| 17 | GND | 957, 1042 |
| 18 | CAZ2 | 773, 1042 |
| 19 | CAZ1 | 583, 1042 |
| 20 | N.C. | 422, 1042 |
| 21 | VCC | 268, 1042 |

Coordinates are for the center of the pad.

Coordinate 0, 0 is the lower left corner of the passivation opening for pad 5.

Applications Information

Optical Hysteresis

In an optical receiver, the electrical power change at the limiting amplifier is 2 times the optical power change.

As an example, if a receiver's optical input power (x) increases by a factor of two, and the preamplifier is linear, then the voltage input to the limiting amplifier also increases by a factor of two.

The optical power change is $10\log(2x/x) = 10\log(2) = +3\text{dB}$.


At the limiting amplifier, the electrical power change is:

$$10\log \frac{(2V_{IN})^2 / R_{IN}}{V_{IN}^2 / R_{IN}} = 10\log(2^2) = 20\log(2) = +6\text{dB}$$

The MAX3272 typical voltage hysteresis is 3.3dB. This provides an optical hysteresis of 1.65dB.

+3.3V, 2.5Gbps Low-Power Limiting Amplifiers

Typical Operating Circuit (continued)




Wire Bonding Die

For high-current density and reliable operation, the MAX3272 uses gold metallization. Make connections to the dice with gold wire only, and use ball-bonding techniques (wedge bonding is not recommended). Die pad dimensions are 94.4 microns by 94.4 microns. Die thickness is 15 mils (0.375mm).

+3.3V, 2.5Gbps Low-Power Limiting Amplifiers

Chip Information

MAX3272/MAX3272A



TRANSISTOR COUNT: 726

PROCESS: SiGe Bipolar


SUBSTRATE: Insulator, Connect to GND

DIE SIZE: 1.68mm × 1.57mm

DIE THICKNESS: 15 mils

MAX3272/MAX3272A

(The package drawing(s) in this data sheet may not reflect the most current specifications. For the latest package outline information, go to www.maxim-ic.com/packages.)



+3.3V, 2.5Gbps Low-Power Limiting Amplifiers

Package Information (continued)

(The package drawing(s) in this data sheet may not reflect the most current specifications. For the latest package outline information, go to www.maxim-ic.com/packages.)

MAX3272/MAX3272A

NOTES:

1. DIE THICKNESS ALLOWABLE IS 0.305mm MAXIMUM (.012 INCHES MAXIMUM).
2. DIMENSIONING & TOLERANCES CONFORM MUST TO ASME Y14.5M. – 1994.
3. N IS THE NUMBER OF TERMINALS.
Nd IS THE NUMBER OF TERMINALS IN X-DIRECTION &
Ne IS THE NUMBER OF TERMINALS IN Y-DIRECTION.
4. DIMENSION b APPLIES TO PLATED TERMINAL AND IS MEASURED BETWEEN 0.20 AND 0.25mm FROM TERMINAL TIP.
5. THE PIN #1 IDENTIFIER MUST BE EXISTED ON THE TOP SURFACE OF THE PACKAGE BY USING INDENTATION MARK OR INK/LASER MARKED. DETAILS OF PIN #1 IDENTIFIER IS OPTIONAL, BUT MUST BE LOCATED WITHIN ZONE INDICATED.
6. EXACT SHAPE AND SIZE OF THIS FEATURE IS OPTIONAL.
7. ALL DIMENSIONS ARE IN MILLIMETERS.
8. PACKAGE WARPAGE MAX 0.05mm.
9. APPLIED FOR EXPOSED PAD AND TERMINALS.
EXCLUDE EMBEDDING PART OF EXPOSED PAD FROM MEASURING.
10. MEETS JEDEC MO220; EXCEPT DIMENSION "b".
11. THIS PACKAGE OUTLINE APPLIES TO PUNCHED QFN (STEPPED SIDES).

| | COMMON DIMENSIONS | | | N _D | N _E |
|----|-------------------|------|------|----------------|----------------|
| | MIN. | NOM. | MAX. | | |
| A | 0.80 | 0.90 | 1.00 | | |
| A1 | 0.00 | 0.01 | 0.05 | | |
| A2 | 0.00 | 0.65 | 0.80 | | |
| A3 | 0.20 REF. | | | | |
| D | 4.00 BSC | | | | |
| D1 | 3.75 BSC | | | | |
| E | 4.00 BSC | | | | |
| E1 | 3.75 BSC | | | | |
| θ | 0° | — | 12° | | |
| P | 0.24 | 0.42 | 0.60 | | |

| PITCH VARIATION A | MIN. | NOM. | MAX. | N _D | N _E | PITCH VARIATION B | MIN. | NOM. | MAX. | N _D | N _E | PITCH VARIATION C | MIN. | NOM. | MAX. | N _D | N _E | PITCH VARIATION D | MIN. | NOM. | MAX. | N _D | N _E |
|-------------------|------|------|------|----------------|----------------|-------------------|------|------|------|----------------|----------------|-------------------|------|------|------|----------------|----------------|-------------------|------|------|------|----------------|----------------|
| | | | | | | | | | | | | | | | | | | | | | | | |
| 0.80 BSC | | | | | | 0.65 BSC | | | | | | 0.50 BSC | | | | | | 0.50 BSC | | | | | |
| N | 12 | | | 3 | N | 16 | | | | 3 | N | 20 | | | | 3 | N | 24 | | | | 3 | N |
| Nd | 3 | | | 3 | Nd | 4 | | | | 3 | Nd | 5 | | | | 3 | Nd | 6 | | | | 3 | Nd |
| Ne | 3 | | | 3 | Ne | 4 | | | | 3 | Ne | 5 | | | | 3 | Ne | 6 | | | | 3 | Ne |
| L | 0.50 | 0.60 | 0.75 | | L | 0.50 | 0.60 | 0.75 | | L | 0.50 | 0.60 | 0.75 | | L | 0.50 | 0.60 | 0.75 | | L | 0.30 | 0.40 | 0.50 |
| b | 0.28 | 0.33 | 0.40 | 4 | b | 0.23 | 0.28 | 0.35 | 4 | b | 0.18 | 0.23 | 0.30 | 4 | b | 0.18 | 0.23 | 0.30 | 4 | b | 0.18 | 0.23 | 0.30 |


| PKG. CODE | EXPOSED PAD VARIATION | | | | | |
|-----------|-----------------------|------|------|------|------|------|
| | D2 | | | E2 | | |
| | MIN. | NOM. | MAX. | MIN. | NOM. | MAX. |
| G1244-2 | 1.95 | 2.10 | 2.25 | 1.95 | 2.10 | 2.25 |
| G1644-1 | 1.95 | 2.10 | 2.25 | 1.95 | 2.10 | 2.25 |
| G2044-3 | 1.95 | 2.10 | 2.25 | 1.95 | 2.10 | 2.25 |
| G2044-4 | 1.55 | 1.70 | 1.85 | 1.55 | 1.70 | 1.85 |
| G2444-1 | 1.95 | 2.10 | 2.25 | 1.95 | 2.10 | 2.25 |

| | | | |
|--|---------------------------------|---|-----|
|  DALLAS SEMICONDUCTOR | |  | |
| PROPRIETARY INFORMATION | | | |
| TITLE: PACKAGE OUTLINE 12,16,20,24L QFN, 4x4x0.90 MM | | | |
| APPROVAL | DOCUMENT CONTROL NO. 21-0106 | REV. E | 2/2 |

+3.3V, 2.5Gbps Low-Power Limiting Amplifiers

Package Information (continued)

(The package drawing(s) in this data sheet may not reflect the most current specifications. For the latest package outline information, go to www.maxim-ic.com/packages.)



| COMMON DIMENSIONS | | | | | | | | | | | | |
|-------------------|-----------|------|------|-----------|------|------|-----------|------|------|-----------|------|------|
| PKG | 12L 4x4 | | | 16L 4x4 | | | 20L 4x4 | | | 24L 4x4 | | |
| REF. | MIN. | NDM. | MAX. | MIN. | NDM. | MAX. | MIN. | NDM. | MAX. | MIN. | NDM. | MAX. |
| A | 0.70 | 0.75 | 0.80 | 0.70 | 0.75 | 0.80 | 0.70 | 0.75 | 0.80 | 0.70 | 0.75 | 0.80 |
| AL | 0.0 | 0.02 | 0.05 | 0.0 | 0.02 | 0.05 | 0.0 | 0.02 | 0.05 | 0.0 | 0.02 | 0.05 |
| A2 | 0.20 REF. | | | 0.20 REF. | | | 0.20 REF. | | | 0.20 REF. | | |
| b | 0.25 | 0.30 | 0.35 | 0.25 | 0.30 | 0.35 | 0.20 | 0.25 | 0.30 | 0.18 | 0.23 | 0.30 |
| D | 3.90 | 4.00 | 4.10 | 3.90 | 4.00 | 4.10 | 3.90 | 4.00 | 4.10 | 3.90 | 4.00 | 4.10 |
| E | 3.90 | 4.00 | 4.10 | 3.90 | 4.00 | 4.10 | 3.90 | 4.00 | 4.10 | 3.90 | 4.00 | 4.10 |
| e | 0.80 BSC. | | | 0.65 BSC. | | | 0.50 BSC. | | | 0.50 BSC. | | |
| k | 0.25 | - | - | 0.25 | - | - | 0.25 | - | - | 0.25 | - | - |
| L | 0.45 | 0.55 | 0.65 | 0.45 | 0.55 | 0.65 | 0.45 | 0.55 | 0.65 | 0.30 | 0.40 | 0.50 |
| N | 12 | | | 16 | | | 20 | | | 24 | | |
| ND | 3 | | | 4 | | | 5 | | | 6 | | |
| NE | 3 | | | 4 | | | 5 | | | 6 | | |
| Wdec | WGGB | | | WGGB | | | WGGB-1 | | | WGGB-2 | | |

| EXPOSED PAD VARIATIONS | | | | | | | | | | | | |
|------------------------|------|------|------|------|------|------|--------------------|--|--|--|--|--|
| PKG CODES | D2 | | | E2 | | | DOWN BONDS ALLOWED | | | | | |
| | MIN. | NDM. | MAX. | MIN. | NDM. | MAX. | | | | | | |
| T1244-2 | 1.95 | 2.30 | 2.25 | 1.95 | 2.10 | 2.25 | YES | | | | | |
| T1244-3 | 1.95 | 2.30 | 2.25 | 1.95 | 2.10 | 2.25 | NO | | | | | |
| T1244-4 | 1.95 | 2.30 | 2.25 | 1.95 | 2.10 | 2.25 | NO | | | | | |
| T1644-2 | 1.95 | 2.30 | 2.25 | 1.95 | 2.10 | 2.25 | NO | | | | | |
| T1644-3 | 1.95 | 2.30 | 2.25 | 1.95 | 2.10 | 2.25 | YES | | | | | |
| T1644-4 | 1.95 | 2.30 | 2.25 | 1.95 | 2.10 | 2.25 | NO | | | | | |
| T2044-1 | 1.95 | 2.30 | 2.25 | 1.95 | 2.10 | 2.25 | NO | | | | | |
| T2044-2 | 1.95 | 2.30 | 2.25 | 1.95 | 2.10 | 2.25 | YES | | | | | |
| T2044-3 | 1.95 | 2.30 | 2.25 | 1.95 | 2.10 | 2.25 | NO | | | | | |
| T2444-1 | 2.45 | 2.60 | 2.63 | 2.45 | 2.60 | 2.63 | NO | | | | | |
| T2444-2 | 1.95 | 2.30 | 2.25 | 1.95 | 2.10 | 2.25 | YES | | | | | |
| T2444-3 | 2.45 | 2.60 | 2.63 | 2.45 | 2.60 | 2.63 | YES | | | | | |
| T2444-4 | 2.45 | 2.60 | 2.63 | 2.45 | 2.60 | 2.63 | NO | | | | | |

NOTES:

- DIMENSIONING & TOLERANCING CONFORM TO ASME Y14.5M-1994.
- ALL DIMENSIONS ARE IN MILLIMETERS. ANGLES ARE IN DEGREES.
- N IS THE TOTAL NUMBER OF TERMINALS.
- THE TERMINAL #1 IDENTIFIER AND TERMINAL NUMBERING CONVENTION SHALL CONFORM TO JEDEC 95-1 SFP-012. DETAILS OF TERMINAL #1 IDENTIFIER ARE OPTIONAL, BUT MUST BE LOCATED WITHIN THE ZONE INDICATED. THE TERMINAL #1 IDENTIFIER MAY BE EITHER A MOLD OR MARKED FEATURE.
- DIMENSION b APPLIES TO METALLIZED TERMINAL AND IS MEASURED BETWEEN 0.25 mm AND 0.30 mm FROM TERMINAL TIP.
- ND AND NE REFER TO THE NUMBER OF TERMINALS ON EACH D AND E SIDE RESPECTIVELY.
- DEPOPULATION IS POSSIBLE IN A SYMMETRICAL FASHION.
- COPLANARITY APPLIES TO THE EXPOSED HEAT SINK SLUG AS WELL AS THE TERMINALS.
- DRAWING CONFORMS TO JEDEC MO220, EXCEPT FOR T2444-1, T2444-3 AND T2444-4.

DALLAS MAXIM SEMICONDUCTOR

PROPRIETARY INFORMATION

TITLE PACKAGE OUTLINE
12, 16, 20, 24L THIN QFN, 4x4x0.8mm

APPROVAL **DOCUMENT CONTROL NO.** 21-0139 **REV.** C **2/2**

Maxim cannot assume responsibility for use of any circuitry other than circuitry entirely embodied in a Maxim product. No circuit patent licenses are implied. Maxim reserves the right to change the circuitry and specifications without notice at any time.

14 **Maxim Integrated Products, 120 San Gabriel Drive, Sunnyvale, CA 94086 408-737-7600**

Mouser Electronics

Authorized Distributor

Click to View Pricing, Inventory, Delivery & Lifecycle Information:

[Analog Devices Inc.:](#)

[MAX3272AETP+](#)