

## MAX705–MAX708/MAX813L

## Low-Cost, $\mu$ P Supervisory Circuits

### General Description

The MAX705–MAX708/MAX813L microprocessor ( $\mu$ P) supervisory circuits reduce the complexity and number of components required to monitor power-supply and battery functions in  $\mu$ P systems. These devices significantly improve system reliability and accuracy compared to separate ICs or discrete components.

The MAX705/MAX706/MAX813L provide four functions:

- 1) A reset output during power-up, power-down, and brownout conditions.
- 2) An independent watchdog output that goes low if the watchdog input has not been toggled within 1.6 seconds.
- 3) A 1.25V threshold detector for power-fail warning, low-battery detection, or for monitoring a power supply other than +5V.
- 4) An active-low manual-reset input.

The MAX707/MAX708 are the same as the MAX705/MAX706, except an active-high reset is substituted for the watchdog timer. The MAX813L is the same as the MAX705, except RESET is provided instead of  $\overline{\text{RESET}}$ .

Two supply-voltage monitor levels are available: The MAX705/MAX707/MAX813L generate a reset pulse when the supply voltage drops below 4.65V, while the MAX706/MAX708 generate a reset pulse below 4.40V. All four parts are available in 8-pin DIP, SO, and  $\mu$ MAX® packages.

### Applications

- Computers
- Controllers
- Intelligent Instruments
- Critical  $\mu$ P Power Monitoring

**Pin Configurations** appear at end of data sheet.

$\mu$ MAX is a registered trademark of Maxim Integrated Products, Inc.

### Benefits and Features

- Supervisory-Function Integration Significantly Improves System Reliability While Reducing Board Space
  - $\mu$ MAX Package
  - Guaranteed RESET Valid at  $V_{CC} = 1V$ 
    - 200ms Reset Pulse Width
    - Debounced TTL/CMOS-Compatible Manual-Reset Input
    - Active-High Reset Output (MAX707/MAX708/MAX813L)
  - Precision-Supply Voltage Monitor
    - 4.65V (MAX705/MAX707/MAX813L)
    - 4.40V (MAX706/MAX708)
  - Voltage Monitor for Power-Fail or Low-Battery Warning

### Ordering Information

| PART      | TEMP RANGE   | PIN-PACKAGE   |
|-----------|--------------|---------------|
| MAX705CPA | 0°C to +70°C | 8 Plastic DIP |
| MAX705CSA | 0°C to +70°C | 8 SO          |
| MAX705CUA | 0°C to +70°C | 8 $\mu$ MAX   |
| MAX705C/D | 0°C to +70°C | Dice*         |


\*Dice are specified at  $T_A = +25^\circ\text{C}$ .

\*\*Contact factory for availability and processing to MIL-STD-883. Devices in PDIP, SO, and  $\mu$ MAX packages are available in both leaded and lead(Pb)-free/RoHS-compliant packaging. Specify lead-free by adding the + symbol at the end of the part number when ordering.

Lead-free packaging is not available for Cerdip packages.

**Ordering Information** continued at end of data sheet.

### Typical Operating Circuit



## Absolute Maximum Ratings

Terminal Voltage (with respect to GND)

$V_{CC}$ .....-0.3V to 6.0V

All Other Inputs (Note 1) .....-0.3V to ( $V_{CC} + 0.3$ V)

Input Current

$V_{CC}$ .....20mA

GND .....20mA

Output Current (all outputs).....20mA

Continuous Power Dissipation ( $T_A = +70^\circ\text{C}$ )

Plastic DIP (derate 9.09mW/ $^\circ\text{C}$  above  $+70^\circ\text{C}$ ).....727mW

SO (derate 5.88mW/ $^\circ\text{C}$  above  $+70^\circ\text{C}$ ).....471mW

$\mu$ MAX (derate 4.10mW/ $^\circ\text{C}$  above  $+70^\circ\text{C}$ ) .....330mW

CERDIP (derate 8.00mW/ $^\circ\text{C}$  above  $+70^\circ\text{C}$ ).....640mW

Operating Temperature Ranges

MAX70\_C\_, MAX813LC\_ ..... $0^\circ\text{C}$  to  $+70^\circ\text{C}$

MAX70\_E\_, MAX813LE\_ ..... $-40^\circ\text{C}$  to  $+85^\circ\text{C}$

MAX70\_MJA..... $-55^\circ\text{C}$  to  $+125^\circ\text{C}$

Storage Temperature Range..... $-65^\circ\text{C}$  to  $+160^\circ\text{C}$

Lead Temperature (soldering, 10s) ..... $+300^\circ\text{C}$

Soldering Temperature (reflow)

Lead(Pb)-free..... $+260^\circ\text{C}$

Containing Lead(Pb)..... $+240^\circ\text{C}$

**Note 1:** The input-voltage limits on PFI and  $\overline{\text{MR}}$  can be exceeded if the input current is less than 10mA.

Stresses beyond those listed under "Absolute Maximum Ratings" may cause permanent damage to the device. These are stress ratings only, and functional operation of the device at these or any other conditions beyond those indicated in the operational sections of the specifications is not implied. Exposure to absolute maximum rating conditions for extended periods may affect device reliability.

## Electrical Characteristics

( $V_{CC} = 4.75\text{V}$  to  $5.5\text{V}$  for MAX705/MAX707/MAX813L,  $V_{CC} = 4.5\text{V}$  to  $5.5\text{V}$  for MAX706/MAX708,  $T_A = T_{\text{MIN}}$  to  $T_{\text{MAX}}$ , unless otherwise noted.)

| PARAMETER                                | SYMBOL              | CONDITIONS                                                              | MIN                                  | TYP  | MAX            | UNITS         |
|------------------------------------------|---------------------|-------------------------------------------------------------------------|--------------------------------------|------|----------------|---------------|
| Operating Voltage Range                  | $V_{CC}$            | MAX70_C                                                                 | 1.0                                  |      | 5.5            | V             |
|                                          |                     | MAX813LC                                                                | 1.1                                  |      | 5.5            |               |
|                                          |                     | MAX70_E/M, MAX813LE/M                                                   | 1.2                                  |      | 5.5            |               |
| Supply Current                           | $I_{\text{SUPPLY}}$ | MAX705C, MAX706C, MAX813LC                                              |                                      | 150  | 350            | $\mu\text{A}$ |
|                                          |                     | MAX705E/M, MAX706E/M, MAX813LE/M                                        |                                      | 150  | 500            |               |
|                                          |                     | MAX707C, MAX708C                                                        |                                      | 50   | 350            |               |
|                                          |                     | MAX707E/M, MAX708E/M                                                    |                                      | 50   | 500            |               |
| Reset Threshold (Note 2)                 | $V_{\text{RT}}$     | MAX705, MAX707, MAX813L                                                 | 4.50                                 | 4.65 | 4.75           | V             |
|                                          |                     | MAX706, MAX708                                                          | 4.25                                 | 4.40 | 4.50           |               |
| Reset Threshold Hysteresis (Note 2)      |                     |                                                                         |                                      | 40   |                | mV            |
| Reset Pulse Width (Note 2)               | $t_{\text{RS}}$     |                                                                         | 140                                  | 200  | 280            | ms            |
| $\overline{\text{RESET}}$ Output Voltage |                     | $I_{\text{SOURCE}} = 800\mu\text{A}$                                    | $V_{CC} - 1.5$                       |      |                | V             |
|                                          |                     | $I_{\text{SINK}} = 3.2\text{mA}$                                        |                                      |      | 0.4            |               |
|                                          |                     | MAX70_C, $V_{CC} = 1\text{V}$ , $I_{\text{SINK}} = 50\mu\text{A}$       |                                      |      | 0.3            |               |
|                                          |                     | MAX70_E/M, $V_{CC} = 1.2\text{V}$ , $I_{\text{SINK}} = 100\mu\text{A}$  |                                      |      | 0.3            |               |
| RESET Output Voltage                     |                     | MAX707, MAX708, $I_{\text{SOURCE}} = 800\mu\text{A}$                    | $V_{CC} - 1.5$                       |      |                | V             |
|                                          |                     | MAX707, MAX708, $I_{\text{SINK}} = 1.2\text{mA}$                        |                                      |      | 0.4            |               |
|                                          |                     | MAX813LC, $I_{\text{SOURCE}} = 4\mu\text{A}$ , $V_{CC} = 1.1\text{V}$   | 0.8                                  |      |                |               |
|                                          |                     | MAX813LE/M, $I_{\text{SOURCE}} = 4\mu\text{A}$ , $V_{CC} = 1.2\text{V}$ | 0.9                                  |      |                |               |
|                                          |                     | MAX813L                                                                 | $I_{\text{SOURCE}} = 800\mu\text{A}$ |      | $V_{CC} - 1.5$ |               |
|                                          |                     |                                                                         | $I_{\text{SINK}} = 3.2\text{mA}$     |      | 0.4            |               |


## Electrical Characteristics (continued)

( $V_{CC}$  = 4.75V to 5.5V for MAX705/MAX707/MAX813L,  $V_{CC}$  = 4.5V to 5.5V for MAX706/MAX708,  $T_A$  =  $T_{MIN}$  to  $T_{MAX}$ , unless otherwise noted.)

| PARAMETER                                   |      | SYMBOL          | CONDITIONS                                                         | MIN                   | TYP   | MAX    | UNITS |
|---------------------------------------------|------|-----------------|--------------------------------------------------------------------|-----------------------|-------|--------|-------|
| Watchdog Timeout Period                     |      | t <sub>WD</sub> | MAX705, MAX706, MAX813L                                            | 1.00                  | 1.60  | 2.25   | s     |
| WDI Pulse Width                             |      | t <sub>WP</sub> | V <sub>IL</sub> = 0.4V, V <sub>IH</sub> = (V <sub>CC</sub> ) (0.8) | 50                    |       |        | ns    |
| WDI Input Threshold                         | Low  |                 | MAX705, MAX706, MAX813L, V <sub>CC</sub> = 5V                      | 0.8                   |       |        | V     |
|                                             | High |                 |                                                                    | 3.5                   |       |        |       |
| WDI Input Current                           |      |                 | MAX705, MAX706, MAX813L, V <sub>CC</sub> = 5V                      | 50                    |       | 150    | μA    |
|                                             |      |                 | MAX705, MAX706, MAX813L, WDI = 0V                                  | -150                  | -50   |        |       |
| $\overline{WDO}$ Output Voltage             |      |                 | MAX705, MAX706, MAX813L, I <sub>SOURCE</sub> = 800μA               | V <sub>CC</sub> - 1.5 |       |        | V     |
|                                             |      |                 | MAX705, MAX706, MAX813L, I <sub>SINK</sub> = 1.2mA                 | 0.4                   |       |        |       |
| $\overline{MR}$ Pull-Up Current             |      |                 | $\overline{MR}$ = 0V                                               | 100                   | 250   | 600    | μA    |
| $\overline{MR}$ Pulse Width                 |      | t <sub>MR</sub> |                                                                    | 150                   |       |        | ns    |
| $\overline{MR}$ Input Threshold             | Low  |                 |                                                                    | 0.8                   |       |        | V     |
|                                             | High |                 |                                                                    | 2.0                   |       |        |       |
| $\overline{MR}$ to Reset Out Delay (Note 2) |      | t <sub>MD</sub> |                                                                    | 250                   |       |        | ns    |
| PFI Input Threshold                         |      |                 | V <sub>CC</sub> = 5V                                               | 1.20                  | 1.25  | 1.30   | V     |
| PFI Input Current                           |      |                 |                                                                    | -25.00                | +0.01 | +25.00 | nA    |
| $\overline{PFO}$ Output Voltage             |      |                 | I <sub>SOURCE</sub> = 800μA                                        | V <sub>CC</sub> - 1.5 |       |        | V     |
|                                             |      |                 | I <sub>SINK</sub> = 3.2mA                                          | 0.4                   |       |        |       |

**Note 2:** Applies to both  $\overline{RESET}$  in the MAX705–MAX708 and RESET in the MAX707/MAX708/MAX813L.

## Typical Operating Characteristics



## Pin Description

| PIN           |      |               |      |         |      | NAME  | FUNCTION                                                                                                                                                                                                                                                                                                                                                                                            |
|---------------|------|---------------|------|---------|------|-------|-----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| MAX705/MAX706 |      | MAX707/MAX708 |      | MAX813L |      |       |                                                                                                                                                                                                                                                                                                                                                                                                     |
| DIP/SO        | μMAX | DIP/SO        | μMAX | DIP/SO  | μMAX |       |                                                                                                                                                                                                                                                                                                                                                                                                     |
| 1             | 3    | 1             | 3    | 1       | 3    | MR    | Manual-Reset Input triggers a reset pulse when pulled below 0.8V. This active-low input has an internal 250μA pullup current. It can be driven from a TTL or CMOS logic line, as well as shorted to ground with a switch.                                                                                                                                                                           |
| 2             | 4    | 2             | 4    | 2       | 4    | VCC   | +5V Supply Input                                                                                                                                                                                                                                                                                                                                                                                    |
| 3             | 5    | 3             | 5    | 3       | 5    | GND   | 0V Ground Reference for all signals                                                                                                                                                                                                                                                                                                                                                                 |
| 4             | 6    | 4             | 6    | 4       | 6    | PFI   | Power-Fail Voltage-Monitor Input. When PFI is less than 1.25V, PFO goes low. Connect PFI to GND or VCC when not used.                                                                                                                                                                                                                                                                               |
| 5             | 7    | 5             | 7    | 5       | 7    | PFO   | Power-Fail Output goes low and sinks current when PFI is less than 1.25V; otherwise PFO stays high.                                                                                                                                                                                                                                                                                                 |
| 6             | 8    | —             | —    | 6       | 8    | WDI   | Watchdog Input. If WDI remains high or low for 1.6sec, the internal watchdog timer runs out and WDO goes low (Figure 1). Floating WDI or connecting WDI to a high-impedance three-state buffer disables the watchdog feature. The internal watchdog timer clears whenever reset is asserted, WDI is three stated, or WDI sees a rising or falling edge.                                             |
| —             | —    | 6             | —    | —       | —    | N.C.  | No Connect                                                                                                                                                                                                                                                                                                                                                                                          |
| 7             | 1    | 7             | 1    | —       | —    | RESET | Active-Low Reset Output pulses low for 200ms when triggered, and stays low whenever VCC is below the reset threshold (4.65V in the MAX705 and 4.40V in the MAX706). It remains low for 200ms after VCC rises above the reset threshold or MR goes from low to high (Figure 3). A watchdog timeout will not trigger RESET unless WDO is connected to MR.                                             |
| 8             | 2    | —             | —    | 8       | 2    | WDO   | Watchdog Output pulls low when the internal watchdog timer finishes its 1.6sec count and does not go high again until the watchdog is cleared. WDO also goes low during low-line conditions. Whenever VCC is below the reset threshold, WDO stays low; however, unlike RESET, WDO does not have a minimum pulse width. As soon as VCC rises above the reset threshold, WDO goes high with no delay. |
| —             | —    | 8             | 2    | 7       | 1    | RESET | Active-High RESET Output is the inverse of RESET. Whenever RESET is high, RESET is low, and vice versa (Figure 2). The MAX813L has a RESET output only.                                                                                                                                                                                                                                             |




Figure 1. MAX705/MAX706/MAX813L Block Diagram




Figure 2. MAX707/MAX708 Block Diagram

## Detailed Description

### Reset Output

A microprocessor's ( $\mu$ P's) reset input starts the  $\mu$ P in a known state. Whenever the  $\mu$ P is in an unknown state, it should be held in reset. The MAX705–MAX708/MAX813L assert reset during power-up and prevent code execution errors during power-down or brownout conditions.

On power-up, once  $V_{CC}$  reaches 1V,  $\overline{RESET}$  is a guaranteed logic low of 0.4V or less. As  $V_{CC}$  rises,  $\overline{RESET}$  stays low. When  $V_{CC}$  rises above the reset threshold, an internal timer releases  $\overline{RESET}$  after about 200ms.  $\overline{RESET}$  pulses low whenever  $V_{CC}$  dips below the reset threshold, i.e. brownout condition. If brownout occurs in the middle of a previously initiated reset pulse, the pulse continues for at least another 140ms. On power-down, once  $V_{CC}$  falls below the reset threshold,  $\overline{RESET}$  stays low and is guaranteed to be 0.4V or less until  $V_{CC}$  drops below 1V.

The MAX707/MAX708/MAX813L active-high  $\overline{RESET}$  output is simply the complement of the  $\overline{RESET}$  output, and is guaranteed to be valid with  $V_{CC}$  down to 1.1V. Some  $\mu$ Ps, such as Intel's 80C51, require an active-high reset pulse.

### Watchdog Timer

The MAX705/MAX706/MAX813L watchdog circuit monitors the  $\mu$ P's activity. If the  $\mu$ P does not toggle the watchdog input (WDI) within 1.6sec and WDI is not three

stated,  $\overline{WDO}$  goes low. As long as  $\overline{RESET}$  is asserted or the WDI input is three stated, the watchdog timer stays cleared and will not count. As soon as reset is released and WDI is driven high or low, the timer starts counting. Pulses as short as 50ns can be detected.

Typically,  $\overline{WDO}$  is not connected to the nonmaskable interrupt input (NMI) of a  $\mu$ P. When  $V_{CC}$  drops below the reset threshold,  $\overline{WDO}$  goes low whether or not the watchdog timer has timed out yet. Normally this would trigger an NMI interrupt, but  $\overline{RESET}$  goes low simultaneously, and thus overrides the NMI interrupt.

If WDI is left unconnected,  $\overline{WDO}$  can be used as a low-line output. Since floating WDI disables the internal timer,  $\overline{WDO}$  goes low only when  $V_{CC}$  falls below the reset threshold, thus functioning as a low-line output.

The MAX705/MAX706 have a watchdog timer and a  $\overline{RESET}$  output. The MAX707/MAX708 have both active-high and active-low reset outputs. The MAX813L has both an active-high reset output and a watchdog timer.

### Manual Reset

The manual-reset input ( $\overline{MR}$ ) allows reset to be triggered by a pushbutton switch. The switch is effectively debounced by the 140ms minimum reset pulse width.  $\overline{MR}$  is TTL/CMOS-logic compatible, so it can be driven by an external logic line.  $\overline{MR}$  can be used to force a watchdog timeout to generate a reset pulse in the MAX705/ MAX706/ MAX813L. Simply connect  $\overline{WDO}$  to  $\overline{MR}$ .

### Power-Fail Comparator

The power-fail comparator can be used for various purposes because its output and noninverting input are not internally connected. The inverting input is internally connected to a 1.25V reference.




Figure 3. MAX705/MAX706/MAX813L Watchdog Timing




Figure 4. MAX705/MAX706  $\overline{\text{RESET}}$ , MR, and  $\overline{\text{WDO}}$  Timing with WDI Three Stated. The MAX707/MAX708/MAX813L  $\overline{\text{RESET}}$  output is the inverse of  $\overline{\text{RESET}}$  shown.

To build an early-warning circuit for power failure, connect the PFI pin to a voltage divider (see *Typical Operating Circuit*). Choose the voltage divider ratio so that the voltage at PFI falls below 1.25V just before the +5V regulator drops out. Use  $\overline{\text{PFO}}$  to interrupt the  $\mu$ P so it can prepare for an orderly power-down.

### Applications Information

#### Ensuring a Valid $\overline{\text{RESET}}$ Output Down to $V_{CC} = 0V$

When  $V_{CC}$  falls below 1V, the MAX705–MAX708  $\overline{\text{RESET}}$  output no longer sinks current—it becomes an open circuit. High-impedance CMOS logic inputs can drift to undetermined voltages if left undriven. If a pulldown resistor is added to the  $\overline{\text{RESET}}$  pin, as shown in Figure 5, any stray charge or leakage currents will be drained to ground, holding  $\overline{\text{RESET}}$  low. Resistor value (R1) is not critical. It should be about 100k $\Omega$ , large enough not to load  $\overline{\text{RESET}}$  and small enough to pull  $\overline{\text{RESET}}$  to ground.

#### Monitoring Voltages Other Than the Unregulated DC Input

Monitor voltages other than the unregulated DC by connecting a voltage-divider to PFI and adjusting the ratio appropriately. If required, add hysteresis by connecting a resistor (with a value approximately 10 times the sum of the two resistors in the potential divider network) between PFI and  $\overline{\text{PFO}}$ . A capacitor between PFI and GND reduces the power-fail circuit's sensitivity to high-frequency noise on the line being monitored.  $\overline{\text{RESET}}$  can be asserted on other voltages in addition to the +5V  $V_{CC}$  line. Connect  $\overline{\text{PFO}}$  to MR to initiate a  $\overline{\text{RESET}}$  pulse when PFI drops below 1.25V. Figure 6 shows the MAX705–MAX708 configured to assert  $\overline{\text{RESET}}$  when the +5V supply falls below the reset threshold, or when the +12V supply falls below approximately 11V.

#### Monitoring a Negative Voltage

The power-fail comparator can also monitor a negative supply rail (Figure 7). When the negative rail is good (a negative voltage of large magnitude),  $\overline{\text{PFO}}$  is low, and when the negative rail is degraded (a negative voltage of lesser magnitude),  $\overline{\text{PFO}}$  is high. By adding the resistors and transistor as shown, a high  $\overline{\text{PFO}}$  triggers a reset. As long as  $\overline{\text{PFO}}$  remains high, the MAX705–MAX708/MAX813L keep reset asserted ( $\overline{\text{RESET}} = \text{low}$ ,  $\text{RESET} = \text{high}$ ). Note that this circuit's accuracy depends on the PFI threshold tolerance, the  $V_{CC}$  line, and the resistors.




Figure 5. RESET Valid to Ground Circuit




Figure 6. Monitoring Both +5V and +12V




Figure 7. Monitoring a Negative Voltage




Figure 8. Interfacing to  $\mu$ Ps with Bidirectional Reset Pins

### Interfacing to $\mu$ Ps with Bidirectional Reset Pins

$\mu$ Ps with bidirectional reset pins, such as the Motorola 68HC11 series, can contend with the MAX705–MAX708 RESET output. If, for example, the RESET output is driven high and the  $\mu$ P wants to pull it low, indeterminate logic levels may result. To correct this, connect a 4.7k $\Omega$  resistor between the RESET output and the  $\mu$ P reset I/O, as in Figure 8. Buffer the RESET output to other system components.



## Ordering Information (continued)

| PART              | TEMP RANGE      | PIN-PACKAGE   |
|-------------------|-----------------|---------------|
| MAX705EPA         | -40°C to +85°C  | 8 Plastic DIP |
| MAX705ESA         | -40°C to +85°C  | 8 SO          |
| MAX705EUA         | -40°C to +85°C  | 8 $\mu$ MAX   |
| MAX705MJA         | -55°C to +125°C | 8 Cerdip**    |
| <b>MAX706CPA</b>  | 0°C to +70°C    | 8 Plastic DIP |
| MAX706CSA         | 0°C to +70°C    | 8 SO          |
| MAX706CUA         | 0°C to +70°C    | 8 $\mu$ MAX   |
| MAX706C/D         | 0°C to +70°C    | Dice*         |
| MAX706EPA         | -40°C to +85°C  | 8 Plastic DIP |
| MAX706ESA         | -40°C to +85°C  | 8 SO          |
| MAX706EUA         | -40°C to +85°C  | 8 $\mu$ MAX   |
| MAX706MJA         | -55°C to +125°C | 8 Cerdip**    |
| <b>MAX707CPA</b>  | 0°C to +70°C    | 8 Plastic DIP |
| MAX707CSA         | 0°C to +70°C    | 8 SO          |
| MAX707CUA         | 0°C to +70°C    | 8 $\mu$ MAX   |
| MAX707C/D         | 0°C to +70°C    | Dice*         |
| MAX707EPA         | -40°C to +85°C  | 8 Plastic DIP |
| MAX707ESA         | -40°C to +85°C  | 8 SO          |
| MAX707EUA         | -40°C to +85°C  | 8 $\mu$ MAX   |
| MAX707MJA         | -55°C to +125°C | 8 Cerdip**    |
| <b>MAX708CPA</b>  | 0°C to +70°C    | 8 Plastic DIP |
| MAX708CSA         | 0°C to +70°C    | 8 SO          |
| MAX708CUA         | 0°C to +70°C    | 8 $\mu$ MAX   |
| MAX708C/D         | 0°C to +70°C    | Dice*         |
| MAX708EPA         | -40°C to +85°C  | 8 Plastic DIP |
| MAX708ESA         | -40°C to +85°C  | 8 SO          |
| MAX708EUA         | -40°C to +85°C  | 8 $\mu$ MAX   |
| MAX708MJA         | -55°C to +125°C | 8 Cerdip**    |
| <b>MAX813LCPA</b> | 0°C to +70°C    | 8 Plastic DIP |
| MAX813LCSA        | 0°C to +70°C    | 8 SO          |
| MAX813LCUA        | 0°C to +70°C    | 8 $\mu$ MAX   |
| MAX813LC/D        | 0°C to +70°C    | Dice*         |
| MAX813LEPA        | -40°C to +85°C  | 8 Plastic DIP |
| MAX813LESA        | -40°C to +85°C  | 8 SO          |
| MAX813LEUA        | -40°C to +85°C  | 8 $\mu$ MAX   |
| MAX813LMJA        | -55°C to +125°C | 8 Cerdip**    |

\*Dice are specified at  $T_A = +25^\circ\text{C}$ .

\*\*Contact factory for availability and processing to MIL-STD-883. Devices in PDIP, SO and  $\mu$ MAX packages are available in both leaded and lead-free packaging. Specify lead free by adding the + symbol at the end of the part number when ordering. Lead-free not available for Cerdip package.

## Pin Configurations



## MAX705–MAX708/MAX813L

MAX705–MAX708/MAX813L  
Low-Cost,  $\mu$ P Supervisory Circuits


| Part Number     | Nominal Reset Threshold (V)                                           | Minimum Reset Pulse Width (ms) | Active-Low Reset | Active-High Reset | <u>RESET</u> Valid to $V_{CC} = 1V$ | Nominal Watchdog Timeout Period (sec), if Available | Separate Watchdog Output | Backup-Battery Switch | $V_{CC}$ -to- $V_{OUT}$ On Resistance Max ( $\Omega$ ) | BATT - to- $V_{OUT}$ On Resistance Max ( $\Omega$ ) | <u>CE</u> Write Protect | Power-Fail Comparator | Manual-Reset Input | Low-Line Output | Battery-On Output | Supply Operating Mode mA max (typ) | Supply Backup Mode $\mu A$ max (typ) | Pins | Price† 1000-up (\$) |
|-----------------|-----------------------------------------------------------------------|--------------------------------|------------------|-------------------|-------------------------------------|-----------------------------------------------------|--------------------------|-----------------------|--------------------------------------------------------|-----------------------------------------------------|-------------------------|-----------------------|--------------------|-----------------|-------------------|------------------------------------|--------------------------------------|------|---------------------|
| MAX1232         | 4.37/4.62                                                             | 250                            | ✓                | ✓                 | ✓                                   | 0.15/0.6/1.2                                        |                          | ✓                     |                                                        |                                                     |                         | ✓                     | ✓                  |                 |                   | 0.2(0.05)                          |                                      | 8    | 1.71                |
| MAX690A/692A    | 4.65/4.40                                                             | 140                            | ✓                |                   | ✓                                   | 1.6                                                 |                          | ✓                     | 10                                                     | 400                                                 |                         | ✓                     |                    |                 |                   | 0.35(0.2)                          | 5(0.05)                              | 8    | 3.26                |
| MAX690R/S/T     | 2.63/2.93/3.08                                                        | 140                            | ✓                |                   | ✓                                   | 1.6                                                 |                          | ✓                     | 6                                                      | 400                                                 |                         | ✓                     |                    |                 |                   | 0.5(0.4)                           | 1(0.4)                               | 8    | 3.23                |
| MAX691A/693A    | 4.65/4.40                                                             | 140/adj.                       | ✓                | ✓                 | ✓                                   | 1.6/adj.                                            | ✓                        | ✓                     | 1.2                                                    | 25                                                  | ✓/10ns                  | ✓                     |                    |                 | ✓                 | 0.1(0.035)                         | 5(0.04)                              | 16   | 3.61                |
| MAX1691         | The MAX1691 is a module with the MAX691A and a 125mAh lithium battery |                                |                  |                   |                                     |                                                     |                          |                       |                                                        |                                                     |                         |                       |                    |                 |                   |                                    |                                      |      |                     |
| MAX696          | Adj.                                                                  | 35/adj.                        | ✓                | ✓                 | ✓                                   | 1.6/adj.                                            | ✓                        | ✓                     |                                                        |                                                     |                         | ✓                     |                    |                 | ✓                 |                                    |                                      | 16   | 3.55                |
| MAX697          | Adj.                                                                  | 35/adj.                        | ✓                | ✓                 | ✓                                   | 1.6/adj.                                            | ✓                        | ✓                     |                                                        |                                                     | ✓                       | ✓                     |                    |                 |                   |                                    |                                      | 16   | 3.58                |
| MAX700          | 4.65/adj.                                                             | 200                            | ✓                | ✓                 |                                     |                                                     |                          |                       |                                                        |                                                     |                         |                       | ✓                  |                 |                   | 0.2(0.1)                           |                                      | 8    | 2.17                |
| MAX703/704      | 4.65/4.40                                                             | 140                            | ✓                |                   | ✓                                   |                                                     |                          | ✓                     | 10                                                     | 400                                                 |                         | ✓                     |                    |                 |                   | 0.35(0.2)                          | 5(0.05)                              | 8    | 1.38*               |
| MAX704R/S/T     | 2.63/2.93/3.08                                                        | 140                            | ✓                |                   | ✓                                   | 1.6                                                 | ✓                        | ✓                     | 6                                                      | 400                                                 |                         | ✓                     | ✓                  |                 |                   | 0.5(0.4)                           | 1(0.4)                               | 8    | 2.93                |
| MAX705/706      | 4.65/4.40                                                             | 140                            | ✓                |                   | ✓                                   | 1.6                                                 | ✓                        | ✓                     |                                                        |                                                     |                         | ✓                     | ✓                  |                 |                   | 0.35(0.2)                          |                                      | 8    | 1.02*               |
| MAX706P         | 2.63                                                                  | 140                            | ✓                | ✓                 | ✓                                   | 1.6                                                 | ✓                        | ✓                     |                                                        |                                                     |                         | ✓                     | ✓                  |                 |                   | 0.35(0.2)                          |                                      | 8    | 1.71                |
| MAX706R/S/T     | 2.63/2.93/3.08                                                        | 140                            | ✓                |                   | ✓                                   |                                                     |                          |                       |                                                        |                                                     |                         | ✓                     | ✓                  |                 |                   | 0.35(0.2)                          |                                      | 8    | 1.71                |
| MAX707/708      | 4.65/4.40                                                             | 140                            | ✓                | ✓                 | ✓                                   |                                                     |                          |                       |                                                        |                                                     |                         | ✓                     | ✓                  |                 |                   | 0.35(0.2)                          |                                      | 8    | 0.88*               |
| MAX708R/S/T     | 2.63/2.93/3.08                                                        | 140                            | ✓                | ✓                 | ✓                                   |                                                     |                          |                       |                                                        |                                                     |                         | ✓                     | ✓                  |                 |                   | 0.35(0.2)                          |                                      | 8    | 1.63                |
| MAX791          | 4.65                                                                  | 140                            | ✓                | ✓                 | ✓                                   | 1                                                   | ✓                        | ✓                     | 1.2                                                    | 25                                                  | ✓/10ns                  | ✓                     | ✓                  | ✓               | ✓                 | 0.15(0.06)                         | 5(0.04)                              | 16   | 3.90                |
| MAX802L/M/R/S/T | 4.60/4.40/<br>2.63/2.93/3.08                                          | 140                            | ✓                | ✓                 | ✓                                   | 1                                                   | ✓                        |                       |                                                        |                                                     | ✓/10ns                  | ✓                     |                    |                 |                   | 0.15(0.07)                         |                                      | 16   | 3.42                |
| MAX793R/S/U/T   | 2.63/2.93/3.07/3.08                                                   | 140                            | ✓                | ✓                 | ✓                                   | 1.6                                                 | ✓                        | ✓                     | TBD                                                    | TBD                                                 | ✓                       | ✓                     |                    |                 |                   | TBD                                | TBD                                  | 16   | ††                  |
| MAX794          | Adj.                                                                  | 140                            | ✓                | ✓                 | ✓                                   | 1.6                                                 | ✓                        | ✓                     | TBD                                                    | TBD                                                 | ✓                       | ✓                     |                    |                 |                   | TBD                                | TBD                                  | 8    | ††                  |
| MAX795R/S/U/T   | 2.63/2.93/3.07/3.08                                                   | 140                            | ✓                |                   | ✓                                   |                                                     |                          | ✓                     | TBD                                                    | TBD                                                 | ✓                       |                       |                    |                 |                   | TBD                                | TBD                                  | 16   | ††                  |
| MAX800L/M       | 4.60/4.40                                                             | 140                            | ✓                | ✓                 | ✓                                   | 1.6/adj.                                            | ✓                        | ✓                     | 1.2                                                    | 25                                                  | ✓/10ns                  | ✓/±2%                 |                    |                 | ✓                 | 0.1(0.035)                         | 5(0.04)                              | 8    | 3.88                |
| MAX801L/N/M     | 4.68/4.58/4.43                                                        | 140                            | ✓/±1.5%          |                   | ✓                                   | 1.6                                                 |                          | ✓                     | TBD                                                    | TBD                                                 |                         |                       |                    |                 |                   | TBD                                | TBD                                  | 8    | ††                  |
| MAX802L/M/R/S/T | 4.60/4.40/<br>2.63/2.93/3.08                                          | 140                            | ✓                |                   | ✓                                   | 1.6                                                 |                          | ✓                     | 10                                                     | 400                                                 |                         | ✓/±2%                 |                    |                 |                   | 0.35(0.2)                          | 5(0.05)                              | 8    | 3.59                |
| MAX804R/S/T     | 2.63/2.93/3.08                                                        | 140                            |                  | ✓                 | ✓                                   | 1.6                                                 |                          | ✓                     | 6                                                      | 400                                                 |                         | ✓/±2%                 |                    |                 |                   | 0.5(0.4)                           | 1(0.4)                               | 8    | 3.66                |
| MAX805L/M/R/S/T | 4.65/4.40/<br>2.63/2.93/3.08                                          | 140                            |                  | ✓                 | ✓                                   | 1.6                                                 |                          | ✓                     | 10                                                     | 400                                                 |                         | ✓                     |                    |                 |                   | 0.35(0.2)                          | 5(0.05)                              | 8    | 3.26                |
| MAX806R/S/T     | 2.63/2.93/3.08                                                        | 140                            | ✓                | ✓                 | ✓                                   |                                                     |                          | ✓                     | 6                                                      | 400                                                 |                         | ✓/±2%                 | ✓                  |                 |                   | 0.5(0.4)                           | 1(0.4)                               | 8    | 3.90                |
| MAX807L/N/M     | 4.68/4.58/4.43                                                        | 140                            | ✓/±1.5%          | ✓/±1.5%           | ✓                                   | 1.6                                                 | ✓                        | ✓                     | TBD                                                    | TBD                                                 | ✓                       | ✓                     | ✓                  | ✓               | ✓                 | TBD                                | TBD                                  | 8    | ††                  |
| MAX808L/N/M     | 4.68/4.58/4.43                                                        | 140                            | ✓/±1.5%          |                   | ✓                                   |                                                     |                          | ✓                     | TBD                                                    | TBD                                                 | ✓                       |                       |                    | ✓               |                   | TBD                                | TBD                                  | 16   | ††                  |
| MAX809L/M/R/S/T | 4.65/4.40/<br>2.63/2.93/3.08                                          | 140                            | ✓                |                   | ✓                                   |                                                     |                          |                       |                                                        |                                                     |                         |                       |                    |                 |                   | 0.06<br>(0.024)                    |                                      | 3    | ††                  |
| MAX810L/M/R/S/T | 4.65/4.40/<br>2.63/2.93/3.08                                          | 140                            |                  | ✓                 | ✓                                   |                                                     |                          |                       |                                                        |                                                     |                         |                       |                    |                 |                   | 0.06<br>(0.024)                    |                                      | 3    | ††                  |
| MAX813L         | 4.65                                                                  | 140                            |                  | ✓                 | ✓                                   | 1.6                                                 | ✓                        |                       |                                                        |                                                     |                         | ✓/±2%                 | ✓                  |                 |                   | 0.35(0.2)                          |                                      | 8    | 1.02*               |
| MAX814K/L/N/T   | 4.80/4.70/4.55/3.03                                                   | 140                            | ✓/±1%            | ✓/±1%             | ✓                                   |                                                     |                          |                       |                                                        |                                                     |                         | ✓/±2%                 | ✓                  | ✓               |                   | TBD                                | TBD                                  | 8    | ††                  |
| MAX815K/L/N/T   | 4.80/4.70/4.55/3.03                                                   | 140                            | ✓/±1%            | ✓/±1%             | ✓                                   | 1.6                                                 | ✓                        |                       |                                                        |                                                     |                         | ✓/±2%                 | ✓                  |                 |                   | TBD                                | TBD                                  | 8    | ††                  |
| MAX816          | Adj/±1%                                                               | 140                            | ✓                | ✓                 | ✓                                   |                                                     |                          |                       |                                                        |                                                     |                         | ✓/±2%                 | ✓                  |                 |                   | TBD                                | TBD                                  | 8    | ††                  |
| MAX820L/M/R/S/T | 4.65/4.40/<br>2.63/2.93/3.08                                          | 140                            | ✓                | ✓                 | ✓                                   | 1                                                   | ✓                        | ✓                     |                                                        |                                                     | ✓/10ns                  | ✓/±2%                 | ✓                  | ✓               |                   | 0.15<br>(0.07)                     |                                      | 16   | 3.82                |
| MAX1210         | 4.37/4.62                                                             |                                |                  |                   |                                     |                                                     |                          | ✓                     | 2.5                                                    | 667                                                 | ✓                       |                       |                    |                 |                   | 0.5 (0.23)                         | 0.1(0.002)                           | 8    | 2.44                |

## Package Information

For the latest package outline information and land patterns (footprints), go to [www.maximintegrated.com/packages](http://www.maximintegrated.com/packages). Note that a "+", "#", or "-" in the package code indicates RoHS status only. Package drawings may show a different suffix character, but the drawing pertains to the package regardless of RoHS status.

| PACKAGE TYPE  | PACKAGE CODE | OUTLINE NO.             |
|---------------|--------------|-------------------------|
| 8 $\mu$ MAX   | U8+1         | <a href="#">21-0036</a> |
| 8 Plastic DIP | P8+1         | <a href="#">21-0043</a> |
| 8 SO          | S8+2         | <a href="#">21-0041</a> |

## Chip Topography



## Revision History

| REVISION NUMBER | REVISION DATE | DESCRIPTION                                                                                                                                                             | PAGES CHANGED     |
|-----------------|---------------|-------------------------------------------------------------------------------------------------------------------------------------------------------------------------|-------------------|
| 0               | 2/92          | Initial release                                                                                                                                                         | —                 |
| 8               | 3/10          | Updated the <i>Features</i> , <i>Absolute Maximum Ratings</i> , <i>Typical Operating Characteristics</i> , Figures 3, 7, 8, and the <i>Package Information</i> sections | 1, 2, 4, 7, 8, 10 |
| 9               | 1/13          | Updated package code for 8 SO package                                                                                                                                   | 11                |
| 10              | 4/15          | Deleted “Automotive Systems” from <i>Applications</i> and updated <i>Benefits and Features</i> sections                                                                 | 1                 |
| 11              | 7/18          | Updated <i>Pin Description</i> table                                                                                                                                    | 5                 |

For pricing, delivery, and ordering information, please visit Maxim Integrated's online storefront at <https://www.maximintegrated.com/en/storefront/storefront.html>.

Maxim Integrated cannot assume responsibility for use of any circuitry other than circuitry entirely embodied in a Maxim Integrated product. No circuit patent licenses are implied. Maxim Integrated reserves the right to change the circuitry and specifications without notice at any time. The parametric values (min and max limits) shown in the *Electrical Characteristics* table are guaranteed. Other parametric values quoted in this data sheet are provided for guidance.

# Mouser Electronics

Authorized Distributor

Click to View Pricing, Inventory, Delivery & Lifecycle Information:

[Analog Devices Inc.:](#)

[MAX707CPA+](#) [MAX707CSA+](#) [MAX707ESA+](#) [MAX707MJA/883B](#) [MAX707CSA+T](#) [MAX707CUA+](#) [MAX707CUA+T](#)  
[MAX707EPA+](#) [MAX707ESA+T](#) [MAX707EUA+](#)