



Intel® Dual Band Wireless-AC 8265





Ultra Wi-Fi. Ultra Features. Ultra Connected Experience

The Intel® Dual Band Wireless-AC 8265 adapter supports Bluetooth® 4.2 and 2x2 11ac Wi-Fi delivering up to 867Mbps¹ including wave 2 features such as downlink MU-MIMO providing up to 3x increase in user speeds in dense deployments, supporting fast downloads and long battery life compared to legacy 11ac devices². Combined with Intel® Core™ processors and exceptional Intel wireless innovations, the Intel® Dual Band Wireless-AC 8265 dramatically reshapes your connected experience at home, work, or on the go.

| 4 th Generation Intel 802.11ac Wireless | | | | |
|--|------------------------|--|--|--|
| Faster Speed Better Coverage Larger Capacity 802.11ac, Dual Band, 80MHz, 2x2, MU-MIMO | | Delivers up to 3x faster Wi-Fi speeds (up to 867 Mbps) than 802.11n, with up to 3x more bandwidth per stream for more users and devices ³ . Downlink MU-MIMO allows an Access Point to simultaneously transmit data to multiple clients and can improve overall downlink network capacity by up to 3x ² . Intel® Wireless-AC enables smoother streaming of higher resolution videos, fewer dropped connections and less congestion, and faster speed further away from the router. | | |
| Bluetooth® 4.2 | | Dual mode Bluetooth® 4.2 enables BR/EDR-low energy devices to act as a hub and peripheral at the same time. Connects to the newest low energy Bluetooth® products as well as your familiar devices, such as headsets, keyboard, mice and more. | | |
| Microsoft* Windows* | | Full support for the latest Microsoft* Windows 10*, Windows 11* OS. | | |
| M.2 2230 or M.2 1216 Form Factors | | Multiple form-factors, including M.2 2230 and M.2 1216 modules enable system configuration and platform usages flexibility. The M.2 1216 form factor delivers 70% smaller footprint and lower profile optimized for thin-and-light designs ⁴ . | | |
| Experience the Intel Difference | | | | |
| Worldwide Regulatory Support Intel® Dynamic Regulatory Solution | | Enables worldwide regulatory compliance on a single Intel® Wireless-AC adapter SKU. The Intel® Dual Band Wireless-AC 8265 detects its location and automatically optimizes the Wi-Fi settings to local regulatory requirements, simplifying travel experience and global enterprise procurement. Future regulatory changes are easily managed during the product lifecycle. | | |
| Business-Class Wireless | | | | |
| Intel® vPro® Technolo | gy ⁵ | Supports Intel's hardware-based security and management features built into Intel® Core™ vPro® processors and chipsets that enables IT to manage PCs virtually anywhere, anytime while reducing deployment costs, improving security and ROI. | | |
| Intel® Active Managen Technology ⁶ | nent | Using integrated platform capabilities and popular third-party management and security applications, Intel® AMT allows IT or managed service providers to better discover, repair, and protect their networked computing assets. Intel® AMT is a feature of Intel® Core™ processors with Intel® vPro® technology. | | |
| Intel® PROSet/Wireless Software7 | | Includes advanced IT tools to improve security, reduce complexity and save IT time and money. Streamlines client deployments and allows remote management of wireless settings and profiles by IT managers. | | |

Intel® Dual Band Wireless-AC 8265 Technical Specifications

Weight

Dimensions (H x W x D) M.2 2230: 22 mm x 30 mm x 2.4 mm [1.5mm Max (Top Side)/ 0.1mm Max (Bottom Side)]

M.2 1216: 12 mm x 16 mm x 1.8 mm

M.2 1216: 0.6g Antenna Diversity Supported

Radio ON/OFF Control Supported

Connector interface M.2: PCIe, USB, or UART (M.2 1216 only)

Operating Temperature (Adapter Shield) 0°C to +80°C

Humidity Non-Operating 50% to 90% RH non-condensing (at temperatures of 25°C to 35°C)

M.2 2230: 2.6g

Microsoft Windows 11*, Microsoft Windows 10*, Linux* (limited feature support) Operating Systems

Wi-Fi CERTIFIED* a/b/g/n/ac, WMM*, WMM-PS*, WPA*, WPA2*, WPS2*, Protected Management Frames, Wi-Fi Alliance

Wi-Fi Direct* for peer to peer device connections, Wi-Fi Miracast* as Source. IEEE WLAN Standard

IEEE 802.11a/b/g/n/ac, 802.11d, 802.11e, 802.11h, 802.11i, 802.11w; 802.11r, 802.11k, 802.11v pending

OS support; Fine Timing Measurement based on 802.11REVmc

Supports seamless roaming between access points Dual Mode Bluetooth® 4.2, Bluetooth® Low Energy

Bluetooth[®] Security9

Roaming⁸

WPA and WPA2, 802.1X (EAP-TLS, TTLS, PEAP, LEAP, EAP-FAST), EAP-SIM, EAP-AKA, EAP-AKA' Authentication

Authentication Protocols PAP, CHAP, TLS, GTC, MS-CHAP*, MS-CHAPv2 64-bit and 128-bit WEP, 128-bit AES-CCMP Encryption

Wi-Fi Direct* Encryption and Authentication WPA2-PSK, AES-CCMP

Compliance

Regulatory For a list of country approvals, please contact your local Intel representatives.


FIPS¹⁰,FISMA **US Government**

UL, C-UL, CB (IEC 60950-1) **Product Safety**

| Product Name | Model Number | Version |
|---|--------------|---|
| Intel [®] Dual Band Wireless-AC 8265 | 8265NGW | 802.11ac, 2x2, Bluetooth® 4.2, PCIe, USB, M.2 2230 MS |
| Intel [®] Dual Band Wireless-AC 8265 | 8265D2W | 802.11ac. 2x2. Bluetooth® 4.2. PCIe. LTE Coexistence. M.2 1216 SD |



For more information on Intel® Wireless products, visit intel.com/wireless



² 802.11ac downlink MU-MIMO technology allows concurrently serving multiple devices simultaneously, in turn increasing network capacity by up to 3x while improving per-user throughput.

Software and workloads used in performance tests may have been optimized for performance only on Intel microprocessors. Performance tests, such as SYSmark and MobileMark, are measured using specific computer systems, components, software, operations and functions. Any change to any of those factors may cause the results to vary. You should consult other information and performance tests to assist you in fully evaluating your contemplated purchases, including the performance of that product when combined with other products.

No license, express or implied, by estoppel or otherwise, to any intellectual property rights is granted by this document. Except as provided in Intel's Terms and Conditions of Sale for such products, Intel assumes no liability whatsoever, and Intel disclaims any express or implied warranty, relating to sale and/or use of Intel products including without limitation, liability or warranties relating to fitness for a particular purpose, merchantability, or infringement of any patent, copyright or other intellectual property right. Intel products are not intended for use in medical, lifesaving, or life sustaining applications. Intel may make changes to specifications and product descriptions at any time, without notice. For the most current product information, please visit: http://www.intel.com/wireless Intel, the Intel logo, and Intel are trademarks or registered trademarks of Intel Corporation or its subsidiaries in the United States and other countries.

*Other names and brands may be claimed as the property of others. For more information visit: http://www.intel.com/content/www/us/en/legal/trademarks.html Copyright © Intel Corporation. All rights reserved.



³ Compared to 802.11n 40MHz channels, 802.11ac 80MHz provides 3x more bandwidth per stream (Max data rate for 2x2 802.11n 40MHz channel is 300Mbps, 150Mbps per stream; Max data rate for 2x2 802.11ac 80MHz channel is 867Mbps, 433Mbps per stream).

⁴ Compared to the footprint of an M.2 2230 module. An M.2 1216 module is 192mm² (12mmx16mm), approximately 70% smaller than the footprint of a M.2 2230 module (22mmx30mm = 660mm²). ⁵ Intel[®] vPro® Technology is sophisticated and requires setup and activation. Availability of features and results will depend upon the setup and configuration of your hardware, software and IT environment. To learn more visit: http://www.intel.com/technology/vpro.

⁶ Requires activation and a system with a corporate network connection, an Intel⁸ AMT-enabled chipset, network hardware and software. For notebooks, Intel⁸ AMT may be unavailable or limited over a host OS-based VPN, when connecting wirelessly, on battery power, sleeping, hibernating or powered off. Results dependent upon hardware, setup & configuration. For more information, visit: http://www.intel.com/technology/platform-technology/intel-amt.

⁷ Intel® PROSet/Wireless Software may not be supported by your device manufacturer. Check with your device manufacturer for details on availability.

⁸ Roaming is supported only within each respective band and mode of access points.

⁹ Some security solutions may not be supported by your device operating system and/or by your device manufacturer. Check with your device manufacturer for details on availability.

¹⁰ On Microsoft* Windows*