


AX92352

2-CH Encoder Card with Real-Time trigger I/O



▲ Side View

Features

- Synchronizes devices via real-time I/O
- Applied to area scan and line scan applications
- Integrates multiple I/O
 - 2-CH 32-bit incremental quadrature encoder input
 - 4-CH trigger input
 - 4-CH trigger output
 - 8-CH isolated DI, 8-CH isolated DO
- Programmable interrupt functions
- PCI Express x1 compliant

Introduction

The AX92352 integrates advanced vision I/O capabilities for machine vision applications, such as synchronizing multiple frame grabbers in line scan and multiple cameras in area scan. It provides 2-CH encoder input with the FIFO function to achieve the tasks of position comparison and linear trigger. Furthermore, it also has trigger I/O with a microsecond-scale real-time control camera to capture images, as well as isolated DIO that can be used with other devices for your vision cases. The AX92352 vision I/O card can fit in the PCI Express slot of any vision control system to simplify the deployment of your machine vision platform.

Specifications

Isolated Encoder Input

Channels	2-CH 32-bit incremental quadrature encoder input (A/B/Z)
Type	Differential or single-ended 5V, 12V open collector
Counter Mode	x1/4, x1/3, x1/2, x1, x2, x4
Input Filter	Programmable de-bounce filter
Frequency Input	Max. 1MHz
Operating Mode	Linear function, FIFO, Position latch

Isolated Trigger Input

Channels	4-CH
Type	Sink
Input range	On (Logic 1): 3.3 to 30 VDC Off (Logic 0): 0 to 2 VDC
Response Time	1 μ s (from trigger input to trigger output)
Input Filter	Programmable de-bounce filter

Isolated Trigger Output

Channels	4-CH
Output Voltage	0 to 30 VDC, sink, open collector
Output Current	Current: max. 100mA per channel
Response Time	1 μ s (from trigger input to trigger output)
Configuration	Derived from 4CH trigger input or encoder input. The user can set the pulse delay time and duration time
Trigger Sources	4CH trigger input/encoder: 4 x Linear function, 2 x FIFO (each channel supports two sources)

Isolated Digital Input

Channels	8-CH
Type	Sink/Source
Input Voltage	On (Logic 1): 10 to 30 VDC or dry contact Off (Logic 0): 0 to 3 VDC
Impedance	7.5KΩ

Isolated Digital Output

Channels	8-CH
Output type	Sink, open collector
Supply voltage	5 to 30 VDC
Sink current	Max. 200 mA per channel

Interrupt

Sources	Two interrupt sources from DI, Trigger/Latch input, Encoder Z phase, FIFO empty, encoder overflow and encoder linear function
---------	---

General Specifications

Bus Type	PCI Express x1
I/O Connector	D-sub 44-pin female connector
Isolation Voltage	2 kVDC
Power Requirements	180mA @ +3.3V (Max.) 120mA @ +12V (Max.)
Dimensions	168 x 100 mm
Board ID	Yes, 4-bit
Operating Temperature	0°C to +70°C (32°F to +158°F)
Storage Temperature	-20°C to +80°C (-4°F to +176°F)
Humidity	10 to 95% RH, non-condensing

Software Support

EOS Support	Windows® 7/Windows® 10 (32/64bit)
Software Compatibility	C#, C/C++

Ordering Information

AX92352 (P/N: E392352102)	AX92352 Vision I/O card with encoder
AX92353 (P/N: E392353100)	4-CH lighting control module (this optional module cannot be operating independently, please apply with AX92352)

Accessories

5A244AP1200E	44-pin DIN-rail terminal board DM44-AP12
594DM443500E	44-pin D-SUB cable, L=1m WHDM44/1.0-6954
594DM443510E	44-pin D-SUB cable, L=2m WHDM44/2.0-6954
594DM443520E	44-pin D-SUB cable, L=3m WHDM44/3.0-6954

*Specifications and certifications are based on options and may vary.

Mouser Electronics

Authorized Distributor

Click to View Pricing, Inventory, Delivery & Lifecycle Information:

[Axiomtek:](#)

[AX92352 Vision I/O card with encoder](#)