




# LMA-series



## ■ Feature

- For medical electric equipment
- Internal dual fuses
- Low leakage current
- High power & peak power (option)
- Small and compact PCB construction
- Built-in inrush current, overcurrent and overvoltage protection circuits
- Harmonic attenuator (Complies with IEC61000-3-2 class A)
- Universal input (AC85-264V)
- Power factor correction

## ■ Safety agency approvals

ANSI/AAMI ES60601, EN60601-1 3rd

## ■ EMI

Complies with FCC-B, CISPR22-B, EN55011-B, EN55022-B, VCCI-B

## ■ 5-year warranty

## ■ CE marking

Low Voltage Directive  
RoHS Directive

## ■ EMS Compliance

: EN61204-3, EN61000-6-2  
IEC60601-1-2 (2014), EN60601-1-2 (2015)


EN61000-4-2  
EN61000-4-3  
EN61000-4-4  
EN61000-4-5  
EN61000-4-6  
EN61000-4-8  
EN61000-4-11

## LMA100F

## Ordering information

LM A 100 F - □ - □① ② ③ ④ ⑤ ⑥

RoHS

Example recommended EMI/EMC filter  
NAM-04-101

High voltage pulse noise type : NAP series

Low leakage current type : NAM series

\* A higher current rating EMI/EMC filter may be recommended in view of the other devices that could be connected in parallel with the power supply.

- ① Series name
- ② Single output
- ③ Output wattage
- ④ Universal input
- ⑤ Output voltage
- ⑥ Optional \*1

- C: with Coating
- G: Low leakage current
- H: with the function to be acceptable to output peak current
- J1: VH(J.S.T.) connector type
- R: with Remote ON/OFF
- R2: with Remote ON/OFF
- S: with Chassis
- SN: with Chassis & cover
- P: Setting in the overcurrent protection rating

This power supply is manufactured by SMD technology. The stress to P.C.B like twisting or bending causes the defect of the unit, so handle the unit with care.  
\* Make sure necessary tests will be carried out on your end equipment with the power supply installed in accordance with any required EMC/EMI regulations.

MODEL	LMA100F-24-Y	LMA100F-24-HY
MAX OUTPUT WATTAGE[W]	103.2	103.2 (206.4) *2
DC OUTPUT	24V 4.3A	24V 4.3A (8.6A) *2

## SPECIFICATIONS

	LMA100F-24-Y	LMA100F-24-HY
INPUT	VOLTAGE[V]	AC85 - 264 1φ (Refer to "Derating", Instruction Manual 1 and 3)
	CURRENT[A]	ACIN 100V 1.4typ (Io=100%) ACIN 200V 0.7typ (Io=100%)
	FREQUENCY[Hz]	50 / 60 (47 - 63)
	EFFICIENCY[%]	ACIN 100V 84.0typ (Io=100%) ACIN 200V 86.0typ (Io=100%)
	POWER FACTOR	ACIN 100V 0.99typ (Io=100%) ACIN 200V 0.95typ (Io=100%)
	INRUSH CURRENT[A]	ACIN 100V 15typ (Io=100%) (At cold start) (Ta=25°C) ACIN 200V 30typ (Io=100%) (At cold start) (Ta=25°C)
	LEAKAGE CURRENT[mA]	0.10 / 0.25max (ACIN 100V / 240V 60Hz, Io=100%, According to IEC60601-1)
	VOLTAGE[V]	24
	CURRENT[A]	4.3
	LINE REGULATION[mV] *7	96max
OUTPUT	LOAD REGULATION[mV] *7	150max
	RISSLE[mVp-p] *3	0 to +50°C 120max -10 - 0°C 160max
	RISSLE NOISE[mVp-p] *3	0 to +50°C 150max -10 - 0°C 180max
	TEMPERATURE REGULATION[mV]	0 to +50°C 240max -10 to +50°C 290max
	DRIFT[mV] *4	96max
	START-UP TIME[ms]	350typ (ACIN 100V, Io=100%)
	HOLD-UP TIME[ms]	20typ (ACIN 100V, Io=100%)
	OUTPUT VOLTAGE ADJUSTMENT RANGE[V]	19.20 to 27.50
	OUTPUT VOLTAGE SETTING[V]	24.00 to 24.96
	OVERCURRENT PROTECTION	Works over 105% of rating (works over 101% of peak current at option -H) and recovers automatically
PROTECTION CIRCUIT AND OTHERS	OVERVOLTAGE PROTECTION[V]	27.60 to 33.60
	OPERATING INDICATION	Not provided
	REMOTE SENSING	Not provided
	REMOTE ON/OFF	Option (Required external power source.)
ISOLATION	INPUT-OUTPUT-RC	*6 AC4,000V 1minute, Cutoff current = 10mA, DC500V 50MΩ min (At Room Temperature) 2MOOP
	INPUT-FG	AC2,000V 1minute, Cutoff current = 10mA, DC500V 50MΩ min (At Room Temperature) 1MOOP
	OUTPUT-RC-FG	*6 AC500V 1minute, Cutoff current = 25mA, DC500V 50MΩ min (At Room Temperature)
	OUTPUT-RC	*6 AC100V 1minute, Cutoff current = 25mA, DC100V 10MΩ min (At Room Temperature)
ENVIRONMENT	OPERATING TEMP., HUMID. AND ALTITUDE *5	-10 to +70°C, 20 - 90%RH (Non condensing), (Refer to "Derating", Instruction Manual 3) 3,000m (10,000feet) max
	STORAGE TEMP., HUMID. AND ALTITUDE	-20 to +75°C, 20 - 90%RH (Non condensing), 9,000m (30,000feet) max
	VIBRATION	10 - 55Hz, 19.6m/s² (2G), 3minutes period, 60minutes each along X, Y and Z axis
	IMPACT	196.1m/s² (20G), 11ms, once each X, Y and Z axis
SAFETY AND NOISE REGULATIONS	AGENCY APPROVALS (AT ONLY AC input)	ANSI/AAMI ES60601-1, EN60601-1 3rd, Complies with IEC60601-1-2 4th Ed.
	CONDUCTED NOISE	Complies with FCC-B, VCCI-B, CISPR22-B, EN55011-B, EN55022-B
	HARMONIC ATTENUATOR	Complies with IEC61000-3-2 (Class A) *8
OTHERS	CASE SIZE/WEIGHT	62 X 33 X 155mm [2.44 X 1.30 X 6.10 inches] (W X H X D) / 290g max (with chassis & cover : 470g max)
	COOLING METHOD	Convection (Refer to "Derating", Instruction Manual 3) *5

\*1 Specification is changed at option, refer to Instruction Manual.

\*2 Peak loading for 10sec. And Duty 40% max.

() means peak current. There is a possibility that an internal device is damaged when the specification is exceeded.

\*3 This is the value that measured on measuring board with capacitor of 22 μF at 150mm from output terminal.

Measured by 20MHz oscilloscope or Ripple-Noise meter (Equivalent to KEISOKU-GIKEN: RM103).

\*4 Drift is the change in DC output for an eight hour period after a half-hour warm-up at 25°C, with the input voltage held constant at the rated input/output.

\*5 Derating is required.

\*6 Applicable when remote control (optional) is added.

\*7 Please contact us about dynamic load and input response.

\*8 Please contact us about another class.


\* To meet the specifications. Do not operate over-loaded condition.

\* Parallel operation is not possible.

\* Derating is required when operated with chassis and cover.

\* Sound noise may be generated by power supply in case of pulse load.


## Block diagram




## External view

※ External size of option is different from standard model.

Standard type



Chassis and cover type



※ 4 Mounting holes are existing.

※ The back side of P.C.B. of the power supply is assembled some SMDs.

Be attention not to bump against the attached area by vibration.

※ Use the spacer of 8mm length or more regarding insulation.

And do not use press-fitting bush.

※ Point A, Point B are thermometry points.

I/O Connector	Mating connector	Terminal
CN1 1-1123724-3	1-1123722-5	Chain 1123721-1
		Loose 1318912-1
CN2 1-1123723-8	1-1123722-8	Chain 1123721-1
		Loose 1318912-1

(Mfr: Tyco Electronics)

※ I/O Connector is Mfr. Tyco Electronics

※ Option:-J1:VH(J.S.T) connector type.

## &lt;PIN CONNECTION&gt;

CN1

Pin No.	Input
1	AC(L)
2	
3	AC(N)
4	
5	FG

CN2

Pin No.	Output
1 to 4	-V
5 to 8	+V

※ Keep drawing current per pin below 5A for CN2.

※ Tolerance : ±1 [±0.04]

※ Weight : 290g max (with chassis & cover : 470g max)

※ PCB material : CEM3

※ Optional chassis and cover material : Electric galvanizing steel board.

※ Dimensions in mm, [ ]inches

※ Mounting torque (Mounting hole of chassis) : 1.5N · m (16kgf · cm) max

Connector type

CN4 Option (Mfr:J.S.T)

PIN No.	Contents
1	RC(+)
2	RC(-)

Barrier strip type

Model B2B-XH-A  
Mating Connector (Terminal)  
XHP-2  
( BXH-001T-P0.6  
or SXH-001T-P0.6 )

## LMA150F


## Ordering information

LM A 150 F -□ -□

① ② ③ ④ ⑤ ⑥ ⑦ ⑧



RoHS



Example recommended EMI/EMC filter  
NAM-04-101



High voltage pulse noise type : NAP series

Low leakage current type : NAM series

\* A higher current rating EMI/EMC filter may be recommended in view of the other devices that could be connected in parallel with the power supply.

① Series name

② Single output

③ Output wattage

④ Universal input

⑤ Output voltage

⑥ Optional \*1

C: with Coating

G: Low leakage current

H: with the function to be acceptable to output peak current

J1: VH(J.S.T.) connector type

R: with Remote ON/OFF

R2: with Remote ON/OFF

S: with Chassis

SN: with Chassis &amp; cover

P: Setting in the overcurrent protection rating

This power supply is manufactured by SMD technology. The stress to P.C.B like twisting or bending causes the defect of the unit, so handle the unit with care.  
\* Make sure necessary tests will be carried out on your end equipment with the power supply installed in accordance with any required EMC/EMI regulations.

MODEL	LMA150F-24-Y	LMA150F-24-HY
MAX OUTPUT WATTAGE[W]	151.2	151.2 (302.4) *2
DC OUTPUT	24V 6.3A	24V 6.3A (12.6A) *2

## SPECIFICATIONS

	LMA150F-24-Y	LMA150F-24-HY
INPUT	VOLTAGE[V]	AC85 - 264 1φ (Refer to "Derating", Instruction Manual 1 and 3)
	CURRENT[A]	ACIN 100V 2.0typ (Io=100%) ACIN 200V 1.0typ (Io=100%)
	FREQUENCY[Hz]	50 / 60 (47 - 63)
	EFFICIENCY[%]	ACIN 100V 85.0typ (Io=100%) ACIN 200V 87.0typ (Io=100%)
	POWER FACTOR	ACIN 100V 0.99typ (Io=100%) ACIN 200V 0.95typ (Io=100%)
	INRUSH CURRENT[A]	ACIN 100V 15typ (Io=100%) (At cold start) (Ta=25°C) ACIN 200V 30typ (Io=100%) (At cold start) (Ta=25°C)
	LEAKAGE CURRENT[mA]	0.10 / 0.25max (ACIN 100V / 240V 60Hz, Io=100%, According to IEC60601-1)
	VOLTAGE[V]	24
	CURRENT[A]	6.3
	LINE REGULATION[mV] *7	96max
OUTPUT	LOAD REGULATION[mV] *7	150max
	RISSLE[mVp-p] *3	0 to +50°C 120max -10 - 0°C 160max
	RISSLE NOISE[mVp-p] *3	0 to +50°C 150max -10 - 0°C 180max
	TEMPERATURE REGULATION[mV]	0 to +50°C 240max -10 to +50°C 290max
	DRIFT[mV] *4	96max
	START-UP TIME[ms]	350typ (ACIN 100V, Io=100%)
	HOLD-UP TIME[ms]	20typ (ACIN 100V, Io=100%)
	OUTPUT VOLTAGE ADJUSTMENT RANGE[V]	19.20 to 27.50
	OUTPUT VOLTAGE SETTING[V]	24.00 to 24.96
	OVERCURRENT PROTECTION	Works over 105% of rating (works over 101% of peak current at option -H) and recovers automatically
PROTECTION CIRCUIT AND OTHERS	OVERVOLTAGE PROTECTION[V]	27.60 to 33.60
	OPERATING INDICATION	Not provided
	REMOTE SENSING	Not provided
ISOLATION	REMOTE ON/OFF	Option (Required external power source.)
	INPUT-OUTPUT-RC	*6 AC4,000V 1minute, Cutoff current = 10mA, DC500V 50MΩ min (At Room Temperature) 2MOOP
	INPUT-FG	AC2,000V 1minute, Cutoff current = 10mA, DC500V 50MΩ min (At Room Temperature) 1MOOP
	OUTPUT-RC-FG	*6 AC500V 1minute, Cutoff current = 25mA, DC500V 50MΩ min (At Room Temperature)
	OUTPUT-RC	*6 AC100V 1minute, Cutoff current = 25mA, DC100V 10MΩ min (At Room Temperature)
ENVIRONMENT	OPERATING TEMP., HUMID. AND ALTITUDE *5	-10 to +70°C, 20 - 90%RH (Non condensing), (Refer to "Derating", Instruction Manual 3) 3,000m (10,000feet) max
	STORAGE TEMP., HUMID. AND ALTITUDE	-20 to +75°C, 20 - 90%RH (Non condensing), 9,000m (30,000feet) max
	VIBRATION	10 - 55Hz, 19.6m/s² (2G), 3minutes period, 60minutes each along X, Y and Z axis
	IMPACT	196.1m/s² (20G), 11ms, once each X, Y and Z axis
SAFETY AND NOISE REGULATIONS	AGENCY APPROVALS (AT ONLY AC input)	ANSI/AAMI ES60601-1, EN60601-1 3rd, Complies with IEC60601-1-2 4th Ed.
	CONDUCTED NOISE	Complies with FCC-B, VCCI-B, CISPR22-B, EN55011-B, EN55022-B
	HARMONIC ATTENUATOR	Complies with IEC61000-3-2 (Class A) *8
OTHERS	CASE SIZE/WEIGHT	75 X 36.5 X 160mm [2.95 X 1.44 X 6.30 inches] (W X H X D) / 370g max (with chassis & cover : 600g max)
	COOLING METHOD	Convection (Refer to "Derating", Instruction Manual 3) *5

\*1 Specification is changed at option, refer to Instruction Manual.

\*2 Peak loading for 10sec. And Duty 40% max.

() means peak current. There is a possibility that an internal device is damaged when the specification is exceeded.

\*3 This is the value that measured on measuring board with capacitor of 22 μF at 150mm from output terminal.

Measured by 20MHz oscilloscope or Ripple-Noise meter (Equivalent to KEISOKU-GIKEN: RM103).

\*4 Drift is the change in DC output for an eight hour period after a half-hour warm-up at 25°C, with the input voltage held constant at the rated input/output.

\*5 Derating is required.

\*6 Applicable when remote control (optional) is added.

\*7 Please contact us about dynamic load and input response.

\*8 Please contact us about another class.


\* To meet the specifications. Do not operate over-loaded condition.

\* Parallel operation is not possible.

\* Derating is required when operated with chassis and cover.

\* Sound noise may be generated by power supply in case of pulse load.


## Block diagram




## External view

※ External size of option is different from standard model.

Standard type



Chassis and cover type



※ 4 Mounting holes are existing.

※ The back side of P.C.B. of the power supply is assembled some SMDs.

Be attention not to bump against the attached area by vibration.  
Use the spacer of 8mm length or more regarding insulation.

And do not use press-fitting bush.

※ Point A, Point B are thermometry points.

## &lt;PIN CONNECTION&gt;

CN1

Pin No.	Input
1	AC(L)
2	
3	AC(N)
4	
5	FG

CN2

Pin No.	Output
1 to 6	+V

CN3

Pin No.	Output
1 to 7	-V

Connector type

CN4 Option (Mfr.J.S.T)

PIN No.	Contents
1	RC(+)
2	RC(-)

Barrier strip type

Model B2B-XH-A  
Mating Connector (Terminal)  
XHP-2

(BXH-001T-P0.6  
or SXH-001T-P0.6)

(Mfr:Tyco Electronics)

※ Keep drawing current per pin below 5A for CN2,CN3.

※ Tolerance : ±1 [±0.04]

※ Weight : 370g max (with chassis & cover : 600g max)

※ PCB material : CEM3

※ Optional chassis and cover material : Electric galvanizing steel board.

※ Dimensions in mm, [ ]=inches

※ Mounting torque (Mounting hole of chassis): 1.5N · m (16kgf · cm) max

## LMA240F


## Ordering information

LM A 240 F -□ -□

① ② ③ ④ ⑤ ⑥



RoHS



Example recommended EMI/EMC filter  
NAM-06-101



High voltage pulse noise type : NAP series

Low leakage current type : NAM series

\* A higher current rating EMI/EMC filter may be recommended in view of the other devices that could be connected in parallel with the power supply.

- ① Series name
- ② Single output
- ③ Output wattage
- ④ Universal input
- ⑤ Output voltage
- ⑥ Optional \*1

- C: with Coating
- G: Low leakage current
- H: with the function to be acceptable to output peak current
- J1: VH(J.S.T.) connector type
- R: with Remote ON/OFF
- R2: with Remote ON/OFF
- S: with Chassis
- SN: with Chassis & cover
- P: Setting in the overcurrent protection rating

This power supply is manufactured by SMD technology. The stress to P.C.B like twisting or bending causes the defect of the unit, so handle the unit with care.

\* Make sure necessary tests will be carried out on your end equipment with the power supply installed in accordance with any required EMC/EMI regulations.

MODEL	LMA240F-24-Y	LMA240F-24-HY
MAX OUTPUT WATTAGE[W]	300	300 (480) *2
DC OUTPUT	Convection 24V 10A Forced air 24V 12.5A	24V 10A (20A) *2 24V 12.5A (20A) *2

## SPECIFICATIONS

	LMA240F-24-Y		LMA240F-24-HY	
<b>INPUT</b>	<b>VOLTAGE[V]</b>		AC85 - 264 1φ (Refer to "Derating", Instruction Manual 1 and 3)	
	ACIN 100V	3.9typ (Io=100%)		
	ACIN 200V	1.8typ (Io=100%)		
<b>FREQUENCY[Hz]</b>		50 / 60 (47 - 63)		
	ACIN 100V	86.0typ (Io=100%)	86.0typ (Io=100%)	
	ACIN 200V	88.0typ (Io=100%)	88.0typ (Io=100%)	
<b>POWER FACTOR</b>		ACIN 100V 0.99typ (Io=100%) ACIN 200V 0.95typ (Io=100%)		
<b>INRUSH CURRENT[A]</b>		ACIN 100V 15 / 30typ (Io=100%) (Primary inrush current /Secondary inrush current) (More than 3 sec. to re-start) ACIN 200V 30 / 30typ (Io=100%) (Primary inrush current /Secondary inrush current) (More than 3 sec. to re-start)		
<b>LEAKAGE CURRENT[mA]</b>		0.15 / 0.40max (ACIN 100V / 240V 60Hz, Io=100%, According to IEC60601-1)		
<b>OUTPUT</b>		<b>VOLTAGE[V]</b>	24	
	Convection	10	10 (Peak 20) *2	
	Forced air	12.5	12.5 (Peak 20) *2	
	<b>LINE REGULATION[mV]</b>		96max	
	<b>LOAD REGULATION[mV]</b>		150max	
	0 to +50°C	120max	120max	
	-10 - 0°C	160max	160max	
	0 to +50°C	150max	150max	
	-10 - 0°C	180max	180max	
	0 to +50°C	240max	240max	
	-10 to +50°C	290max	290max	
	<b>DRIFT[mV]</b>		96max	
	<b>START-UP TIME[ms]</b>		350typ (ACIN 100V, Io=100%)	
	<b>HOLD-UP TIME[ms]</b>		20typ (ACIN 100V, Io=100%)	
	<b>OUTPUT VOLTAGE ADJUSTMENT RANGE[V]</b>		19.20 to 27.50	
	<b>OUTPUT VOLTAGE SETTING[V]</b>		24.00 to 24.96	
<b>PROTECTION</b>		<b>OVERCURRENT PROTECTION</b>	Works over 105% of rating (works over 101% of peak current at option -H) and recovers automatically	
<b>CIRCUIT AND OTHERS</b>		<b>OVERVOLTAGE PROTECTION[V]</b>	27.60 to 33.60	
<b>OPERATING INDICATION</b>		Not provided		
<b>REMOTE SENSING</b>		Not provided		
<b>REMOTE ON/OFF</b>		Option (Required external power source.)		
<b>ISOLATION</b>		<b>INPUT-OUTPUT-RC</b>	*6 AC4,000V 1minute, Cutoff current = 10mA, DC500V 50MΩ min (At Room Temperature) 2MOOP	
	<b>INPUT-FG</b>		AC2,000V 1minute, Cutoff current = 10mA, DC500V 50MΩ min (At Room Temperature) 1MOOP	
	<b>OUTPUT-RC-FG</b>		*6 AC500V 1minute, Cutoff current = 25mA, DC500V 50MΩ min (At Room Temperature)	
	<b>OUTPUT-RC</b>		*6 AC100V 1minute, Cutoff current = 25mA, DC100V 10MΩ min (At Room Temperature)	
<b>ENVIRONMENT</b>		<b>OPERATING TEMP., HUMID. AND ALTITUDE</b>	*5 -10 to +70°C, 20 - 90%RH (Non condensing), (Refer to "Derating", Instruction Manual 3) 3,000m (10,000feet) max	
	<b>STORAGE TEMP., HUMID. AND ALTITUDE</b>		-20 to +75°C, 20 - 90%RH (Non condensing), 9,000m (30,000feet) max	
<b>VIBRATION</b>		10 - 55Hz, 19.6m/s <sup>2</sup> (2G), 3minutes period, 60minutes each along X, Y and Z axis		
<b>IMPACT</b>		196.1m/s <sup>2</sup> (20G), 11ms, once each X, Y and Z axis		
<b>SAFETY AND NOISE REGULATIONS</b>		<b>AGENCY APPROVALS (AT ONLY AC input)</b>	ANSI/AAMI ES60601-1, EN60601-1 3rd, Complies with IEC60601-1-2 4th Ed.	
	<b>CONDUCTED NOISE</b>		Complies with FCC-B, VCCI-B, CISPR22-B, EN55011-B, EN55022-B	
	<b>HARMONIC ATTENUATOR</b>		Complies with IEC61000-3-2 (Class A) *8	
<b>OTHERS</b>		<b>CASE SIZE/WEIGHT</b>	84 X 46 X 180mm [3.31 X 1.81 X 7.09 inches] (W X H X D) / 540g max (with chassis & cover : 860g max)	
	<b>COOLING METHOD</b>		Convection / Forced air (Refer to "Derating", Instruction Manual 3) *5	

\*1 Specification is changed at option, refer to Instruction Manual.

\*2 Peak loading for 10sec. And Duty 40% max.

() means peak current. There is a possibility that an internal device is damaged when the specification is exceeded.

\*3 This is the value that measured on measuring board with capacitor of 22 μF at 150mm from output terminal.

Measured by 20MHz oscilloscope or Ripple-Noise meter (Equivalent

to KEISOKU-GIKEN: RM103).

\*4 Drift is the change in DC output for an eight hour period after a half-hour warm-up at 25°C, with the input voltage held constant at the rated input/output.

\*5 Derating is required.

\*6 Applicable when remote control (optional) is added.

\*7 Please contact us about dynamic load and input response.

\*8 Please contact us about another class.


\*9 To meet the specifications. Do not operate over-loaded condition.

\* Parallel operation is not possible.

\* Derating is required when operated with chassis and cover.


\* Sound noise may be generated by power supply in case of pulse load.

## Block diagram



## External view

※ External size of option is different from standard model.



※ 5 Mounting holes are existing.

※ The back side of P.C.B. of the power supply is assembled some SMDs.

Be attention not to bump against the attached area by vibration.

※ Use the spacer of 8mm length or more regarding insulation.

And do not use press-fitting bush.

※ Point A, Point B, Point C are thermometry points.

## &lt;PIN CONNECTION&gt;

## CN1

## CN2

## CN3

## Connector type

## CN4 Option (Mfr.J.S.T)

PIN No.	Contents
1	RC(+)
2	RC(-)

## Barrier strip type

Model B2B-XH-A  
Mating Connector (Terminal)  
XHP-2  
( BXH-001T-P0.6  
or SXH-001T-P0.6 )

I/O Connector	Mating connector	Terminal
CN1 1-1123724-3	1-1123722-5	Chain 1123721-1
		Loose 1318912-1
CN2 1-1123723-6	1-1123722-6	Chain 1123721-1
		Loose 1318912-1
CN3 1-1123723-7	1-1123722-7	Chain 1123721-1
		Loose 1318912-1

(Mfr:Tyco Electronics)

※ I/O Connector is Mfr. Tyco Electronics

※ Option:-J1:VH(J.S.T) connector type.

※ Keep drawing current per pin below 5A for CN2,CN3.

※ Tolerance :  $\pm 1$  [ $\pm 0.04$ ]

※ Weight : 540g max (with chassis & cover : 860g max)

※ PCB material : CEM3

※ Optional chassis and cover material : Electric galvanizing steel board.

※ Dimensions in mm, [ ]=inches


※ Mounting torque (Mounting hole of chassis) :  $1.5N \cdot m$  (16kgf  $\cdot$  cm) max

### Assembling and Installation Method


#### Installation method

■ This power supply is manufactured by SMD technology. The stress to P.C.B like twisting or bending causes the defect of the unit, so handle the unit with care.


■ In case of metal chassis, keep the distance between d1 & d2 for to insulate between lead of component and metal chassis, use the spacer of 8mm or more between d1. If it is less than d1 & d2, insert the insulation sheet between power supply and metal chassis.



■ There is a possibility that it is not possible to cool enough when the power supply is used by the sealing up space as showing in right figure. Please use it after confirming the temperature of point A and point B of Instruction Manual 3.




■ (F) mounting is not possible when unit is with case cover, but if need to operate unit by (F) positioning with case cover, temperature / load derating is necessary. For more details, please contact our sales or engineering departments.




#### Mounting screw

■ The mounting screw should be M3. The hatched area shows the allowance of metal parts for mounting.

#### ● LMA100F, LMA150F



#### ● LMA240F




■ If metallic fittings are used on the component side of the board, ensure there is no contact with surface mounted components.

■ This product uses SMD technology. Please avoid the PCB installation method which includes the twisting stress or the bending stress.


\* Recommendation to electrically connect FG to metal chassis for reducing noise.

## Derating


### ● Derating curve for input voltage




### ● LMA100F Ambient temperature derating curve (Reference value)



### ● LMA150F Ambient temperature derating curve (Reference value)



### ● LMA240F Ambient temperature derating curve (Reference value)



Output voltage	Output power[W]	
	①Convection	②Forced air
24V	240.0	300.0

■ The operative ambient temperature is different by with / without chassis cover or mounting position.

Note: In the hatched area, the specification of Ripple, Ripple Noise is different from other area.

■ Make sure the temperature at point A and point B is less than the temperatures shown in Instruction Manual 3.

■ The ambient temperature should be measured 5 to 10 cm away from the power supply so that it won't be influenced by the heat from the power supply. Please consult us for more details.

**Instruction Manual**

◆ It is necessary to read the "Instruction Manual" and "Before using our product" before you use our product.

Instruction Manual <https://en.cosel.co.jp/product/powersupply/LMA/>  
 Before using our product <https://en.cosel.co.jp/technical/caution/index.html>

**LMA**



**NOTICE**



**Basic Characteristics Data**

Model	Circuit method	Switching frequency [kHz]	Input current *1 [A]	Inrush current protection	PCB/Pattern			Series/Parallel operation availability	
					Material	Single sided	Double sided	Series operation	Parallel operation
LMA100F	Active filter	60	1.4	Thermistor	CEM-3		Yes	Yes	No
	Forward converter	130							
LMA150F	Active filter	60	2.0	Thermistor	CEM-3		Yes	Yes	No
	Forward converter	130							
LMA240F	Active filter	60	3.9	SCR	CEM-3		Yes	Yes	No
	Forward converter	130							

\*1 The value of input current is at ACIN 100V and rated load.

# Mouser Electronics

Authorized Distributor

Click to View Pricing, Inventory, Delivery & Lifecycle Information:

Cosel:

[LMA100F-24-HY](#) [LMA240F-24-HY](#) [LMA240F-24-Y](#) [LMA150F-24-HY](#) [LMA100F-24-Y](#) [LMA150F-24-Y](#)