


PDA-series



Feature

High efficiency
 Low noise
 Complies with SEMI F47
 Harmonic attenuator (Complies with IEC61000-3-2)
 Universal input (85-264VAC)
 Built-in inrush current, overcurrent and overvoltage protection circuits

Safety agency approvals

UL62368-1, c-UL (equivalent to CAN/CSA-C22.2 No.62368-1),
 EN62368-1
 Complies with DEN-AN

5-year warranty (refer to Instruction Manual)

CE marking

Low Voltage Directive
 RoHS Directive

UKCA marking

Electrical Equipment Safety Regulations
 RoHS Regulations

EMI

Complies with CISPR11-B, CISPR32-B, EN55011-B,
 EN55032-B, FCC Part 15-B, FCC Part 18-B, VCCI-B

EMS Compliance : EN61204-3, EN61000-6-2

EN61000-4-2
 EN61000-4-3
 EN61000-4-4
 EN61000-4-5
 EN61000-4-6
 EN61000-4-8
 EN61000-4-11

PDA15F

PD

A

15

F

-□

-□

①


②

③

④

⑤

⑥



Example recommended EMI/EMC filter
NAC-06-472



High voltage pulse noise type : NAP series
Low leakage current type : NAM series
* A higher current rating EMI/EMC filter
may be recommended in view of the
other devices that could be connected
in parallel with the power supply.

- ① Series name
- ② Single output
- ③ Output wattage
- ④ Universal input
- ⑤ Output voltage
- ⑥ Optional *1
N : with cover

For option details, refer to
Instruction Manual 6.

* Make sure necessary tests will be carried out on your end equipment with the power supply installed in accordance with any required EMC/EMI regulations.

MODEL	PDA15F-5	PDA15F-12	PDA15F-24
MAX OUTPUT WATTAGE[W]	15	15.6	16.8
DC OUTPUT	5V 3A	12V 1.3A	24V 0.7A


SPECIFICATIONS

MODEL	PDA15F-5	PDA15F-12	PDA15F-24
VOLTAGE[VAC]	85 - 264 1 φ (Refer to "Derating" and Instruction Manual 1.1)		
INPUT	CURRENT[A]	0.35typ	0.19typ
	FREQUENCY[Hz]	50 / 60 (45 - 440)	
	EFFICIENCY[%]	75.0typ	81.0typ
	INRUSH CURRENT[A]	15typ (Io=100%) at cold start	83.5typ
OUTPUT	LEAKAGE CURRENT[ma]	0.15 / 0.30max (ACIN 100V / 240V, 60Hz, Io=100%, According to IEC62368-1, and DEN-AN)	
	VOLTAGE[V]	5	12
	CURRENT[A]	3.0	1.3
	LINE REGULATION[mV]	20max	48max
	LOAD REGULATION[mV]	40max	100max
	RIPPLE[mVp-p]	80max	120max
	RIPPLE NOISE[mVp-p]	120max	150max
	TEMPERATURE REGULATION[mV]	50max	120max
	DRIFT[mV]	20max	48max
	START-UP TIME[ms]	80typ (ACIN 100V, Io=100%)	
	HOLD-UP TIME[ms]	20typ (ACIN 100V, Io=100%) / 150typ (ACIN 230V, Io=100%)	
	OUTPUT VOLTAGE ADJUSTMENT RANGE[V]	4.50 to 5.50	10.0 to 13.2
	OUTPUT VOLTAGE SETTING[V]	5.00 to 5.15	12.00 to 12.48
	OVERCURRENT PROTECTION	Works over 105% of rating and recovers automatically	
	OVERVOLTAGE PROTECTION	5.75 to 7.00	15.0 to 18.0
	REMOTE SENSING	Not provided	
ISOLATION	INPUT-OUTPUT	AC3,000V 1minute, Cutoff current = 10mA, DC500V 100MΩ min (At Room Temperature)	
	INPUT-FG	AC2,000V 1minute, Cutoff current = 10mA, DC500V 100MΩ min (At Room Temperature)	
	OUTPUT-FG	AC500V 1minute, Cutoff current = 25mA, DC500V 100MΩ min (At Room Temperature)	
ENVIRONMENT	OPERATING TEMP., HUMID. AND ALTITUDE	-20 to +70°C, 20 - 90%RH (Non condensing), 5,000m (16,500feet) max	
	STORAGE TEMP., HUMID. AND ALTITUDE	-20 to +75°C, 20 - 90%RH (Non condensing), 9,000m (30,000feet) max	
	VIBRATION	10 - 55Hz, 19.6m/s ² (2G), 3minutes period, 60minutes each along X, Y and Z axis	
	IMPACT	196.1m/s ² (20G), 11ms, once each X, Y and Z axis	
SAFETY AND NOISE REGULATIONS	AGENCY APPROVALS	UL62368-1, c-UL (equivalent to CAN/CSA-C22.2No.62368-1), EN62368-1, Complies with DEN-AN	
	CONDUCTED NOISE	Complies with CISPR11-B, CISPR32-B, EN55011-B, EN55032-B, FCC Part15-B, FCC Part18-B, VCCI-B	
	HARMONIC ATTENUATOR	Complies with IEC61000-3-2 (Class A) (No built-in power factor correction)	
OTHERS	CASE SIZE/WEIGHT	31 X 78 X 85mm [1.22 X 3.07 X 3.35 inches] (without terminal block) (W X H X D) / 180g max (with cover : 210g max)	
	COOLING METHOD	Convection/Forced air (Requires external fan) (Refer to "Derating")	


- *1 The listed options may affect the published standard specifications. Please contact us for detailed product specifications.
- *2 Derating is required. Please contact us for DC input.
- *3 At low load conditions, the burst mode operation will start. To check load regulation, you will need to measure the characteristics at average mode with instruments.
- *4 This is the value that measured on measuring board with capacitor of 22 μF at 150mm from output terminal.
Measured by 20MHz oscilloscope or Ripple-Noise meter
(Equivalent to KEISOKU-GIKEN:RM104).
Ripple and ripple noise spec is change at Io=0 to 15% by burst operation.

- *5 Drift is the change in DC output for an eight hour period after a half-hour warm-up at 25°C, with the input voltage held constant at the rated input/output.
- *6 Please contact us about another class. When two or more units are operating it may not comply with the IEC61000-3-2. Please contact us for details.
- * To meet the specification, do not operate overload condition.
- * Parallel operation is not possible.
- * Sound noise may be generated by power supply in case of pulse load.

Block diagram



External view



PDA30F

PD

A

30

F

-□

-□

①


②

③

④

⑤

⑥



Example recommended EMI/EMC filter
NAC-06-472



High voltage pulse noise type : NAP series
Low leakage current type : NAM series
* A higher current rating EMI/EMC filter may be recommended in view of the other devices that could be connected in parallel with the power supply.

- ① Series name
- ② Single output
- ③ Output wattage
- ④ Universal input
- ⑤ Output voltage
- ⑥ Optional *1
N : with cover

For option details, refer to Instruction Manual 6.

*Make sure necessary tests will be carried out on your end equipment with the power supply installed in accordance with any required EMC/EMI regulations.

MODEL	PDA30F-5	PDA30F-12	PDA30F-24
MAX OUTPUT WATTAGE[W]	30	30	31.2
DC OUTPUT	5V 6A	12V 2.5A	24V 1.3A

SPECIFICATIONS

MODEL	PDA30F-5	PDA30F-12	PDA30F-24
VOLTAGE[VAC]	85 - 264 1 φ (Refer to "Derating" and Instruction Manual 1.1)		
INPUT	CURRENT[A]	0.62typ	
	ACIN 100V	0.32typ	
	ACIN 230V		
	FREQUENCY[Hz]	50 / 60 (45 - 440)	
INPUT	EFFICIENCY[%]	83.0typ	82.0typ
	ACIN 100V	87.0typ	85.5typ
	ACIN 230V		
	INRUSH CURRENT[A]	15typ (Io=100%) at cold start	83.5typ
INPUT	ACIN 230V	35typ (Io=100%) at cold start	86.5typ
	LEAKAGE CURRENT[ma]	0.25 / 0.55 max (ACIN 100V / 240V, 60Hz, Io=100%, According to IEC62368-1, and DEN-AN)	
	VOLTAGE[V]	5	12
	CURRENT[A]	6.0	2.5
OUTPUT	LINE REGULATION[mV]	20max	48max
	LOAD REGULATION[mV]	40max	100max
	TEMPERATURE REGULATION[mV]	50max	120max
	DRIFT[mV]	20max	48max
OUTPUT	START-UP TIME[ms]	80typ (ACIN 100V, Io=100%)	
	HOLD-UP TIME[ms]	20typ (ACIN 100V, Io=100%) / 150typ (ACIN 230V, Io=100%)	
	OUTPUT VOLTAGE ADJUSTMENT RANGE[V]	4.50 to 5.50	10.0 to 13.2
	OUTPUT VOLTAGE SETTING[V]	5.00 to 5.15	12.00 to 12.48
PROTECTION	OVERCURRENT PROTECTION	Works over 105% of rating and recovers automatically	
	OVERVOLTAGE PROTECTION	5.75 to 7.00	15.0 to 18.0
	REMOTE SENSING	Not provided	
	ISOLATION		
ISOLATION	INPUT-OUTPUT	AC3,000V 1minute, Cutoff current = 10mA, DC500V 100MΩ min (At Room Temperature)	
	INPUT-FG	AC2,000V 1minute, Cutoff current = 10mA, DC500V 100MΩ min (At Room Temperature)	
	OUTPUT-FG	AC500V 1minute, Cutoff current = 25mA, DC500V 100MΩ min (At Room Temperature)	
	ENVIRONMENT		
ENVIRONMENT	OPERATING TEMP., HUMID. AND ALTITUDE	-20 to +70°C, 20 - 90%RH (Non condensing), 5,000m (16,500feet) max	
	STORAGE TEMP., HUMID. AND ALTITUDE	-20 to +75°C, 20 - 90%RH (Non condensing), 9,000m (30,000feet) max	
	VIBRATION	10 - 55Hz, 19.6m/s ² (2G), 3minutes period, 60minutes each along X, Y and Z axis	
	IMPACT	196.1m/s ² (20G), 11ms, once each X, Y and Z axis	
SAFETY AND NOISE REGULATIONS	AGENCY APPROVALS	UL62368-1, c-UL (equivalent to CAN/CSA-C22.2No.62368-1), EN62368-1, Complies with DEN-AN	
	CONDUCTED NOISE	Complies with CISPR11-B, CISPR32-B, EN55011-B, EN55032-B, FCC Part15-B, FCC Part18-B, VCCI-B	
	HARMONIC ATTENUATOR	Complies with IEC61000-3-2 (Class A) (No built-in power factor correction)	
	CASE SIZE/WEIGHT	31 X 78 X 103mm [1.22 X 3.07 X 4.06 inches] (without terminal block) (W X H X D) / 250g max (with cover : 280g max)	
OTHERS	COOLING METHOD	Convection/Forced air (Requires external fan) (Refer to "Derating")	

*1 The listed options may affect the published standard specifications. Please contact us for detailed product specifications.

*2 Derating is required. Please contact us for DC input.

*3 At low load conditions, the burst mode operation will start. To check load regulation, you will need to measure the characteristics at average mode with instruments.

*4 This is the value that measured on measuring board with capacitor of 22 μF at 150mm from output terminal.
Measured by 20MHz oscilloscope or Ripple-Noise meter
(Equivalent to KEISOKU-GIKEN:RM104).
Ripple and ripple noise spec is change at Io=0 to 15% by burst operation.

*5 Drift is the change in DC output for an eight hour period after a half-hour warm-up at 25°C, with the input voltage held constant at the rated input/output.


*6 Please contact us about another class. When two or more units are operating it may not comply with the IEC61000-3-2. Please contact us for details.

* To meet the specification, do not operate overload condition.


* Parallel operation is not possible.

* Sound noise may be generated by power supply in case of pulse load.

Block diagram



External view



- * Tolerance : ± 1 [± 0.04]
- * Weight : 250g max (with cover : 280g max)
- * PCB Material / thickness : CEM3 / 1.6mm [0.06]
- * Chassis material : Galvanized steel plate
- * Dimensions in mm, []= inches
- * Mounting torque : 0.6N · m max
- * Screw tightening torque : M3 0.8N · m max
- * Please connect safety ground to the unit in 2-M3 holes
- * Point ①, Point ② are thermometry points. Please refer to Instruction Manual 3.

PDA50F

PD

A

50

F

-□

-□

①


②

③

④

⑤

⑥



Example recommended EMI/EMC filter
NAC-06-472



High voltage pulse noise type : NAP series
Low leakage current type : NAM series
* A higher current rating EMI/EMC filter may be recommended in view of the other devices that could be connected in parallel with the power supply.

- ① Series name
- ② Single output
- ③ Output wattage
- ④ Universal input
- ⑤ Output voltage
- ⑥ Optional *1
N : with cover

For option details, refer to Instruction Manual 6.

* Make sure necessary tests will be carried out on your end equipment with the power supply installed in accordance with any required EMC/EMI regulations.

MODEL	PDA50F-5	PDA50F-12	PDA50F-24
MAX OUTPUT WATTAGE[W]	50	51.6	52.8
DC OUTPUT	5V 10A	12V 4.3A	24V 2.2A

SPECIFICATIONS

	MODEL	PDA50F-5	PDA50F-12	PDA50F-24	
INPUT	VOLTAGE[VAC] *2		85 - 264 1 φ (Refer to Instruction Manual 1.1)		
	CURRENT[A]	ACIN 100V	1.05typ		
		ACIN 230V	0.52typ		
	FREQUENCY[Hz]		50 / 60 (45 - 440)		
	EFFICIENCY[%]	ACIN 100V	81.5typ	82.5typ	85.0typ
		ACIN 230V	85.0typ	85.0typ	87.5typ
	INRUSH CURRENT[A]	ACIN 100V	15typ (lo=100%) at cold start		
	ACIN 230V	35typ (lo=100%) at cold start			
	LEAKAGE CURRENT[ma] 0.3 / 0.65 max (ACIN 100V / 240V, 60Hz, lo=100%, According to IEC62368-1, and DEN-AN)				
OUTPUT	VOLTAGE[V]		5	12	24
	CURRENT[A] *2		10	4.3	2.2
	LINE REGULATION[mV] *3		20max	48max	96max
	LOAD REGULATION[mV] *3		40max	100max	150max
	RIPPLE[mVp-p] *4	0 to +50℃	80max	120max	120max
		-20 to 0℃	140max	160max	160max
		lo=0 to 15%	300max	300max	300max
	RIPPLE NOISE[mVp-p] *4	0 to +50℃	120max	150max	150max
		-20 to 0℃	160max	180max	180max
		lo=0 to 15%	360max	360max	360max
	TEMPERATURE REGULATION[mV]	0 to +50℃	50max	120max	240max
		-20 to +50℃	60max	150max	290max
	DRIFT[mV] *5		20max	48max	96max
	START-UP TIME[ms]		80typ (ACIN 100V, lo=100%)		
	HOLD-UP TIME[ms]		20typ (ACIN 100V, lo=100%) / 140typ (ACIN 230V, lo=100%)		
OUTPUT VOLTAGE ADJUSTMENT RANGE[V]		4.00 to 5.50	10.0 to 13.2	19.2 to 27.0	
OUTPUT VOLTAGE SETTING[V]		5.00 to 5.15	12.00 to 12.48	24.00 to 24.96	
PROTECTION CIRCUIT AND OTHERS	OVERCURRENT PROTECTION		Works over 105% of rating and recovers automatically		
	OVERVOLTAGE PROTECTION		5.75 to 7.00	15.0 to 18.0	30.0 to 37.0
	REMOTE SENSING		Not provided		
ISOLATION	INPUT-OUTPUT		AC3,000V 1minute, Cutoff current = 10mA, DC500V 100MΩ min (At Room Temperature)		
	INPUT-FG		AC2,000V 1minute, Cutoff current = 10mA, DC500V 100MΩ min (At Room Temperature)		
	OUTPUT-FG		AC500V 1minute, Cutoff current = 25mA, DC500V 100MΩ min (At Room Temperature)		
ENVIRONMENT	OPERATING TEMP.,HUMID.AND ALTITUDE *2		-20 to +70℃, 20 - 90%RH (Non condensing), 5,000m (16,500feet) max		
	STORAGE TEMP.,HUMID.AND ALTITUDE		-20 to +75℃, 20 - 90%RH (Non condensing), 9,000m (30,000feet) max		
	VIBRATION		10 - 55Hz, 19.6m/s ² (2G), 3minutes period, 60minutes each along X, Y and Z axis		
	IMPACT		196.1m/s ² (20G), 11ms, once each X, Y and Z axis		
SAFETY AND NOISE REGULATIONS	AGENCY APPROVALS		UL62368-1, c-UL (equivalent to CAN/CSA-C22.2No.62368-1), EN62368-1, Complies with DEN-AN		
	CONDUCTED NOISE		Complies with CISPR11-B, CISPR32-B, EN55011-B, EN55032-B, FCC Part15-B, FCC Part18-B, VCCI-B		
	HARMONIC ATTENUATOR *6		Complies with IEC61000-3-2 (Class A) (No built-in power factor correction)		
OTHERS	CASE SIZE/WEIGHT		31 X 82 X 120mm [1.22 X 3.23 X 4.72 inches] (without terminal block) (W X H X D) / 330g max (with cover : 370g max)		
	COOLING METHOD *2		Convection/Forced air (Requires external fan) (Refer to “Derating”)		

*1 The listed options may affect the published standard specifications. Please contact us for detailed product specifications.

*2 Derating is required. Please contact us for DC input.

*3 At low load conditions, the burst mode operation will start. To check load regulation, you will need to measure the characteristics at average mode with instruments.

*4 This is the value that measured on measuring board with capacitor of 22 μF at 150mm from output terminal.
Measured by 20MHz oscilloscope or Ripple-Noise meter
(Equivalent to KEISOKU-GIKEN:RM104).
Ripple and ripple noise spec is change at Io=0 to 15% by burst operation.

*5 Drift is the change in DC output for an eight hour period after a half-hour warm-up at 25°C, with the input voltage held constant at the rated input/output.


*6 Please contact us about another class. When two or more units are operating it may not comply with the IEC61000-3-2. Please contact us for details.

* To meet the specification, do not operate overload condition.


* Parallel operation is not possible.

* Sound noise may be generated by power supply in case of pulse load.

Block diagram




External view



PDA100F

PD A 100 F -□ -□
① ② ③ ④ ⑤ ⑥



Example recommended EMI/EMC filter
NAC-06-472



High voltage pulse noise type : NAP series
Low leakage current type : NAM series
* A higher current rating EMI/EMC filter may be recommended in view of the other devices that could be connected in parallel with the power supply.

- ① Series name
- ② Single output
- ③ Output wattage
- ④ Universal input
- ⑤ Output voltage
- ⑥ Optional *1
N : with cover

For option details, refer to Instruction Manual 6.

* Make sure necessary tests will be carried out on your end equipment with the power supply installed in accordance with any required EMC/EMI regulations.

MODEL	PDA100F-5	PDA100F-12	PDA100F-15	PDA100F-24
MAX OUTPUT WATTAGE[W]	100	102	105	108
DC OUTPUT	5V 20A	12V 8.5A	15V 7A	24V 4.5A

SPECIFICATIONS

MODEL	PDA100F-5	PDA100F-12	PDA100F-15	PDA100F-24
VOLTAGE[VAC]	85 - 264 1 φ (Refer to Instruction Manual 1.1)			
INPUT	CURRENT[A]	1.3typ		
	ACIN 100V	0.6typ		
	ACIN 230V			
	FREQUENCY[Hz]	50 / 60 (45 - 66)		
INPUT	EFFICIENCY[%]	87.0typ	88.5typ	87.5typ
	ACIN 100V	89.5typ	91.0typ	89.5typ
	ACIN 230V			
	POWER FACTOR (lo=100%)	0.97typ		
INPUT	ACIN 100V	0.87typ		
	ACIN 230V			
	INRUSH CURRENT[A]	15typ (lo=100%) at cold start		
	ACIN 230V	35typ (lo=100%) at cold start		
INPUT	LEAKAGE CURRENT[ma]	0.4 / 0.75 max (ACIN 100V / 240V, 60Hz, lo=100%, According to IEC62368-1, and DEN-AN)		
	VOLTAGE[V]	5	12	15
	CURRENT[A]	20	8.5	7
	LINE REGULATION[mV]	20max	48max	60max
OUTPUT	LOAD REGULATION[mV]	40max	100max	120max
	RIPPLE[mVp-p]	80max	120max	120max
	0 to +50°C	140max	160max	160max
	-20 to 0°C	300max	360max	500max
OUTPUT	RIPPLE NOISE[mVp-p]	120max	150max	150max
	0 to +50°C	160max	180max	180max
	-20 to 0°C	360max	400max	600max
	lo=0 to 15%	50max	120max	240max
OUTPUT	TEMPERATURE REGULATION[mV]	60max	150max	180max
	0 to +50°C	20max	60max	96max
	-20 to +50°C			
	DRIFT[mV]	20max	48max	60max
OUTPUT	START-UP TIME[ms]	100typ (ACIN 100V, lo=100%)		
	HOLD-UP TIME[ms]	20typ (ACIN 100V, lo=100%)		
	OUTPUT VOLTAGE ADJUSTMENT RANGE[V]	4.00 to 5.50	10.00 to 13.20	13.20 to 18.00
	OUTPUT VOLTAGE SETTING[V]	5.00 to 5.15	12.00 to 12.48	15.00 to 15.60
PROTECTION	OVERCURRENT PROTECTION	Works over 105% of rating and recovers automatically		
	OVERVOLTAGE PROTECTION	5.75 to 7.00	15.00 to 18.00	20.00 to 25.00
	REMOTE SENSING	Not provided		
	INPUT-OUTPUT	AC3,000V 1minute, Cutoff current = 10mA, DC500V 100MΩ min (At Room Temperature)		
ISOLATION	INPUT-FG	AC2,000V 1minute, Cutoff current = 10mA, DC500V 100MΩ min (At Room Temperature)		
	OUTPUT-FG	AC500V 1minute, Cutoff current = 25mA, DC500V 100MΩ min (At Room Temperature)		
	OPERATING TEMPERATURE,HUMID	-20 to +70°C, 20 - 90%RH (Non condensing)		
	STORAGE TEMPERATURE,HUMID	-20 to +75°C, 20 - 90%RH (Non condensing)		
ENVIRONMENT	VIBRATION	10 - 55Hz, 19.6m/s ² (2G), 3minutes period, 60minutes each along X, Y and Z axis		
	IMPACT	196.1m/s ² (20G), 11ms, once each X, Y and Z axis		
	SAFETY AND NOISE	UL62368-1, c-UL (equivalent to CAN/CSA-C22.2No.62368-1), EN62368-1, Complies with DEN-AN		
	CONDUCTED NOISE	Complies with CISPR11-B, CISPR32-B, EN55011-B, EN55032-B, FCC Part15-B, FCC Part18-B, VCCI-B		
REGULATIONS	HARMONIC ATTENUATOR	Complies with IEC61000-3-2 (Class A)		
	CASE SIZE/WEIGHT	32 X 93 X 147mm [1.26x3.66x5.79 inches] (without terminal block) / 440g max (with cover : 500g max)		
	COOLING METHOD	Convection/Forced air (Refer to "Derating")		

*1 The listed options may affect the published standard specifications. Please contact us for detailed product specifications.

*2 Derating is required. Please contact us for DC input.

*3 At low load conditions, the burst mode operation will start. To check load regulation, you will need to measure the characteristics at average mode with instruments.

*4 This is the value that measured on measuring board with capacitor of 22 μF at 150mm from output terminal.
Measured by 20MHz oscilloscope or Ripple-Noise meter

(Equivalent to KEISOKU-GIKEN:RM104).

Ripple and ripple noise spec is change at lo=0 to 15% by burst operation.

*5 Drift is the change in DC output for an eight hour period after a half-hour warm-up at 25°C, with the input voltage held constant at the rated input/output.


*6 Please contact us about another class. When two or more units are operating it may not comply with the IEC61000-3-2. Please contact us for details.

* To meet the specification, do not operate overload condition.


* Parallel operation is not possible.

* Sound noise may be generated by power supply in case of pulse load.

Block diagram




External view



- * Tolerance : ± 1
- * Weight : 440g max (with cover : 500g max)
- * PCB Material / thickness : FR-4 / 1.6mm [0.06]
- * Chassis material : Aluminum
- * Dimensions in mm, [] = inches
- * Mounting torque : $0.6N \cdot m$ max
- * Screw tightening torque : $M4 \ 1.6N \cdot m$ max
- * Please connect safety ground to the FG terminal on the unit.
- * Point ① is the thermometry points. Please refer to Instruction Manual 3.

PDA150F

PD A 150 F -□ -□
① ② ③ ④ ⑤ ⑥



Example recommended EMI/EMC filter
NAC-06-472



High voltage pulse noise type : NAP series
Low leakage current type : NAM series
* A higher current rating EMI/EMC filter may be recommended in view of the other devices that could be connected in parallel with the power supply.

- ① Series name
- ② Single output
- ③ Output wattage
- ④ Universal input
- ⑤ Output voltage
- ⑥ Optional *1
N : with cover

For option details, refer to Instruction Manual 6.

* Make sure necessary tests will be carried out on your end equipment with the power supply installed in accordance with any required EMC/EMI regulations.

MODEL	PDA150F-5	PDA150F-12	PDA150F-15	PDA150F-24
MAX OUTPUT WATTAGE[W]	150	156	150	156
DC OUTPUT	5V 30A	12V 13A	15V 10A	24V 6.5A

SPECIFICATIONS

MODEL	PDA150F-5	PDA150F-12	PDA150F-15	PDA150F-24
VOLTAGE[VAC]	85 - 264 1 φ (Refer to Instruction Manual 1.1)			
INPUT	CURRENT[A]	1.8typ		
	ACIN 100V	0.9typ		
	ACIN 230V			
	FREQUENCY[Hz]	50 / 60 (45 - 66)		
INPUT	EFFICIENCY[%]	85.0typ	87.0typ	87.0typ
	ACIN 100V	87.5typ	89.0typ	89.0typ
	ACIN 230V			
	POWER FACTOR (lo=100%)	0.97typ	0.97typ	0.97typ
INPUT	ACIN 100V	15typ (lo=100%) at cold start		
	ACIN 230V	35typ (lo=100%) at cold start		
INPUT	LEAKAGE CURRENT[mA]	0.4 / 0.75 max (ACIN 100V / 240V, 60Hz, lo=100%, According to IEC62368-1, and DEN-AN)		
OUTPUT	VOLTAGE[V]	5	12	15
	CURRENT[A]	30	13	10
	LINE REGULATION[mV]	20max	48max	60max
	LOAD REGULATION[mV]	40max	100max	120max
	RIPPLE[mVp-p]	0 to +50°C	80max	120max
		-20 to 0°C	140max	160max
		lo=0 to 15%	300max	500max
	RIPPLE NOISE[mVp-p]	0 to +50°C	120max	150max
		-20 to 0°C	160max	180max
		lo=0 to 15%	360max	600max
	TEMPERATURE REGULATION[mV]	0 to +50°C	50max	150max
		-20 to +50°C	60max	290max
	DRIFT[mV]	20max	48max	60max
	START-UP TIME[ms]	120typ (ACIN 100V, lo=100%)		
PROTECTION CIRCUIT AND OTHERS	HOLD-UP TIME[ms]	20typ (ACIN 100V, lo=100%)		
	OUTPUT VOLTAGE ADJUSTMENT RANGE[V]	4.00 to 5.50	10.00 to 13.20	13.20 to 18.00
	OUTPUT VOLTAGE SETTING[V]	5.00 to 5.15	12.00 to 12.48	15.00 to 15.60
	24.00 to 24.96			
ISOLATION	OVERCURRENT PROTECTION	Works over 105% of rating and recovers automatically		
	OVERVOLTAGE PROTECTION	5.75 to 7.00	15.00 to 18.00	20.00 to 25.00
	REMOTE SENSING	Not provided		
ENVIRONMENT	INPUT-OUTPUT	AC3,000V 1minute, Cutoff current = 10mA, DC500V 100MΩ min (At Room Temperature)		
	INPUT-FG	AC2,000V 1minute, Cutoff current = 10mA, DC500V 100MΩ min (At Room Temperature)		
	OUTPUT-FG	AC500V 1minute, Cutoff current = 25mA, DC500V 100MΩ min (At Room Temperature)		
SAFETY AND NOISE REGULATIONS	OPERATING TEMPERATURE,HUMID	-20 to +70°C, 20 - 90%RH (Non condensing)		
	STORAGE TEMPERATURE,HUMID	-20 to +75°C, 20 - 90%RH (Non condensing)		
	VIBRATION	10 - 55Hz, 19.6m/s ² (2G), 3minutes period, 60minutes each along X, Y and Z axis		
	IMPACT	196.1m/s ² (20G), 11ms, once each X, Y and Z axis		
OTHERS	AGENCY APPROVALS	UL62368-1, c-UL (equivalent to CAN/CSA-C22.2No.62368-1), EN62368-1, Complies with DEN-AN		
	CONDUCTED NOISE	Complies with CISPR11-B, CISPR32-B, EN55011-B, EN55032-B, FCC Part15-B, FCC Part18-B, VCCI-B		
	HARMONIC ATTENUATOR	Complies with IEC61000-3-2 (Class A)		
OTHERS	CASE SIZE/WEIGHT	34 X 93 X 168mm [1.34x3.66x6.61 inches] (without terminal block) / 530g max (with cover : 600g max)		
	COOLING METHOD	Convection/Forced air (Refer to "Derating")		

*1 The listed options may affect the published standard specifications. Please contact us for detailed product specifications.

*2 Derating is required. Please contact us for DC input.

*3 At low load conditions, the burst mode operation will start. To check load regulation, you will need to measure the characteristics at average mode with instruments.

*4 This is the value that measured on measuring board with capacitor of 22 μF at 150mm from output terminal.
Measured by 20MHz oscilloscope or Ripple-Noise meter

(Equivalent to KEISOKU-GIKEN:RM104).

Ripple and ripple noise spec is change at lo=0 to 15% by burst operation.

*5 Drift is the change in DC output for an eight hour period after a half-hour warm-up at 25°C, with the input voltage held constant at the rated input/output.


*6 Please contact us about another class. When two or more units are operating it may not comply with the IEC61000-3-2. Please contact us for details.

To meet the specification, do not operate overload condition.


* Parallel operation is not possible.

* Sound noise may be generated by power supply in case of pulse load.

Block diagram



External view



- * Tolerance : ± 1
- * Weight : 530g max (with cover : 600g max)
- * PCB Material / thickness : FR-4 / 1.6mm [0.06]
- * Chassis material : Aluminum
- * Dimensions in mm, [] = inches
- * Mounting torque : 0.6N · m max
- * Screw tightening torque : M4 1.6N · m max
- * Please connect safety ground to the FG terminal on the unit.
- * Keep drawing current per pin below 20A for TB1.
- * Point ① is the thermometry points. Please refer to Instruction Manual 3.

Assembling and Installation Method

Installation method


■ For the metal chassis, keep the distance d1 for isolation between component and metal chassis.

The d1 dimension is the distance required for insulation and does not satisfy cooling conditions. For cooling conditions, please refer to "Derating" and section 3 of the instruction manual.

■ Do not insert a screw more than 6mm from the outside of a power supply to keep enough insulation distance between the screw and internal components.


■ If you use two or more power supplies side by side, please keep a sufficient distance between them to allow enough air ventilation.

■ Ambient temperature around each power supply should not exceed the temperature range shown in "Derating".




Derating


Derating curve for input voltage PDA15F, PDA30F



PDA15F Ambient temperature derating curve (Reference value)




PDA15F-□-N Ambient temperature derating curve (Reference value)




Derating


- PDA30F
Ambient temperature derating curve
(Reference value)




- PDA30F-□-N
Ambient temperature derating curve
(Reference value)




- PDA50F-5
Ambient temperature derating curve
(Reference value)




- PDA50F-5-N
Ambient temperature derating curve
(Reference value)




- PDA50F-12, -24
Ambient temperature derating curve
(Reference value)




- PDA50F-12-N, -24-N
Ambient temperature derating curve
(Reference value)



- PDA100F
Ambient temperature derating curve
(Reference value)




- PDA100F-□-N
Ambient temperature derating curve
(Reference value)




Derating


● PDA150F-5 Ambient temperature derating curve (Reference value)




● PDA150F-5-N Ambient temperature derating curve (Reference value)



● PDA150F-12, -15, -24 Ambient temperature derating curve (Reference value)



● PDA150F-12-N, -15-N, -24-N Ambient temperature derating curve (Reference value)



- The operating ambient temperature is different by with / without chassis cover or mounting position.
- In the hatched area, the specification of Ripple, Ripple Noise is different from other area.
- The ambient temperature should be measured 5 to 10 cm away from the power supply so that it won't be influenced by the heat from the power supply.
- Please make sure the maximum component temperature rise given in Instruction manual 3 is not exceeded.
- Please contact us for more information about operating ambient temperature.

Instruction Manuals

- ◆ Please see catalog and instructionmanual before you use.

Instruction Manuals <https://www.cosel.co.jp/redirect/catalog/en/PDA/>
Before using our product <https://en.cosel.co.jp/technical/caution/index.html>



Basic Characteristics Data

Model	Circuit method	Switching frequency [kHz] *1 *2	Input current *3 [A]	Inrush current protection	PCB/Pattern			Series/Parallel operation availability	
					Material	Single sided	Double	Series operation	Parallel operation
PDA15F	Flyback converter	20 to 125	0.35	Thermistor	CEM-3	Yes	-	Yes	No
PDA30F	Flyback converter	30 to 130	0.62	Thermistor	CEM-3	Yes	-	Yes	No
PDA50F	Flyback converter	25 to 130	1.05	Thermistor	CEM-3	Yes	-	Yes	No
PDA100F	Active filter	20 to 250	1.3	Thermistor	FR-4	-	Yes	Yes	No
	Flyback converter	45 to 110							
PDA150F	Active filter	20 to 250	1.8	Thermistor	FR-4	-	Yes	Yes	No
	Flyback converter	45 to 110							

*1 The value changes depending on input and load.

*2 At light load, burst operation is performed to reduce input power. The switching frequency is changed by using condition. Please contact us for more details.

*3 The value of input current is at ACIN 100V and rated load.

Mouser Electronics

Authorized Distributor

Click to View Pricing, Inventory, Delivery & Lifecycle Information:

[Cosel:](#)

[PDA150F-24](#) [PDA100F-12-N](#) [PDA100F-24](#) [PDA150F-24-N](#) [PDA100F-15-N](#) [PDA150F-12](#) [PDA150F-15-N](#)
[PDA100F-24-N](#) [PDA100F-12](#) [PDA100F-15](#) [PDA150F-15](#) [PDA150F-12-N](#)