

ADA Series

Special attachment for installation of ADA Series is prepared.

Installation attachment type	Model
F-ADA-1	ADA Series
F-ADA-2	ADA Series
F-ADA-3	ADA Series
F-ADA-4	ADA Series
F-ADA-5	ADA600F

★Refer to Instruction Manual 2.3 for installation A, B and C.

F-ADA-1 ★Material:SPCC t=2.0	F-ADA-2 ★Material:SPCC t=2.0	F-ADA-3 ★Material:SPCC t=2.0
① It is use in accordance with installation B. ② It is use in accordance with installation A.	① Using hole-A It is use in accordance with installation B. ② Using hole-B It is use in accordance with installation A.	It is possible to comply with installation A because the space is kept by 30mm.
F-ADA-4 ★Material:SPCC t=2.0	F-ADA-5 ★Material:SPCC t=2.0	
It is use in accordance with installation C. It is possible to comply with installation A or B when the power supply is vertically installed.	It is possible to install from the rear, and to use from the front. (Only ADA600F)	

Harness to use the function of ADA Series is prepared.

★ Please see the our company home page or consult us about detailed information.

ADA Series

Mating harness


Model	Harness model #	Contents
ADA Series	H-SN-23	:Harness for using option:-W and/or -R when I/O interface is terminal block type (standard).
	H-IN-11	:Input harness when I/O interface is connector type (option:-J).
	H-OU-26	:Output harness when I/O interface is connector type (option:-J).
	H-PA-5	:Harness for parallel operation when I/O interface is connector type (option:-J).
	H-RC-2	:Harness for using option:-R when I/O interface is connector type (option:-J).

●Model number

H-SN-23

Housing : PHDR-14VS(J.S.T)
Pin : SPHD-002T-P0.5(J.S.T)

●Type



●Wire

Pin #	Wire	AWG	Color	Length ℓ (mm)
1	UL1061	28	red	500
2	UL1061	28	black	500
3	-	-	-	-
4	-	-	-	-
5	-	-	-	-
6	-	-	-	-
7	-	-	-	-
8	-	-	-	-
9	UL1061	28	orange	500
10	UL1061	28	blue	500
11	-	-	-	-
12	-	-	-	-
13	UL1061	28	yellow	500
14	UL1061	28	black	500


★ Even number pin side of the connector is the same wiring as odd number pin side.

●Model number

H-IN-11

Housing : 1-178129-6(AMP)
Pin : 1-175218-5 equivalent goods(AMP)

●Type



●Wire


Pin #	Wire	AWG	Color	Length ℓ (mm)
B 1	UL1051	18	white	500
A 1	UL1051	18	white	500
B 2	-	-	-	-
A 2	-	-	-	-
B 3	UL1051	18	black	500
A 3	UL1051	18	black	500

●Model number

H-OU-26

Housing : 178289-5(AMP)
Pin : 1-353717-5 equivalent goods(AMP)

●Type



●Wire


Pin #	Wire	AWG	Color	Length ℓ (mm)
B 1	UL1007	16	red	500
A 1	UL1007	16	red	500
B 2	UL1007	16	red	500
A 2	UL1007	16	red	500
B 3	UL1007	16	red	500
A 3	UL1007	16	black	500
B 4	UL1007	16	black	500
A 4	UL1007	16	black	500
B 5	UL1007	16	black	500
A 5	UL1007	16	black	500

●Model number

H-PA-5

Housing : 171822-2(AMP)
Pin : 170204-2 equivalent goods(AMP)

●Type



●Wire


Pin #	Wire	AWG	Color	Length ℓ (mm)
1	UL1007	22	white	200
2	UL1007	22	black	200

●Model number

H-RC-2

Housing : 171822-3(AMP)
Pin : 170204-2 equivalent goods(AMP)

●Type









●Wire

Pin #	Wire	AWG	Color	Length ℓ (mm)
1	UL1007	22	white	500
2	-	-	-	-
3	UL1007	22	red	500

Fan unit

ADA Series

Fan unit type	Matching model	External	Harness								
FAN-AD6-24	ADA600F-24		<table><tr><th colspan="2">Wire</th></tr><tr><th>Color</th><th>Content</th></tr><tr><td>red</td><td>POWER</td></tr><tr><td>black</td><td>GND</td></tr></table>	Wire		Color	Content	red	POWER	black	GND
Wire											
Color	Content										
red	POWER										
black	GND										
FAN-AD6-48	ADA600F-30 ADA600F-36 ADA600F-48		<table><tr><th colspan="2">Wire</th></tr><tr><th>Color</th><th>Content</th></tr><tr><td>red</td><td>POWER</td></tr><tr><td>black</td><td>GND</td></tr></table>	Wire		Color	Content	red	POWER	black	GND
Wire											
Color	Content										
red	POWER										
black	GND										
FAN-AD7-24	ADA750F-24		<table><tr><th colspan="2">Wire</th></tr><tr><th>Color</th><th>Content</th></tr><tr><td>red</td><td>POWER</td></tr><tr><td>black</td><td>GND</td></tr></table>	Wire		Color	Content	red	POWER	black	GND
Wire											
Color	Content										
red	POWER										
black	GND										
FAN-AD7-48	ADA750F-30 ADA750F-36 ADA750F-48		<table><tr><th colspan="2">Wire</th></tr><tr><th>Color</th><th>Content</th></tr><tr><td>red</td><td>POWER</td></tr><tr><td>black</td><td>GND</td></tr></table>	Wire		Color	Content	red	POWER	black	GND
Wire											
Color	Content										
red	POWER										
black	GND										
FAN-AD1-24	ADA1000F-24		<table><tr><th colspan="2">Wire</th></tr><tr><th>Color</th><th>Content</th></tr><tr><td>red</td><td>POWER</td></tr><tr><td>black</td><td>GND</td></tr></table>	Wire		Color	Content	red	POWER	black	GND
Wire											
Color	Content										
red	POWER										
black	GND										
FAN-AD1-48	ADA1000F-30 ADA1000F-36 ADA1000F-48		<table><tr><th colspan="2">Wire</th></tr><tr><th>Color</th><th>Content</th></tr><tr><td>red</td><td>POWER</td></tr><tr><td>black</td><td>GND</td></tr></table>	Wire		Color	Content	red	POWER	black	GND
Wire											
Color	Content										
red	POWER										
black	GND										

- * 1 Handle with care and don't add the impact such as falls or throwing to the unit.
- * 2 Exchange the unit after intercepting the input power.
- * 3 When the unit is exchanged, make sure there are not loosening of terminal screw and shutting the harness.

Mouser Electronics

Authorized Distributor

Click to View Pricing, Inventory, Delivery & Lifecycle Information:

Cosel:

[F-ADA-2](#) [F-ADA-3](#) [F-ADA-1](#) [F-ADA-4](#) [F-ADA-5](#)