




## Bestückungsplan / contact layout



## Leiterplatten-Lochbild / PCB drillhole pattern





Elastische Einpresszone / compliant pressfit zone

Isolierwerkstoff / housing material : PBT GF30

Bauart 7 / type 7

Anforderungsstufe 2 = 400 Steckzyklen / performance class 2 = 400 mating cycles

Fehlende Masse und Angaben nach IEC 60 603-2 / DIN EN 60 603-2

Missing information and dimensions per IEC 60 603-2 / DIN EN 60 603-2

Schichtaufbau im metallisierten Loch siehe Zeichnung 164062/Nr.6

diameter of drilled hale see drawing 164062/No.6

1)  $\phi$  1,0  $\stackrel{+}{_{-}}$  0.09 Durchmesser des metallisierten Loches

Ø 1,0 - 0,09 Diameter of finished plated-through hole

 $\emptyset$  1,15 ± 0.025 Bohrungsdurchmesser des Loches

Ø 1,15 ± 0.025 Diameter of drilled hole

34	Information:	Tolerances	$\Leftrightarrow \Box$	Scale 2	:1	
Consider protection memo from DIN			All Dimensions in mm			
		Subject to modification without prior notice. Drawing will not be updated.		Federleiste B/3, 20 EE Fem. Con. B/3, 20 Pressfit		
		<b>erni</b> www.E	RNI.com		284418	
	Index Date	H:00062514.	SZA		STVB/3	,

## **Mouser Electronics**

**Authorized Distributor** 

Click to View Pricing, Inventory, Delivery & Lifecycle Information:

ERNI Electronics:

284418