




The diagram shows a rectangular grid with dimensions and labels. The width is labeled as $18 \times 2 = 36$ and the height as $4 \times 2 = 8$. The grid is composed of 18 columns and 4 rows of squares. The columns are labeled 1 through 19, and the rows are labeled a through e. The grid is divided into four quadrants by a vertical line between columns 18 and 19, and a horizontal line between rows 4 and 5. The quadrants are labeled 1, 2, 3, and 4. The grid is also divided into four quadrants by a vertical line between columns 18 and 19, and a horizontal line between rows 4 and 5. The quadrants are labeled 1, 2, 3, and 4. The grid is also divided into four quadrants by a vertical line between columns 18 and 19, and a horizontal line between rows 4 and 5. The quadrants are labeled 1, 2, 3, and 4.



Technical drawing of a perforated plate (Fig. 10.10). The drawing shows a rectangular plate with a grid of circular holes. Dimensions include a total width of $18 \times 2 = 36$, a total height of $4 \times 2 = 8$, and a hole diameter of $\varnothing 0,05$. The text "alle Löcher all holes" is present. The plate is shown with a wavy line indicating a cross-section, and a dashed line indicates the internal structure. The plate is labeled with "1)" and "2)".

Information: BA 2	Tolerances		 All Dimensions in mm	Scale	2:1	
	All rights reserved. Only for information. To insure that this is the latest version of this drawing, please contact one of the ERNI companies before using.			Subject to modification without prior notice. Drawing will not be updated.		Designation ERmet Federleiste B 19 <i>ERmet Female Type B 19</i>
			 www.ERNI.com	354145		I
c		02.06.2010		ERMB19		
Index		Date	0-00069845.SZA			

Mouser Electronics

Authorized Distributor

Click to View Pricing, Inventory, Delivery & Lifecycle Information:

[ERNI Electronics:](#)

[354145](#)