



Kontaktübersicht:
contacts overview

L = lang / long
M = mittel / middle
S = kurz / short






M 1 : 5


verpackt in Tray
VPE: 36 St.

tray packaging
packaging unit 36 pcs.

DETAIL A
MAßSTAB 1 : 1



Bestückungsplan
contact layout




Gehäuse / housing: PBTP grau 30% GF / PBTP gray 30 %GF
Kontakte / contacts: Phosphor Bronze / phosphor bronze

Oberflächenbeschichtung / plating:
Kontaktbereich
/ mating area: 2-3 µm Ni 1.2 µm Au
Anschlussbereich
/ termination: 2-3 µm Ni 1 µm Sn matt

Bedruckungsvorschrift siehe Id.-Nr. 294996 /
printingcode Id.-No. 294996

Anforderungsstufe 1
class 1



Lochbild für Leiterplatte
Board hole pattern

- 1) $\varnothing 0.6 \pm 0.05$ Durchmesser des
metallisierten Loches
 $\varnothing 0.6 \pm 0.05$ Diameter of finished
plated-through hole

Schichtaufbau im metallisierten Loch
siehe Zeichnung 114406
Metal plating of plated-through hole
see drawing 114406

Copyright by ERNI GmbH.
Proprietary notice pursuant to ISO 16016 to be observed.

Information:		Tolerances		Scale	3:1
All rights reserved. Only for Information. To ensure that this is the latest version of this drawing, please contact one of the ERNI companies before using.		Subject to modification without prior notice. Drawing will not be updated.		Designation	
-		03.09.2007		ERmet Messerl. PM 7 pol RC ERmet Male PM 7 pin RC	
Index		Date		254018	
				Class	
				ERPM	

Mouser Electronics

Authorized Distributor

Click to View Pricing, Inventory, Delivery & Lifecycle Information:

[ERNI Electronics:](#)

[254018](#)