









Bestückungsplan / contact layout



M / scale 2:1

Lochbild für Leiterplatte
(Bestückungsseite)

board hole pattern
(component mounting side)




- 1) $\varnothing 0,6 \pm 0,05$ Durchmesser des metallisierten Loches
 $\varnothing 0,6 \pm 0,05$ Diameter of finished plated-through hole

Schichtaufbau im metallisierten Loch siehe Zeichnung 164062 Nr.1
 Metal plating of plated-through hole according to 164062 No.1

Fehlende Maße und Angaben nach IEC 61076-4-101
 Missing information and dimensions per IEC 61076-4-101

Copyright by ERNI Production GmbH & Co. KG
Proprietary notice pursuant to ISO 16101 to be observed.

Information: Distanzstück $H=3.1$ / <i>distance $H=3.1$</i> Abschirmbleche Reihe z+f montiert <i>shieldings row z+f mounted</i> Anforderungsstufe 2 / <i>class 2</i>				Tolerances  All Dimensions in mm		Scale 2:1	
All rights reserved. Only for Information. To ensure that this is the latest version of this drawing, please contact one of the ERNI companies before using.				Subject to modification without prior notice. Drawing will not be updated.		Designation ERmet-FS Federleiste C <i>ERmet-Female Straight Type C</i>	
				www.ERNI.com		114028	
e		23.01.2018				I	
Index		Date				A3	
						Class ERMC	

Copyright by ERNI Production GmbH & Co. KG
Proprietary notice pursuant to ISO 16016 to be observed.

Mouser Electronics

Authorized Distributor

Click to View Pricing, Inventory, Delivery & Lifecycle Information:

[ERNI Electronics:](#)

[114028](#)