



SERIES 38BT and 38BH Sub-Miniature Horizontal PC Mount

FEATURES

- Drop-In Replacement for Industry Standard
- Sealed Plunger Option
- Printed Circuit Board Mount
- SPST and SPDT, Momentary Contact



DIMENSIONS in inches (and millimeters)



SPECIFICATIONS

Rating Criteria

Operating Life: 80,000 make-and-break cycles at full load

Contact Rating (resistive load):

Gold Contacts: 0.4 VA maximum at 20 Vac or Vdc maximum

Silver Contacts: 1.0 Amp maximum at 120 Vac or 28 Vdc

Contact Resistance: Below 20 milliohms typical initial at 2-4 Vdc, 100 mA

Insulation Resistance: 1000 megaohms min.

Voltage Breakdown: 1000 Vrms minimum at sea level

Operating Temperature: -30°C. to +85°C.

Solderability: Per MIL-STD-202F, Method 208D, or EIA RS-186E Method 9 (1 hour steam aging)

Materials and Finishes

Base and Cover: Thermoplastic (UL 94V-0)

Plunger: Thermoplastic (UL 94V-0), (S versions include an internal o-ring seal)



Terminals: Copper alloy, gold or silver plate (as specified) over nickel plate

Spring: Plated Music Wire


Contact System: Copper alloy, gold or silver plate (as specified) over nickel plate

Switch Support: Brass, tin-plated

CIRCUITRY



ORDERING INFORMATION



Mouser Electronics

Authorized Distributor

Click to View Pricing, Inventory, Delivery & Lifecycle Information:

Grayhill:

[38BT-4-H-4-S](#) [38BH-4-H-2-S](#) [38BH-4-H-4-S](#) [38BT-0-H-3-N](#) [38BH-0-H-3-S](#) [38BH-4-H-2-N](#) [38BT-4-H-3-S](#) [38BH-0-H-1-S](#) [38BH-4-H-1-S](#) [38BH-4-H-3-N](#) [38BT-0-H-4-N](#) [38BT-4-H-4-N](#)