

Actuator

61-1310.0







61-1310.0 Actuator

_	_	-		_
-	u	m	N	п
	ıı	v	13	

Front dimension: Ø 18 mm

Front form: round

Front bezel colour: Black

Front bezel material: Plastic

MOUNTING

Mounting cut-out: Ø 16 mm

Mounting type: Panel mounting

OPERATING-/INDICATION PART

Lens illumination: illuminative

MECHANICAL CHARATERISTIC

Switching action: Maintained or momentary

Mechanical lifetime: According to DIN/IEC 60512-5-6 and EN/IEC 60947-5-1, 1 Mio. cycles of

operation (maintain), 2 Mio. cycles of operation (momentary)

Operating force: 3 N ... 5 N snap-action switching element, 3.5 ... 11 N slow-make switching

element

Operating Travel: 3 mm

Tightening torque: Max. 0.5 Nm

Weight: 0.005 kg

AMBIENT CONDITION

IP 40 rear side, according to EN IEC 60529, IP67 front side, according to EN IEC

60529

Operating temperature: $-25 \, ^{\circ}\text{C} \, ... + 55 \, ^{\circ}\text{C}$

Storage temperature: $-40 \, ^{\circ}\text{C} \dots + 85 \, ^{\circ}\text{C}$

CERTIFICATE

REACH: REACH compliant

RoHS: RoHS compliant

OTHER

Short Description: Actuator, Ø 16 mm, Ø 18 mm, illuminative, round, Black, Plastic, Maintained or

momentary


Internal size: Ø 15,8 mm

Housing colour: Black


Housing material: Plastic, according to UL 94 V0, self-extinguishing

Hints: Convertible from momentary to maintained action

Wiring diagrams:




Mounting cut-outs:



A = Solder/Plug-in terminal 2.8 mm x 0.5 mm

C = Screw terminal

Dimension drawings:



A = Plug-in terminal 2.8 mm x 0.5 mm C = Screw terminal E = Slow-make switching element F = Snap-action switching element

Where to Buy

	Distributor	Quantity in Stock	
DigiKey	Digi-Key	9 in stock	Buy ☐
MOUSER	Mouser Electronics	0 in stock	Buy ☐
Newark	Newark Electronics	0 in stock	Buy
SICER ELECTRONICS	Sager	0 in stock	Buy
RS	RS Americas	0 in stock	Buy 🛱

Powered by oemsecrets.com

Mouser Electronics

Authorized Distributor

Click to View Pricing, Inventory, Delivery & Lifecycle Information:

EAO:

61-1310.0