

# Actuator

704.011.218







### 704.011.218 Actuator

Е	D	0	N	٦
г	п	v	14	

Front dimension: Ø 35 mm

Front form: round

Front bezel colour: Nature

Front bezel material: Aluminium

#### **MOUNTING**

Design: flush

Mounting cut-out: Ø 30.5 mm

Mounting type: Panel mounting

#### **OPERATING-/INDICATION PART**

Lens colour: Red

Lens material: Aluminium

Lens illumination: non illuminative

Lens shape: flush

**Lens optics:** opaque

#### **ELECTRICAL CHARACTERISTICS**


Standards: The switches comply with the "Standards for low-voltage switching devices" DIN

EN 60947-1

#### **MECHANICAL CHARATERISTIC**

Switching action: Momentary


Mechanical lifetime:	≤3 Mio. cycles of operation		
Operating force:	8 N		
Operating Travel:	ca. 5.8 mm ± 0.2 mm		
Weight:	0.051 kg		
AMBIENT CONDITION			
IP Protection:	IP65 front side		
Operating temperature:	– 40 °C + 55 °C		
Storage temperature:	– 40 °C + 85 °C		
CERTIFICATE			
REACH:	REACH compliant		
RoHS:	RoHS compliant		
OTHER			
Short Description:	Actuator, $\varnothing$ 30.5 mm, $\varnothing$ 35 mm, flush, non illuminative, Red, Aluminium, opaque, round, Nature, Aluminium, anodised, Momentary		
Housing colour:	Grey		
Housing material:	Plastic		
Hints:	Max. 3 switching elements can be clipped on, The colour of anodised aluminium parts can vary due to technical production reasons		
max. number of switching elements:	3		
Wiring diagrams:  Mounting cut-outs:	E		
mounting cut-outs.			



A = Screw terminal

B = Push-in terminal (PIT)
C = Plug-in terminal 6.3 mm x 0.8 mm
D = Double plug-in terminal 6.3 mm x 0.8

#### **Dimension drawings:**



A = Screw terminal

### Where to Buy

	Distributor	Quantity in Stock	
RS	RS Americas	75 in stock	Buy □
DigiKey	Digi-Key	10 in stock	Buy 🛱
MOUSER	Mouser Electronics	5 in stock	Buy 🛱

Powered by oemsecrets.com

## **Mouser Electronics**

**Authorized Distributor** 

Click to View Pricing, Inventory, Delivery & Lifecycle Information:

EAO:

704.011.218