

EAO – Your Expert Partner for Human Machine Interfaces

10-A312.314A - Bi-colour LED

10-A312.314A - Bi-colour LED



Attention: The preview is based on a sample product. This can differ from your current configuration.

Other Attributes

Weight	0,002 kg
Operation current	15 / 14 mA ± 15 %
Operating voltage	24 V DC $+10$ %

Illumination

LED colour	red/green
Socket	T1 $\frac{3}{4}$ MG


Optics

Lumi. intensity	600 / 630 mcd
Dom. wavelength	625/525 nm

EAO – Your Expert Partner for Human Machine Interfaces

10-A312.314A - Bi-colour LED

Dimensions



Additional information

Luminous intensity data of the LEDs on direct voltage

Electrical and optical data are measured at 25 °C

The specified versions are built with a protection diode (half wave rectifier) in series and the LED

If the 24VDC Bi-colour lamp is driven with normal polarity (plus on middle contact of the lamp) the first mentioned colour will light up, with inverted polarity the second colour will light up

Luminosity and wave length variations caused by LED manufacturing processes may cause slight differences regarding the illumination

Mouser Electronics

Authorized Distributor

Click to View Pricing, Inventory, Delivery & Lifecycle Information:

EAO:

[10-A312.314A](#)