# EAO – Your Expert Partner for Human Machine Interfaces

#### 82-6151.0215 - Indicator 22 mm stainless-steel

#### 82-6151.0215 - Indicator 22 mm stainless-steel



Attention: The preview is based on a sample product. This can differ from your current configuration.

#### Mounting

 $\begin{array}{ll} \text{Design} & \text{flush} \\ \text{Mounting cut-out} & \varnothing \ 22,3 \ \text{mm} \end{array}$ 

#### **Front**

Front dimension Ø 25 mm
Front shape round
Front ring shape flush

Front bezel material Stainless steel

#### Other Attributes

Operating voltage 110 V AC Weight 0,021 kg
Operation current 2 mA

#### Operating-/Indication part

Lens optics opaque
Lens material Stainless steel
Lens profile flat
Lens illumination illuminative
Lens colour Stainless steel

#### **IP-Rating**

Front protection IP65, IP67

#### **Connection Method**

Terminal Solder 2.8 x 0.5 mm

#### Illumination

Illumination Dot with red LED

#### **Function**


Indicator

eao 🔳


# EAO – Your Expert Partner for **Human Machine Interfaces**

### 82-6151.0215 - Indicator 22 mm stainless-steel


#### **Dimensions**




#### **Mounting cut-outs**



#### Wiring diagram



#### **Component layout**



eao 🔳

## **Mouser Electronics**

**Authorized Distributor** 

Click to View Pricing, Inventory, Delivery & Lifecycle Information:

EAO:

82-6151.0215