

EAO – Your Expert Partner for Human Machine Interfaces

82-6152.0124 - Indicator 22 mm stainless-steel

82-6152.0124 - Indicator 22 mm stainless-steel



Attention: The preview is based on a sample product. This can differ from your current configuration.

Mounting

| | |
|------------------|-----------|
| Design | flush |
| Mounting cut-out | Ø 22,3 mm |

Front

| | |
|----------------------|-----------------|
| Front dimension | Ø 25 mm |
| Front shape | round |
| Front ring shape | flush |
| Front bezel material | Stainless steel |

Other Attributes

| | |
|-------------------|------------|
| Operating voltage | 24 V AC/DC |
| Weight | 0,018 kg |
| Operation current | 7 mA |

Operating-/Indication part

| | |
|-------------------|-----------------|
| Lens optics | opaque |
| Lens material | Stainless steel |
| Lens profile | flat |
| Lens illumination | illuminative |
| Lens colour | Stainless steel |

IP-Rating

| | |
|------------------|------------|
| Front protection | IP65, IP67 |
|------------------|------------|

Connection Method

| | |
|----------|----------------|
| Terminal | Screw terminal |
|----------|----------------|

Illumination

| | |
|--------------|--------------------|
| Illumination | Ring with blue LED |
|--------------|--------------------|

Function

| |
|-----------|
| Indicator |
|-----------|

EAO – Your Expert Partner for Human Machine Interfaces

82-6152.0124 - Indicator 22 mm stainless-steel


Dimensions




Mounting cut-outs



Wiring diagram



Component layout



Mouser Electronics

Authorized Distributor

Click to View Pricing, Inventory, Delivery & Lifecycle Information:

EAO:

82-6152.0124