



### FEATURES

- ♦ Fully encapsulated Plastic Case
- ♦ 3 Mounting Versions:
  - PCB Mounting with Solder Pins
  - Chassis Mounting with Screw Terminals
  - DIN-Rail Mounting
- ♦ Package Dimension 88.9x67.5x34.2 mm (PCB Mounting Version)
- ♦ Universal Input 85-264VAC, 47-440 Hz
- ♦ Protection Class II
- ♦ Extended Operating Temp.Range -40°C to +60°C at full Load
- ♦ LED Output Indicator (Chassis Version Models)
- ♦ Industrial Safety to UL/cUL/IEC/EN 60950-1 and UL508
- ♦ Medical Safety Approval to UL/cUL/IEC/EN 60601-1 3<sup>rd</sup> Edition
- ♦ Over Load Protection
- ♦ 3 Year Product Warranty

The new AB60S series is a range of fully encapsulated AC/DC power modules. These high performance products feature an extended operating temperature range of -40°C to +80°C. Universal input voltage 85-264VAC and UL/IEC/EN safety approvals including medical safety and UL508 listing qualify these power supplies modules for applications in products with worldwide markets. EMI-filter meets EN55022, class B and FCC, part 15, class B.

The AB60S series power modules provide an economical solution for many space critical applications in commercial, medical and industrial electronic equipment.

### Model Selection Guide

Model Number PCB Mounting	Output Voltage	Output Current Max. mA	Input Current		Max. capacitive Load μF	Efficiency (typ.) @Max. Load, 115VAC %
			115VAC, 60Hz	230VAC, 50Hz		
	VDC		@Max. Load mA(typ.)			
AB60S0500A	5.1	10000	880	528	8000	84
AB60S1200A	12	5000	1000	600	3900	87
AB60S1500A	15	4000	1000	600	3300	87
AB60S2400A	24	2500	1000	600	1500	87
AB60S4800A	48	1250	988	593	680	88

## Input Specifications

Parameter	Model	Min.	Typ.	Max.	Unit
AC Voltage Input Range	All Models	85	---	264	VAC
Input Frequency Range		47	---	440	Hz
DC Voltage Input Range		120	---	370	VDC
No-Load Power Consumption		---	0.5	---	W
Inrush Current (Cold Start at 25°C)	115VAC	---	---	30	A
	230VAC	---	---	60	A

## Output Specifications

Parameter	Conditions		Min.	Typ.	Max.	Unit
Output Voltage Accuracy			---	±1.0	±2.0	%
Line Regulation	Vin=Min. to Max.		---	±0.2	±1.0	%
Load Regulation	Iout=Min. to Max.		---	±0.5	±1.0	%
Min.Load	No minimum Load Requirement					
Ripple & Noise	0-20 MHz Bandwidth	(5.1VDC Output Models)	---	2.0	3.0	%V <sub>PP</sub> of Vo
		(Other Output Models)	---	1.0	1.5	%V <sub>PP</sub> of Vo
Over Voltage Protection	Zener diode clamp		---	120	---	% of Vo
Temperature Coefficient			---	±0.02	---	%/°C
Overshoot			---	---	5	%
Current Limitation	85VAC, Hiccup Mode, auto-recovery (long term overload condition may cause damage)		105	---	---	%Inom.
Short Circuit Protection	Hiccup mode, indefinite (automatic recovery)					

## General Specifications

Parameter	Conditions	Min.	Typ.	Max.	Unit
I/O Isolation Voltage (reinforced)		4000	---	---	VACrms
Leakage Current		---	80	---	μA
I/O Isolation Resistance	500 VDC	1000	---	---	MΩ
Switching Frequency		---	100	---	KHz
Hold-up Time	115VAC, 60Hz	---	20	---	ms
	230VAC, 50Hz	---	80	---	ms
MTBF (calculated)	MIL-HDBK-217F@25°C, Ground Benign	125,000	---	---	Hours
Protection Class II	According IEC/EN 60536				
Safety Approvals	IEC/EN 60950-1, 60601-1 3 <sup>rd</sup> , 2XMOPP cUL/UL 60950-1, 60601-1 3 <sup>rd</sup> , 2XMOPP, UL 508 listed				

## EMC Specifications

Parameter	Standards & Level	Performance
Conducted and radiated EMI	EN55011, EN55022, FCC part 15	Class B
ESD	EN61000-4-2 air ± 8kV , Contact ± 4kV	A
Radiated immunity	EN61000-4-3 10V/m	A
Fast transient	EN61000-4-4 ± 2kV	A
Surge	EN61000-4-5 ±1kV	A
Conducted immunity	EN61000-4-6 10Vrms	A
PFMF	EN61000-4-8 30A/m	A
Dips	EN61000-4-11 30% 10ms	A
Interruption	EN61000-4-11 >95% 5000ms	B

## Environmental Specifications

Parameter	Conditions	Min.	Max.
Temperature Range (operational)	Ambient	-40°C	+80°C
Power Derating	Above +60°C		2.3W / °C
Storage Temperature Range		-40°C	+95°C
Humidity (non condensing)		---	95% rel. H
Cooling	Free-Air convection		

## Notes

- 1 This product is not designed for use in critical life support systems, equipment used in hazardous environment, nuclear control systems or other such applications which necessitate specific safety and regulatory standards other the ones listed in this datasheet.
- 2 Specifications typical at Ta=+25°C, resistive load, 115VAC, 60Hz input voltage, after warm-up time rated output current unless otherwise noted.
- 3 Safety approvals cover frequency 47-63 Hz.
- 4 We recommend to protect the converter by a slow blow fuse in the input supply line.
- 5 Other input and output voltage may be available, please contact factory.
- 6 To order the module with chassis mount package, please add a **suffix C** (e.g. AB60S1500C).
- 7 To order the module in chassis mount with DIN-Rail kit, please add a **suffix D** (e.g. AB60S1500D).
- 8 That "natural convection" is about 20LFM but is not equal to still air (0 LFM).
- 9 Specifications are subject to change without notice.

## Package Specifications PCB Mounting

## Mechanical Dimensions

The drawing consists of two views: a Bottom View and a Side View.

**Bottom View:**

- Overall width: 67.5 [2.66] mm
- Overall height: 88.9 [3.50] mm
- Pin 6 is located 25.4 [1.00] mm from the top edge.
- Pin 4 is located 17.75 [0.70] mm from the top edge.
- Pin 2 is located 55.88 [2.20] mm from the bottom edge.
- Pin 1 is located 36.45 [1.44] mm from the bottom edge.
- Two mounting holes are located 17.00 [0.67] mm from the centerline.
- The mounting holes are labeled "Mounting M4 Thread".

**Side View:**

- Overall height: 81.3 [3.20] mm
- Pin diameter:  $\varnothing 1.0 \pm 0.04$  mm
- Pin 1 is located 6.0 [0.24] mm from the bottom edge.
- Pin 2 is located 34.2 [1.35] mm from the bottom edge.
- Pin 4 is located 0.7 [0.03] mm from the bottom edge.

## Pin Connections

Pin	Function
1	AC (N)
2	AC (L)
4	+Vout
6	-Vout


- ▶ All dimensions in mm (inches)
- ▶ Tolerance:  $\pm 1.0 (\pm 0.04)$
- ▶ Pin diameter  $\varnothing 1.0 \pm 0.1$   
( $0.04 \pm 0.004$ )

- ▶ All dimensions in mm (inches)
- ▶ Tolerance:  $\pm 1.0$  ( $\pm 0.04$ )
- ▶ Pin diameter  $\varnothing 1.0 \pm 0.1$  ( $0.04 \pm 0.004$ )

## Physical Characteristics

Case Size	: 88.9x67.5x34.2mm (3.50x2.66x1.35 inches)
Case Material	: Plastic resin (flammability to UL 94V-0 rated)
Pin Material	: Copper Alloy with Gold Plate Over Nickel Subplate
Weight	: 360g


## Package Specifications Chassis Mounting (order code suffix C)

Mechanical Dimensions		Connections	
 <p>Top View</p> <p>4x Ø3.5</p> <p>Indication LED</p> <p>POWER "GOOD" INDICATOR</p> <p>100.0 [3.94]</p> <p>112.0 [4.41]</p> <p>90.0 [3.54]</p> <p>11.0 [0.43]</p> <p>50.0 [1.97]</p> <p>67.8 [2.67]</p> <p>5.0 [0.20]</p> <p>16.8 [0.66]</p> <p>38.0 [1.50]</p>		Pi n	Function
		1	AC (N)
		2	AC (L)
		3	NC
		4	+Vout
		5	NC
		6	-Vout
		7	NC
NC: No Connection			
<p>► All dimensions in mm (inches)</p> <p>► Tolerance: <math>\pm 1.0</math> (<math>\pm 0.04</math>)</p>			

## Physical Characteristics

Case Size	: 112.0x67.8x38.0mm (4.41x2.67x1.50 inches)
Case Material	: Plastic resin (flammability to UL 94V-0 rated)
Weight	: 380g


## Package Specifications with DIN Rail Mounting Bracket (order code suffix D)

Mechanical Dimensions	
 <p>Top View</p> <p>4x Ø3.5</p> <p>Indication LED</p> <p>POWER "GOOD" INDICATOR</p> <p>100.0 [3.94]</p> <p>112.0 [4.41]</p> <p>90.0 [3.54]</p> <p>11.0 [0.43]</p> <p>50.0 [1.97]</p> <p>67.8 [2.67]</p> <p>5.0 [0.20]</p> <p>16.8 [0.66]</p> <p>38.0 [1.50]</p> <p>3.0 [0.12]</p> <p>11.0 [0.43]</p>	

## Physical Characteristics

Case Size	: 112.0x67.8x38.0mm (4.41x2.67x1.50 inches)
Case Material	: Plastic resin (flammability to UL 94V-0 rated)
Weight	: 433g

## DIN-Rail Mounting Bracket



## Part Numbering System

A	B	60	S	05	00	A
Product type	Family series	Watt	Number of Outputs	Output Voltage I	Output Voltage II	Option Code
AC/DC Power Module	Medical application	60 – 60W	S - Single	05 - 5.1V	00 - not applicable	A - PCB Mount
				12 - 12V		C - Chassis Mount
				15 - 15V		D - Din Rail Mount
				24 - 24V		
				48 - 48V		

### CONTACT: [www.deltaww.com/dcdc](http://www.deltaww.com/dcdc)

#### USA:

Telephone:  
East Coast: 978-656-3993  
West Coast: 510-668-5100  
Fax: (978) 656 3964  
Email: [DCDC@delta-corp.com](mailto:DCDC@delta-corp.com)

#### Europe:

Phone: +31-20-655-0967  
Fax: +31-20-655-0999  
Email: [DCDC@delta-es.com](mailto:DCDC@delta-es.com)

#### Asia & the rest of world:

Telephone: +886 3 4526107  
ext 6220~6224  
Fax: +886 3 4513485  
Email: [DCDC@delta.com.tw](mailto:DCDC@delta.com.tw)

## WARRANTY

Delta offers a three(3) years limited warranty. Complete warranty information is listed on our web site or is available upon request from Delta.

Information furnished by Delta is believed to be accurate and reliable. However, no responsibility is assumed by Delta for its use, nor for any infringements of patents or other rights of third parties, which may result from its use. No license is granted by implication or otherwise under any patent or patent rights of Delta. Delta reserves the right to revise these specifications at any time, without notice

# Mouser Electronics

Authorized Distributor

Click to View Pricing, Inventory, Delivery & Lifecycle Information:

## Delta Electronics:

<a href="#"><u>AB60S0500C</u></a>	<a href="#"><u>AB60S2400A</u></a>	<a href="#"><u>AB60S2400D</u></a>	<a href="#"><u>AB60S0500D</u></a>	<a href="#"><u>AB60S1200D</u></a>	<a href="#"><u>AB60S1200A</u></a>	<a href="#"><u>AB60S0500A</u></a>	<a href="#"><u>AB60S4800C</u></a>
<a href="#"><u>AB60S2400C</u></a>	<a href="#"><u>AB60S1500A</u></a>	<a href="#"><u>AB60S1500D</u></a>	<a href="#"><u>AB60S4800D</u></a>	<a href="#"><u>AB60S4800A</u></a>	<a href="#"><u>AB60S1500C</u></a>	<a href="#"><u>AB60S1200C</u></a>	