

DELTA PARTS NUMBERING SYSTEM

MODELS OTHER THAN POWER ENTRY MODULE TYPES AND P.C. BOARD MOUNTING TYPES

<u>03</u>	<u>GE</u>	<u>E</u>	<u>G3</u>	<u>V</u>	<u>-R</u>
					Option resistor Design sequence: (for cylinder types, the 8th digit designates the outside diameter; S- \varnothing 38mm; M- \varnothing 43mm; L- \varnothing 50mm)
					Input/Output connection: G = lugs; W = PVC wires; S = screws G5 = 5 lugs (6.3*0.8mm) W5 = 5 wires (UL 1015 AWG#18, 4" long)
					Case style: A- Small mounting ears 90 degrees from terminal sides B- Triangle mounting ears 90 degrees from terminal sides C- Triangle mounting ears on terminal sides D- IEC connector with mounting screws E- IEC connector package F- Cylinder types G- Two-hole mounting bars, 90 degrees from terminal sides N- IEC connector with snap-in type
Series: Electrical circuit, see specific catalog pages					
Current rating: AC rms e.g.: 03 amp					

POWER ENTRY MODULE TYPES

<u>06</u>	<u>AR</u>	<u>2</u>	<u>D</u>		
				Special design: A- with ground choke D- with double pole power switch for models AB, AK, AR series	
				Module construction: 1- IEC connector & fuse holder 2- IEC connector, fuse holder and power switch 3- IEC connector, fuse holder, power switch and voltage selector switch 4- IEC connector, fuse holder & voltage selector switch 5- For models other than CK, CR series; same construction as 4 but with voltage selector switch at front panel	
Series: Electric circuit, see specific catalog pages					
Current rating: AC rms e.g.: 06 amp					

PCB MOUNTING TYPES

<u>03</u>	<u>ME</u>	<u>3</u>	<u>A</u>	<u>-R</u>	
				Option resistor Special design: A: with ground choke	
				Design sequence	
Series: Electrical circuit, see specific catalog page					
Current rating: AC rms e.g. :03 amp					

DELTA PARTS NUMBERING SYSTEM

3-Phase Types

10

TD

S6

D

Current rating: AC rms
e.g.: 10 amp

Series:

- TD: used in "Δ" system
- TDH: used in "Δ" system
- TDR: used in "Δ" system, vertical style
- TDV: used in "Δ" system, vertical style
- TDS: used in "Δ" system, screw style
- TY: used in both "Δ" & "y" system
- TYS: used in "Δ" & "y" system, screw style
- TYT: used in "Δ" & "y" system terminal block style
- PT: P.C.B. Filter
- PY: P.C.B. Filter

Input/Output connection :

- G = lugs; W = PVC wires; S = screws; T = terminal blocks
- e.g.
- G6 = 6 lugs
- W6 = 6 wires
- T2: 2 terminal blocks
- TIW4: 1 terminal block / 4 wires

Special Design:

Dual: diff. and common choke



Mouser Electronics

Authorized Distributor

Click to View Pricing, Inventory, Delivery & Lifecycle Information:

[Delta Electronics:](#)

[20VBAS5](#) [03AK2D](#) [06BEEG3FM-R](#) [10SB3SM](#) [06EK3M](#) [20GENG3EM](#) [03BEEG3GM](#) [10BENG3GM](#)
[03GENG3EM-R](#) [03GEEG3EM](#) [10BEEG3GM-R](#) [06BEEG3GM-R](#) [06BENG3GM](#) [03SB3SM](#) [10EK3M](#) [02BEEG3FM-R](#)
[06SB3SM](#) [10BEEG3GM](#) [04BEEG3FM-R](#) [06BEEG3GM](#) [03BEEG3GM-R](#) [03EK3M](#) [06AE2](#) [06GENG3E-R\(H\)](#)
[03MK2](#) [03DPCG5CM](#)