

USB to RS-485 Miniature Converters

Models: BB-485USB9F-2W, BB-485USB9F-2W-LS,
BB-485USB9F-4W, BB-485USB9F-4W-LS

B+B SMARTWORX

Powered by

ADVANTECH

www.advantech-bb.com



PRODUCT FEATURES

- Connect RS-485 devices to your USB port
- Data rates: 921.6 kbps (RS-485); 12 Mbps (USB)
- Quick, convenient in-line installation
- USB port powered
- USB 2.0 (12 Mbps) compatible
- Small – fits easily into laptop bag; perfect for field service applications
- (1) USB cable included
- Locked Serial Number versions

Universal Serial Bus (USB) has become the connectivity workhorse of today's PCs, replacing the familiar serial port. However, many commercial and industrial devices still use the RS-485 interface. To connect these devices to modern PCs, you need a simple and reliable conversion solution. Models BB-485USB9F-2W-x and BB-485USB9F-4W-x offer this solution in a space saving, USB port powered package.

Simply install the drivers and plug the converter into an available USB port on your computer or USB hub. The device will show up as an additional COM port in the Windows Device Manager which is fully compatible with your Windows applications. Choose BB-485USB9F-2W-x for RS-485 2-wire applications or the BB-485USB9F-4W-x for RS-485 4-wire applications. A one meter USB cable is included. Locked serial number versions are also available.

ORDERING INFORMATION

MODEL NUMBER	DESCRIPTION
BB-485USB9F-2W	USB to RS-485 2-Wire Converter
BB-485USB9F-4W	USB to RS-485 4-Wire Converter
BB-485USB9F-2W-LS	USB to RS-485 2-Wire Converter (Locked Serial Number)
BB-485USB9F-4W-LS	USB to RS-485 4-Wire Converter (Locked Serial Number)

ACCESSORIES -

BB-USBAMBM-3F – 0.91 m (3 ft) USB Cable, Type A male, to Type B male (one included)
BB-USBAMBM-6F – 1.83 m (6 ft) USB Cable, Type A male, to Type B male



IN THE FIELD

Monitoring Laboratory Equipment

Industry: Industrial Automation
Product: USB Miniature Converter

Locked Serial Numbers Explained

We configure our single-port USB to serial converters in two ways. In standard format, each product has a unique serial number. "Locked serial" format uses the same serial number that is associated with a model type.

If your converter will always be used with the same computer, the standard serialized model is all you need. If the converter is shared among several computers, like field service laptops, the locked serial number model lets you plug and play without having to worry about matching the two.

DESCRIPTION	SERIALIZED	LOCKED SERIAL NUMBER
Every unit is assigned a unique COM port	✓	-
Same type model numbers shares the same COM port	-	✓
Ideal applications	Fixed Locations	Field Service

When ordering Locked Serial Number versions, add a "-LS" to the item number.
Serialized and Locked Serial Number versions available for the same price.

All product specifications are subject to change without notice.
485USB9F-2W-x_485USB9F-4W-x_3018ds

B+B SMARTWORX

Powered by

ADVANTECH

orders@advantech-bb.com
support@advantech-bb.com

Corporate Headquarters: 707 Dayton Road, PO Box 1040 Ottawa, IL 61350 USA 815-433-5100 Fax 433-5104
European Office: Westlink Commercial Park, Oranmore Co. Galway Ireland +353 91 792444 Fax +353 91 792445

USB to RS-485 Miniature Converters

Models: BB-485USB9F-2W, BB-485USB9F-2W-LS,
BB-485USB9F-4W, BB-485USB9F-4W-LS




SPECIFICATIONS

SERIAL TECHNOLOGY	
RS-485 2-Wire	Data A(-), Data B(+), Ground
RS-485 4-Wire	TDA(-), TDB(+), RDA(-), RDB(+), Ground
Connector	DB9 Female
Data Rate	Up to 921.6 Kbps
USB TECHNOLOGY	
Connector	USB Type B Female
Standard	2.0 (Backward Compatible)
Data Rate	12 Mbps
POWER	
Source	USB Port
Input Voltage	5 VDC
Consumption	~ 0.5 W (Low power device, draws less than 100 mA)
SOFTWARE	
Driver CD	Windows XP, 7 (32/64 bit), 8 (32/64 bit), 8.1 (32/64), 10 (32/64)
MECHANICAL	
Dimensions	5.8 x 3.2 x 1.6 cm (2.3 x 1.3 x 0.6 in)
Enclosure	In-line mounted, plastic
Weight	04.3 g (0.23 lb) with USB cable
ENVIRONMENTAL	
Operating Temperature	0 to +70 °C (+32 to +158 °F)
Storage Temperature	-40 to +85 °C (-40 to +185 °F)
Operating Humidity	0 to 95 % (non-condensing)
MEANTIME BEFORE FAILURE (MTBF)	
MTBF 2-Wire	2130833 hours
MTBF 4-Wire	1869313 hours
MTBF Method	Parts Count Reliability Prediction

APPROVALS, DIRECTIVES, STANDARDS


Approvals	FCC, CE	
EU	2014/30/EU	Electromagnetic Compatibility Directive
	2011/65/EU	Reduction of Hazardous Substances Directive
EMC	EN 55022:2010 + AC	Information Technology Equipment - Radio Disturbance Characteristics - Limits and Methods of Measurement
	EN 61000-6-1	Generic Immunity Standard for Residential, Commercial and Light-Industrial Environments

PINOUT: DB9 FEMALE CONNECTOR



PIN	485USB9F-2W	485USB9F-4W
1	Not Used	Not Used
2	Data A(-)	RDA(-)
3	Data B(+)	TDB(+)
4	Ground	Ground
5	Not Used	Not Used
6	Ground	Ground
7	Data B(+)	RDB(+)
8	Data A(-)	TDA(-)
9	Not Used	Not Used

MECHANICAL DIAGRAM



Mouser Electronics

Authorized Distributor

Click to View Pricing, Inventory, Delivery & Lifecycle Information:

[Advantech:](#)

[BB-485USB9F-2W](#)