

ADAM-6266

4-ch Relay Output Modbus TCP Module with 4-ch DI



Main Features

NEW

- 4-ch Relay Output, 4-ch DI, 2-port Ethernet
- Daisy chain connection with auto-bypass protection
- Remote monitoring and control with mobile devices
- Group configuration capability for multiple module setup
- Flexible user-defined Modbus address
- Intelligent control ability by Peer-to-Peer and GCL function
- Multiple protocol support: Modbus TCP, TCP/IP, UDP, HTTP, DHCP
- Web language support: XML, HTML 5, Java Script

Introduction

In order to fulfill ideal remote DAQ devices in IoT world, Advantech releases ADAM-6200 series, a new selection of Ethernet I/O family comprised of analog I/O, digital I/O and relay modules. ADAM-6200 series module possesses plenty of advanced features whatever the evolution of hardware design and what's worth expecting for user is a variety of useful software functions to make it effective in the application field. With new design and strong capabilities, ADAM-6200 can be a well-integrated I/O solution in Ethernet control system.

Features

Daisy Chain Networking and Auto-Bypass Protection

Daisy chain connectivity offers flexible cabling and space saving capabilities. With Ethernet auto-bypass function supported, it prevents accidental power failure if one of the module's unexpectedly shuts down.



Group Configuration Capability for Multiple Module Setup

To aid configuration and save time, engineers can configure and upgrade the firmware of multiple ADAM-6200s simultaneously.



Remote Monitoring and Control with Smart Phone

With support for HTML5, the ADAM-6200 can be monitored and controlled from any browser on mobile devices whilst in the field and when the engineer is connected to their network.




Peer-to-Peer

Modules will actively update the input channel status to specific output channels. Without dealing with the trouble of long distance wiring, users can define the mapping between a pair of modules.




Graphic Condition Logic

Users can define the control logic rules through graphical configuration Utility, and download defined logic rules to specific ADAM module. Then, it will execute the logic rules automatically just like a standalone controller.



Architecture



Specifications

Relay Output

- Channels 4 Form C
- Contact Rating 250 V_{AC} @ 5A
30 V_{DC} @ 5A
- Max. Switching Voltage 400 V_{AC}
300 V_{DC}
- Breakdown Voltage 500 V_{AC} (50/60Hz)
- Max. Breakdown Capacity 1250 VA
- Frequency of Operation 360 Operations/Hour with Load
72,000 Operations/Hour without Load
- Set/Reset Time 8 ms/8 ms
- Mechanical Endurance > 15 x 10⁶ Operations
- Isolation between Contact 1000 V_{ms}
- Insulation Resistance > 10 GΩ @ 500 V_{DC}

Digital Input

- Channels 4
- Dry Contact Logic 0: Open
Logic 1: Closed to DI COM
- Wet Contact Logic 0: 0 ~ 3 V_{DC} or 0 ~ -3 V_{DC}
Logic 1: 10 ~ 30 V_{DC} or -10 ~ -30 V_{DC}
(Dry/Wet Contact Decided by Switch)
- Input Impedance 5.2 kW (Wet Contact)
- Transition Time 0.2 ms
- Frequency Input Range 0.1 ~ 3 kHz
- Counter Input 3 kHz (32 bit + 1 bit Overflow)
- Keep/Discard Counter Value when power off
- Supports Inverted DI Status

General

- Ethernet 2-port 10/100 Base-TX (for Daisy Chain)
- LED Indication 4 RL + 4 DI
- Protocol Modbus/TCP, TCP/IP, UDP, HTTP, DHCP
- Connector Plug-in 5P/15P Screw Terminal Blocks
- Power Input 10 ~ 30 V_{DC} (24 V_{DC} Standard)
- Watchdog Timer System (1.6 Seconds)
Communication (Programmable)
- Protection Built-in TVS/ESD Protection
Power Reversal Protection
Over Voltage Protection: +/- 35V_{DC}
Isolation Protection: 2500 V_{DC}
- Power Consumption 4.2 W @ 24 V_{DC}
- Dimensions (W x H x D) 70 x 122 x 27 mm
- Enclosure PC
- Mounting DIN 35 Rail, Stack, Wall


Software

- .NET Class Library (SDK) Windows and Windows CE Class Library, VB and VC#
Sample Code for I/O Reading or Configuration and Communication
- Adam/Apax .NET Utility Network Setting, I/O Configuration, Data Stream, P2P, GCL Configuration

Environment

- Operating Temperature -10 ~ 70°C (14 ~ 158°F)
- Storage Temperature -20 ~ 80°C (-4 ~ 176°F)
- Operating Humidity 20 ~ 95% RH (non-condensing)
- Storage Humidity 0 ~ 95% RH (non-condensing)

Pin Assignment



Ordering Information

- ADAM-6266 4-ch Relay Output Modbus TCP Module with 4-ch DI

Accessories


- PWR-242 DIN-rail Power Supply (2.1A Output Current)
- PWR-243 Panel Mount Power Supply (3A Output Current)
- PWR-244 Panel Mount Power Supply (4.2A Output Current)

Software

- PCLS-ADAMVIEW32 ADAMView Data Acquisition Software
- PCLS-OPC/MTP30 OPC Server for Modbus/TCP Protocol

Dimensions

Unit: mm




Front View



Side View



DIN-Rail Mounting Adapter



Wall Mounting Bracket

Mouser Electronics

Authorized Distributor

Click to View Pricing, Inventory, Delivery & Lifecycle Information:

[Advantech:](#)

[ADAM-6266-AE](#)