

# Dual Band (2.4 GHz, 5 GHz) Wi-Fi Ethernet Bridge/Router, Serial Server

AirborneM2M™ Industrial BB-ABDN-xx-IN5xx0 series

ADVANTECH

[www.advantech.com](http://www.advantech.com)



## PRODUCT FEATURES

- RS-232/422/485 or 10/100 Mbps Ethernet to 802.11a/b/g/n (2.4, 5 GHz)
- Advanced Enterprise class wireless security
- One or two serial ports, one Ethernet port
- Wide operating temperature: -40 to +85 °C
- 5 to 36 VDC power required, sold separately. Power input via terminal block or DC jack

AirborneM2M™ Industrial Ethernet Bridge/Router and Wireless Device Serial Servers are built for networking equipment in a wide array of machine-to-machine (M2M) applications. AirborneM2M series features industrial strength packaging and supports a wide temperature rating (-40 to +85 °C) to withstand challenging M2M environments. Available in both single and dual serial port models or a single Ethernet port model.

These AirborneM2M products establish wireless connections over both 2.4 GHz and 5 GHz bands. Whenever the 2.4 GHz airspace is overcrowded with competing wireless transmission, AirborneM2M products can be switched over to 5 GHz band to keep data flowing.

## Powering Options

External 5-36 VDC power source required. USA power cord included, other cords sold separately.

## ORDERING INFORMATION

MODEL NUMBER	DESCRIPTION	PoE Power-over-Ethernet
BB-ABDN-ER-IN5010	Ethernet Bridge/Router – Industrial Wireless, Dual Band (2.4 / 5 GHz)	no
BB-ABDN-SE-IN5410	Serial Device Server – Industrial Wireless, Dual Band (2.4 / 5 GHz) - with one RS-232/422/485 port	no
BB-ABDN-SE-IN5420	Serial Device Server – Industrial Wireless, Dual Band (2.4 / 5 GHz) - with two RS-232/422/485 ports	no

Available in: North America, European Union (EU), Japan

## ACCESSORIES - sold separately

BB-MDR-20-24 – Power supply, 24VDC, 120-240 VAC, 50/60 Hz, 1.0A DIN rail

BB-PS-WDS – Power supply, 5VDC, 120-240 VAC, 50/60 Hz, 3A, 15W, barrel connector  
(Note: includes USA cord; other cords sold separately.)

BB-DRAD35 – 35mm DIN rail adapter kit (pair of 2)

BB-ACH2-AT-DP003-G – Antenna replacement, Wi-Fi 2.4/5GHz, 3.8/5.5dBi, RP-SMA

BB-TBKT7 – Terminal block replacement, 2-position, 3.5mm, screw, Euro RA, plug

All product specifications are subject to change without notice.  
BB-ABDN-er-se-IN5xx0\_EthBridgeRouter-SerSvr\_3920ds

ADVANTECH

Advantech B+B SmartWorx, 707 Dayton Road, PO Box 1040 Ottawa, IL 61350 USA 1 (800)346-3119/Toll Free | [orders@advantech-bb.com](mailto:orders@advantech-bb.com) | [support@advantech-bb.com](mailto:support@advantech-bb.com)

# Dual Band (2.4 GHz, 5 GHz) Wi-Fi Ethernet Bridge/Router, Serial Server

AirborneM2M™ Industrial BB-ABDN-xx-IN5xx0 series



## SPECIFICATIONS

TECHNOLOGY	
Wireless Technology	IEEE 802.11 a/b/g/n, Wi-Fi Compliant
Wired Interface	2 ports, RS-232/422/485, (RS-232/422 4-wire or RS-485 2-wire) 10/100 Ethernet port (Bridge, Router (NAT3) Modes) Software selectable
Frequency	2.4~2.4835 GHz (US/Canada/Europe) 2.4~2.497 GHz (Japan) 5.150 ~ 5.350 GHz 5.725 ~ 5.825 GHz
Modulation Technology	DSSS, CCK, OFDM
Modulation Type	DBPSK, DQPSK, CCK, BPSK, QPSK, 16QAM, 64QAM
Network Access Modes	Infrastructure (Client), Ad Hoc
	US/Canada: 11 Channels 802.11b/g
	13 Channels 802.11a
	Europe: 13 Channels 802.11b/g
	19 Channels 802.11a
	France: 4 Channels 802.11b/g
	Japan: 14 Channels 802.11b
Wireless Data Rates	802.11a/g = 54, 48, 36, 24, 18, 12, 9, 6 Mbps
	802.11b = 11, 5.5, 2, 1 Mbps
	802.11n = 65, 58.5, 42, 39, 26, 19.5, 13, 6.5 Mbps
Network Protocols	TCP/IP, ARP, ICMP, DHCP, DNS, UDP, TFTP, UDP, PING, HTTP, FTP
Receive Sensitivity – 802.11 b/g	54Mb/s = -72 dBm
	36Mb/s = -78 dBm
	18Mb/s = -84 dBm
Receive Sensitivity – 802.11 a	6Mb/s = -89 dBm
	11Mb/s = -86 dBm
	1Mb/s = -92 dBm
Wireless Security	54Mb/s = -74 dBm
	36Mb/s = -80 dBm
	6Mb/s = -90 dBm
Secure Communications	- Open, WEP 64 & 128 bit, WPA-PSK (TKIP), WPA2-PSK (AES), 802.1x (EAP), WPA-Enterprise, WPA2-Enterprise, EAP-TLS/MSCHAPv2, EAP-TTLS/MSCHAPv2, EAP-TTLS (MD5), EAP-PEAPv0/MSCHAPv2, LEAP
	- Zero host security footprint
	- Advanced certificate storage and management
Transmit Power	SSH and SSL tunneling.
	Encrypted configuration.
	802.11b = 15 dBm (31.6mW)
	802.11g = 12.6dBm (18.12mW)
	802.11a = 17 dBm (50.1mW)

POWER	
Input Voltage	5-36VDC +/-5%, 500mA (maximum)
Power Connection	2-position terminal block, 2.1mm barrel jack
Power Use	2.5W at 5VDC
Supply In-rush Current	3000 mA (maximum) for 20ms
Source (all models)	External, required (USA cord included, other cords sold separately)
LED INDICATORS	
4 LEDs	COMM, LINK, POWER, POST (Power on Self Test)
ENVIRONMENTAL	
Operating Temperature	-40 to +85 °C
Storage Temperature	-40 to +85 °C
Operating Humidity	5 to 95%, non-condensing
MECHANICAL	
Antenna	RP-SMA Omni-directional 5.5 dBi 2.4GHz / 5GHz Antenna
Enclosure	Metal enclosure
Ingress Protection Rating	IP30
Mounting	Panel mount, optional DIN rail brackets
Dimensions	12.1 x 12.0 x 2.9 cm (4.9 x 4.7 x 1.2 in)
MEANTIME BETWEEN FAILURES (MTBF)	
MTBF	BB-ABDN-ER-IN5010 = 392467 hours BB-ABDN-SE-IN5410 = 360740 hours BB-ABDN-SE-IN5420 = 350412 hours
MTBF Calc. Method	MIL 217F (Parts Count Reliability Prediction)
APPROVALS, DIRECTIVES & STANDARDS	
North America	FCC Title 47 Part 15 Class B Sub C Intentional Radiator
CE - Directives	2014/35/EU - Low Voltage Directive 2014/53/EU - Radio Equipment Directive (RED) Hereby, Advantech B+B SmartWorx declares that the radio equipment type Wi-Fi Ethernet Bridge/Router or Serial Server is in compliance with Directive 2014/53/EU. The full text of the EU declaration of conformity is available at the following internet address: <a href="http://www.advantech-bb.com">www.advantech-bb.com</a> 2011/65/EU - amended by (EU) 2015/863 Reduction of Hazardous Substances Directive (RoHS) 2012/19/EU - Waste Electrical & Electronic Equipment Directive (WEEE)
CE - Standards	<b>EMC:</b> ETSI EN 300 328 v2.1.1 - EMC & Radio Spectrum Matters (ERM) Wideband Transmission Systems - 2.4 GHz ISM Band ETSI EN 301 893 v2.1.1 - EMC & Radio Spectrum Matters (ERM) Wideband Transmission Systems - 5 GHz ISM Band ETSI EN 301 489-1 v2.1.1 - Applied in accordance with the specific requirements of: ETSI EN 301 489-17 v3.1.1 - EMC & Radio Spectrum Matters (ERM) Broadband Data Systems EN 55032+AC, Class A - Information Technology Equipment (ITE) - RF Emissions EN 55024 - Information Technology Equipment (ITE) - Immunity Characteristics - Limits and Methods of Measurement <b>Safety:</b> EN 60950-1 + A1 + A11 + A12 + A2 - Information Technology Equipment - Safety - Part 1 - General Requirements <b>RF Exposure:</b> EN 62311 - Assessment of electronic and electrical equipment related to human exposure restrictions for EM fields (0 Hz to 300 GHz)

# Mouser Electronics

Authorized Distributor

Click to View Pricing, Inventory, Delivery & Lifecycle Information:

[B+B SmartWorx:](#)

[BB-ABDN-SE-IN5420](#)