
# **PCL-722**

## 144-ch Digital I/O ISA Card



# **Specifications**

#### **Digital Input**

- Channels
- Compatibility
- Input Voltage
- Interrupt Capable Ch.

#### **Digital Output**

- Channels
- Compatibility
- Output Voltage Port A, B

Port C

 Output Capability Port A, B

Port C

#### General

- Bus Type
- Power Consumption
- Operating Temperature  $0 \sim 60^{\circ} \text{ C} (32 \sim 140^{\circ} \text{ F})$
- -20 ~ 70° C (-4 ~ 158° F) Storage Temperature
- Operating Humidity
- I/O Connectors
- 5 ~ 95% RH, non-condensing (refer to IEC 68-2-3) 6 x 50-pin box header
- Dimensions (L x H) 334 x 100 mm (13.2" x 3.9")

### **Ordering Information**

PCL-722

**Features** 

•

Emulates 8255 PPI mode 0

Interrupt handling capability

Output status readback

- PCL-10150-1.2
- PCLD-782B
- PCLD-785B
- PCLD-7216
- PCLD-885
- ADAM-3950

#### **Pin Assignments**

PC 7	1	2	GND
PC 6	3	4	GND
PC 5	5	6	GND
PC 4	7	8	GND
PC 3	9	10	GND
PC 2	11	12	GND
PC 1	13	14	GND
PC 0	15	16	GND
PB 7	17	18	GND
PB 6	19	20	GND
PB 5	21	22	GND
PB 4	23	24	GND
PB 3	25	26	GND
PB 2	27	28	GND
PB 1	29	30	GND
PB 0	31	32	GND
PA 7	33	34	GND
PA 6	35	36	GND
PA 5	37	38	GND
PA 4	39	40	GND
PA 3	41	42	GND
PA 2	43	44	GND
PA 1	45	46	GND
PA 0	47	48	GND
+5V	49	50	GND
			1

## RoHS COMPLIANT 2002/56/EC CE

- - 50-pin Flat Cable, 1.2 m
  - 24-ch IDI Board w/ 20-pin & 50-pin Flat Cables 24-ch Relay Board w/ 20-pin & 50-pin Flat Cables

Buffered circuits for higher driving capacity than the 8255

Pin compatible with Opto-22 I/O module racks

- - 16-ch SSR I/O Module Carrier Board
    - 16-ch Power Relay Board w/ 20p & 50p Flat Cables
    - 50-pin DIN-rail Flat Cable Wiring Board

144-ch Digital I/O ISA Card

144 (24 channels x 6 ports) shared with output

Bits 0 and 3 of Port C can generate an interrupt to IRQ

144 (24 channels x 6 ports) shared with input 5 V/TTL Logic 0: 0.5 V max. Logic 1: 2.4 V min. Logic 0: 0.4 V max.

5 V/TTL

Logic 0: 0.8 V max.

Logic 1: 2.0 V min.

2, 3, 4, 5, 6 or 7

Logic 1: 2.0 V min. Sink: 12 mA

> Source: 8 mA Sink: 24 mA Source: 15 mA

Typical: 5 V @ 1.3 A Max.: 5 V @ 1.8 A

ISA

# **Mouser Electronics**

Authorized Distributor

Click to View Pricing, Inventory, Delivery & Lifecycle Information:

Advantech: PCL-722-BE