SKY-4120B

2U 24-Bay JBOD Enclosure for High-Availability Applications



Features


- Supports 24 x hot-swappable 2.5" SAS (12/6 Gb) drives
- SES enclosure management and smart fan control
- 3 x Mini SAS HD (SFF-8644) per expander module (2 x for input and 1 x for output)
- Storage daisy chain support for up to 72 drives
- High-efficiency (80PLUS) redundant power supply

Specifications


	Form Factor	011.04 hovo	
System		2U 24 bays	
	Number of Drives	24 x 2.5" bays	
	Drive Type	SAS 12/6 Gb only	
	SAS Expansion Port	3 x Mini SAS HD (SFF-8644) per expander module	
	Cooling	2 x (1+1) 6038 easy-swap fans with smart fan control	
Power Supply	Power Output	550W 1+1 redundant power	
	Input Range	100 ~ 240V _{AC}	
Mechanical	Dimensions (W x H x D)	438 x 88.4 x 502 mm (19.7" x 17.2" x 3.4") (without handle ears)	
	Weight	20 kg (without hard drives)	
Environment		Operating	Non-operating
	Temperature	0 ~ 40 °C (32 ~ 104 °F)	-40 ~ 60 °C (-40 ~ 140 °F)
	Humidity	95% @ 40 °C, non-condensing	95% @ 60 °C, non-condensing
	Vibration (5 ~ 500Hz)	0.25Grms	2G
	Shock	10G @11 ms duration, half sine wave	
Miscellaneous	LED Indicators	System power, system alert, location, controller fan, controller temperature, controller ready	

C€ FCC

Front View




Rear View



All product specifications are subject to change without notice.

SKY-4120B



Ordering Information

Part NumberDescriptionSKY-4120B-R5A1E2U 24-bay dual controller JBOD enclosure

Packing List

Part Number	Description	Quantity
9680017208	22" slide rail kit	1

Optional Accessories

Part Number	Description
1700025067-01	mSAS HD (8644) to mSAS HD, 1.5m
1700025066-01	mSAS (8088) to mSAS HD, 1.5m

Mouser Electronics

Authorized Distributor

Click to View Pricing, Inventory, Delivery & Lifecycle Information:

Advantech: SKY-4120B-R5A1E