# WebAccess/SCADA



# **Features**

- Enables 100% web-based remote engineering, monitoring, and control •
- Driver support for major PLCs, PACs, I/O modules, CNCs, network switches, and computer platforms

**Browser-Based SCADA Software** 

- Supports standard protocols including Modbus, OPC UA, OPC DA, Ethernet/ IP, DNP3, SNMP, and BACnet
- WebAcccess/Dashboard 2.0 HTML5-based GUI for cross-browser, crossplatform data analysis; Widget Builder for creating custom widgets; and access to external databases and web service interfaces for data acquisition from third-party software systems
- Provides WebAccess APP for remote monitoring/control and alarm push notification for Android/iOS mobile devices
- Easily integrated with third-party software (e.g., MES and ERP) via open interface web services (RESTful API and SignalR), widget interfaces, and WebAccess APIs
- Flexible database restore mode for automatic data access with improved query speeds
- Soft license online authentication

# Introduction

Advantech WebAccess/SCADA is a 100% web-based SCADA software solution/IIoT platform with open interfaces for developing IoT applications aimed at various vertical markets. It also acts as a gateway for collecting data from ground equipment and transferring the data to cloud applications via MQTT publish/subscribe. In addition to traditional SCADA functions. WebAccess/SCADA features an HTML5-based intelligent dashboard that enables cross-platform, cross-browser data analysis.

The basic components of WebAccess/SCADA are as follows:

- 1. Project Node: This is the project development platform. It also acts as a web server for all clients to connect to development projects, thus facilitating remote monitoring and system control. All system configuration settings, project database files, and graphics are stored in this node.
- 2. SCADA Node: With various built-in device drivers, this node enables real-time communication with and control over automation equipment via serial, Ethernet, or proprietary communication protocols. It also provides real-time data access for all remote clients.
- 3. ViewDAQ Client: Through Microsoft Internet Explorer's ActiveX control. ViewDAQ Client monitors and controls the SCADA node. Clients must first connect to the project node to obtain the SCADA node address before they can communicate directly with the SCADA node. Data can be visualized in real time as dynamic graphics, presenting historical trends and alarm information for the user. ViewDAQ Client can be used to acknowledge alarms and adjust set-point data, status data, and other information.
- 4. Dashboard Client: This enables users to access the dashboard server via any browser on any platform (e.g., computer, pad, or smartphone) with iOS, Android, or Windows.
- 5. WebAccess APP: This provides a new interface for displaying usage information. Connecting to the WebAccess server enables users to perform remote monitoring of control points and alarms while visualizing trends and communication statuses via the dashboard. Additionally, it provides push notifications for mobile devices.

# **Feature Details**

# **100% Web-Based Architecture**

WebAccess/SCADA is a 100% web-based SCADA software application. As Advantech's core IoT application platform, it provides a unique environment for development and remote maintenance, allowing access to and manipulation of data stored on a central server. This enables the configuring, changing/updating, and remote monitoring of equipment, projects, and systems worldwide via a standard web browser, thus saving time that would otherwise be required for system development. WebAccess/SCADA Professional comes with 1,024 clients at no extra cost, which, compared to other similar products, can save a considerable amount of money for system integrators. For edge computing application, WebAccess/SCADA also publishes real-time and historical data to private/ public cloud platforms via MQTT, thus providing a database for big data intended for use in cloud applications.

# WebAccess/Dashboard 2.0

With the functions of the original Dashboard, WebAccess/Dashboard 2.0 uses web services based on Node.js® as the underlying data transport layer, enabling immediate data transfer to clients. In addition to obtaining data from WebAccess, the dashboard can also access data on standard SQL database management systems (SQL Server, MYSQL, ORACLE), and the web service interface can be used to acquire data from other software systems. WebAccess/Dashboard 2.0 also comes with a dashboard editor for creating custom information pages that display analysis charts and diagrams. In addition to more than 40 built-in widgets, Dashboard 2.0 comes with Widget Builder, a widget development tool that aids users in creating unique widgets. Once dashboard screens have been created, users can conveniently utilize the dashboard viewer to access data from different devices via different browsers.

#### AD\ANTECH WISE-PaaS/IIoT Software and Solutions

#### All product specifications are subject to change without notice.

Last undated: 2-Feb-2018

# WebAccess APP

WebAccess APP is the new mobile app for WebAccess/SCADA 8.3 and above, with support for iOS 9 and Android 4.4 and above. With Node.js as the underlying data transport layer, data can be immediately transferred to phones.

# **Open Interface**

WebAccess/SCADA offers several types of interfaces, including RESTful API and SignalR, for various applications. First, a web service interface allows partners to integrate WebAccess data into their apps or application systems. Second, a pluggable widget interface enables programmers to develop widgets and run Dashboard 2.0. Finally, WebAccess API provides a DLL interface for programmers to access the WebAccess platform and develop related Windows applications. By supporting these interfaces, WebAccess serves as a platform for developing IoT applications in various vertical markets.

# **Supports Multiple Drivers**

WebAccess/SCADA supports hundreds of devices. In addition to supporting Advantech I/O devices and controllers, it supports all major programmable logic controllers, controllers, and I/O devices by manufacturers such as Allen Bradley, Siemens, LonWorks, Mitsubushi, Beckhoff, and Yokogawa. For vertical market applications, WebAccess/SCADA supports the DNP 3.0 protocol, which was developed for the power and energy industry. It also supports standard protocols such as Modbus, OPC DA, and OPC UA, and can be easily integrated with other SCADA software. All of these device drivers are integrated into WebAccess/ SCADA at no extra cost. Please refer to the driver list for information on supported devices.

# WebAccess/SCADA



## **Integrated with Google Maps and GPS Tracking**

WebAccess/SCADA integrates real-time data from physical sites with Google Maps and GPS location tracking, enabling users to remotely monitor building energy consumption, field production rates, highway traffic flow, and alarm status information. By right-clicking on Google Maps or entering the coordinates of a target location, users can create markers for up to three sites for tracking real-time data. This functionality can then be integrated with GPS modules to track marker locations via Google Maps, enabling the data to be shared with relevant in-vehicle systems.

## WebAccess Express - The Auto-Configuration Tool

Advantech's WebAccess Express is an automated graphical application that gives remote control of device information with a single click. It can automatically discover ADAM and EKI modules connected via a network or serial port, and it can upload real-time data to a database through preconfigured monitoring interfaces. The tool also provides remote monitoring functions by allowing for data exchange/communication with SNMP, DiagAnywhere Server, or SUSI 4.0 APIs, and it allows users to check the CPU health, memory, temperature, and voltage of target machines. Integrating SNMP, DiagAnywhere, and SUSI API drivers means that WebAccess/SCADA can be configured to issue an alarm when abnormal or suspicious data are detected.

#### Integrated with WISE-PaaS/VideoCMS

WebAccess/SCADA is integrated with WISE-PaaS/VideoCMS to provide a comprehensive video management solution that supports real-time monitoring and video playback. With this intelligent video surveillance system, events can be displayed as alarms and the corresponding video can be played back accordingly.

# Integrated with WebAccess/NMS

WebAccess/NMS is an HTML5-based network device management system that can be easily integrated with a web interface. Additionally, with WebAccess/SCADA graphics, users can examine event logs and monitor the real-time status of network devices in the network topology.

#### Integrated with WISE-PaaS/RMM

Previously, WebAccess/SCADA supported only sensor and device monitoring. Now, with the integration of WISE-PaaS/RMM, it also provides support for monitoring of the status of equipment, such as the CPU temperature, CPU usage, and board temperature, thereby enabling remote equipment monitoring.

## **Powerful Excel Reports**

For self-defined reporting, WebAccess/SCADA provides a function for exporting reports to Microsoft Excel. Users can build self-defined Excel templates for automatically generating on-demand or periodic reports that can be emailed to users in .pdf or .csv format. Additionally, because the Excel report function is web-based, this means that reports can be generated and accessed via a web browser from any location. However, users will need to have purchased a Microsoft Excel license.

#### **Open Data Connectivity**

For integration with third-party software, WebAccess/SCADA supports OPC UA/DA, DDE, Modbus, and BACnet server/client for real-time online data exchanges. Through the ODBC interface, WebAccess/SCADA can restore historical data in Microsoft SQL Server, Oracle, MySQL, and Microsoft Access for offline data sharing with MES or ERP systems.

#### **Real-Time Database**

The WebAccess/SCADA Real-Time Database (RTDB) was designed to meet industrial needs for high-speed, large-volume data access. The RTDB's fully integrated design means that users do not need to learn how to operate the database. Instead, users can enable RTDB use on the WebAccess configuration page for the WebAccess SCADA node to conduct data processing (simultaneous collection and retrieval) at a scale of millions of records per second. Moreover, the RTDB maintenance feature automatically archives and deletes obsolete data.

# **Multitouch Gesture Support**

WebAccess/SCADA supports multitouch operation and various preset gestures, such as flick for page turning and zoom in/out, in addition to two-handed operation. This more intuitive handling style maximizes operating safety, increases usability, and reduces training time. Furthermore, WebAccess/SCADA also supports multipoint tap/grab/spread gestures to initiate predefined actions.

## **Redundant SCADA Nodes, COM Ports, and Devices**

Advantech's WebAccess/SCADA ensures continuous reliable communication with automation equipment. The WebAccess backup node activates when the primary node is down. WebAccess/SCADA device drivers are designed to communicate with backup ports and devices whenever the primary connection is lost and to automatically restore to the primary connection when it becomes available.

# **Software Specifications**

75/150/300/600/1500/5000/20K/Unlimited

75/150/300/600/1500/5000/20K/Unlimited

Supports over 450 types of PLCs and RTUs

Unlimited (subject to HDD size)

1,024 (free)

4,000

Yes

Yes

Yes

Yes

Yes

Yes

Yes

Yes Yes

#### Advantech WebAccess Professional

- Number of I/O Tags
- Number of Internal Tags
- Number of Web Clients
- Number of Drivers

#### Graphics

- Number of Graphic Pages
- Variables Per Graphic Pages
- . **Built-in Gallery**
- Multi-Touch Gesture

#### **HTML5** Dashboard

## Cross Browser and Platform

- **Built-in Widgets**
- **Open Widget Interface**
- Widget Builder

#### **Network Architecture**

•	SCADA Node Redundancy	
	Device Redundancy	

•	Super SCADA with	
	Breakpoint Resume	

#### Alarm and Trend Log

<ul> <li>Number of Alarm Logs</li> </ul>	30,000
Number of Action Logs	30,000
Number of Data Logging	Number of I/O tags x 2
<ul> <li>Alarm Groups per SCADA</li> </ul>	9,999

# **Ordering Information**

## **Professional Version with USB Key**

	WA-P83-U075E WA-P83-U150E	WebAccess/SCADA 8.3 Professional with 75 Tags WebAccess/SCADA 8.3 Professional with 150 Tags
	WA-P83-U300E	WebAccess/SCADA 8.3 Professional with 300 Tags
•	WA-P83-U600E	WebAccess/SCADA 8.3 Professional with 600 Tags
•	WA-P83-U15HE	WebAccess/SCADA 8.3 Professional with 1,500 Tags
•	WA-P83-U50HE	WebAccess/SCADA 8.3 Professional with 5,000 Tags
	WA-P83-U20KE	WebAccess/SCADA 8.3 Professional with 20,000 Tags
•	WA-P83-U64KE	WebAccess/SCADA 8.3 Professional with Unlimited Tags

# Version Upgrade\*\*

• WA-X83-U000E WebAccess/SCADA Professional Version Upgrade to 8.3 \*Upgrade WebAccess from 7.x to 8.3. Upgrade from 8.x to 8.3 is free of charge.

# **Minimum Requirements**

# **Project Node/SCADA Node**

<ul> <li>Operating System</li> </ul>	Windows XP (SCADA node only), Windows 7 SP1, Windows
	8.1, Windows Server 2008 R2, Windows 10 (does not support
	Home or Home Premium), IIS 7.5, and NET Framework 4.5
<ul> <li>Hardware</li> </ul>	Intel <sup>®</sup> Atom <sup>™</sup> /Celeron <sup>®</sup> dual-core processor with 4 GB RAM
	and 200 GB HDD space
Display Resolution	1024 x 768 (lower resolutions also supported)
	Lower resolutions also supported
USB	USB port for license hard key on the SCADA node
Network Environment	SCADA node must remain connected to the Internet when

using a soft key

#### **Open Connectivity**

- **OPC DA/UA Server/Client** .
- . **Modbus Server** Yes

SQL Server/Oracle/MySQL/Microsoft Access

TclScript/VBScript/JScript (can be encrypted)

Yes, conforms to 21 CFR Part 11

**BACnet Server** Yes **DDE Server** Yes

## **Open Interface**

- Windows API Yes
- RESTful API Yes SignalR Yes

# Web-enabled Integration

- Video **Google Maps and GPS**
- Location Tracking

# Report

- Web-Based Report
- Excel Report
- Send Email by PDF or Excel Yes

# **Others**

- Database •
- Script Language
- Supports IPv6 .
- WebAccess APP • .
- **Electronic Signature** Scheduler
- . Receipt

## **Professional Version with Soft Key**

	WA-P83-N075E	WebAccess/SCADA 8.3 Professional with 75 Tags
	WA-P83-N150E	WebAccess/SCADA 8.3 Professional with 150 Tags
	WA-P83-N300E	WebAccess/SCADA 8.3 Professional with 300 Tags
	WA-P83-N600E	WebAccess/SCADA 8.3 Professional with 600 Tags
1	WA-P83-N15HE	WebAccess/SCADA 8.3 Professional with 1,500 Tags
	WA-P83-N50HE	WebAccess/SCADA 8.3 Professional with 5,000 Tags
	WA-P83-N20KE	WebAccess/SCADA 8.3 Professional with 20,000 Tags
	WA-P83-N64KE	WebAccess/SCADA 8.3 Professional with Unlimited Tags

#### I/O Tag Upgrades WA-X83-P075F

•

WA-X83-P075E WA-X83-P300E	WebAccess/SCADA Professional license, 75 Tags upgrade WebAccess/SCADA Professional license, 300 Tags upgrade
WA-X83-P600E	WebAccess/SCADA Professional license, 600 Tags upgrade
WA-X83-P15HE	WebAccess/SCADA Professional license, 1,500 Tags upgrade
WA-X83-P50HE	WebAccess/SCADA Professional license, 5,000 Tags upgrade

## **Dashboard Viewer**

•	Hardware	PC: Intel <sup>®</sup> Core <sup>™</sup> i3 with 4 GB RAM
		iPhone: iPhone 5
		Android: 1.5 GHz quad-core with 2 GB RAM
		Windows Phone: 1.5 GHz quad-core with 2 GB RAM
	Browser	Internet Explorer: IE 11
		Chrome: Version 37
		Firefox: Version 31
		Safari: Version 7

#### WebAccess APP

Platform Environment iOS 9 and Android 4.4

# **Mouser Electronics**

Authorized Distributor

Click to View Pricing, Inventory, Delivery & Lifecycle Information:

Advantech:

 WA-P83-U300E
 WA-P83-U50HE
 WA-P83-N150E
 WA-P83-U64KE
 WA-P83-U075E
 WA-P83-N075E
 WA-P83 

 N300E
 WA-P83-N600E
 WA-P83-U15HE
 WA-P83-U20KE
 WA-P83-N64KE
 WA-P83-U600E
 WA-P83-N20KE
 WA-P83-U150E
 WA-P83-N15HE
 WA-P83-N50HE