

**IEC320-C13 (Aus)**

Country of Origin : China  
Operating Temperature :  $0 \div 40$  [°C]  
Length/cord : 1.8m / 3x0.75mm<sup>2</sup>  
Approvals : SAA, VDE, KEMA-KEUR, CEBEC, DEMKO, Intertek, Nemko, NCS/FI, SEV, ÖVE, IMQ, NF

| Application      | For Class I. Appliances |                        |
|------------------|-------------------------|------------------------|
| WEIGHT / PACKING | 1pc                     | N.W.: 197 g / pc       |
|                  | Box                     | 0.56 x 0.36 x 0.20 [m] |
|                  |                         | 150 pcs / 1box         |
|                  |                         | G.W.: 26 kg / box      |



**IEC320-C13 (Brazil)**

Country of Origin : China  
Operating Temperature :  $0 \div 40$  [°C]  
Length/cord : 1.8m / 3x0.75mm<sup>2</sup>  
Approvals : TUV, VDE, KEMA-KEUR, CEBEC, DEMKO, Intertek, Nemko, ENEC/FI, SEV, ÖVE

| Application      | For Class I. Appliances |                        |
|------------------|-------------------------|------------------------|
| WEIGHT / PACKING | 1pc                     | N.W.: 158g / pc        |
|                  | Box                     | 0.36 x 0.20 x 0.55 [m] |
|                  |                         | 100pcs / 1box          |
|                  |                         | G.W.: 16.7 kg / box    |



**IEC320-C13 (Swiss)**

Country of Origin : China  
Operating Temperature :  $0 \div 40$  [°C]  
Length/cord : 1.8m / 3x0.75mm<sup>2</sup>  
Approvals : SEV

| Application      | For Class I. Appliances |                        |
|------------------|-------------------------|------------------------|
| WEIGHT / PACKING | 1pc                     | N.W.: 169g / pc        |
|                  | Box                     | 0.36 x 0.20 x 0.55 [m] |
|                  |                         | 100pcs / 1box          |
|                  |                         | G.W.: 19kg / box       |



**IEC320-C13 (EU)**

Country of Origin : China  
Operating Temperature :  $0 \div 40[^\circ\text{C}]$   
Length/cord : 1.8m / 3x0.75mm<sup>2</sup>  
Approvals : VDE, KEMA-KEUR, CEBEC, DEMKO, Intertek, Nemko, NCS/FI, ÖVE, IMQ, NF, SEV

| Application      | For Class I. Appliances |                        |
|------------------|-------------------------|------------------------|
| WEIGHT / PACKING | 1pc                     | N.W.: 185g / pc        |
|                  | Box                     | 0.55 x 0.36 x 0.20 [m] |
|                  |                         | 90pcs / 1box           |
|                  |                         | G.W.: 18.2 kg / box    |



**IEC320-C13 (UK)**

Country of Origin : China  
Operating Temperature :  $0 \div 40[^\circ\text{C}]$   
Length/cord : 1.8m / 3x0.75mm<sup>2</sup>  
Approvals : ASTA

| Application      | For Class I. Appliances |                        |
|------------------|-------------------------|------------------------|
| Fuse             | 5A / 250V               |                        |
| WEIGHT / PACKING | 1pc                     | N.W.: 195g / pc        |
|                  | Box                     | 0.48 x 0.26 x 0.44 [m] |
|                  |                         | 75pcs / 1box           |
|                  |                         | G.W.: 12.5 kg / box    |



**IEC320-C13 (UL)**

Country of Origin : China  
Operating Temperature :  $0 \div 40[^\circ\text{C}]$   
Length/cord : 1.8m / 3x0.75mm<sup>2</sup>  
Approvals : UL

| Application      | For Class I. Appliances |                        |
|------------------|-------------------------|------------------------|
| WEIGHT / PACKING | 1pc                     | N.W.: 72g / pc         |
|                  | Box                     | 0.56 x 0.36 x 0.20 [m] |
|                  |                         | 125pcs / 1box          |
|                  |                         | G.W.: 12.5 kg / box    |



**IEC320-C13 (C)**

Country of Origin : China  
Operating Temperature :  $0 \div 40[^\circ\text{C}]$   
Length/cord : 1.8m / 3x0.75mm<sup>2</sup>  
Approvals : CCC

| Application      | For Class I. Appliances |                        |
|------------------|-------------------------|------------------------|
| WEIGHT / PACKING | 1pc                     | N.W.: 182g / pc        |
|                  | Box                     | 0.55 x 0.36 x 0.20 [m] |
|                  |                         | 90pcs / 1box           |
|                  |                         | G.W.: 18.2 kg / box    |



**IEC320-C13 (AG)**

Country of Origin : China  
Operating Temperature :  $0 \div 40[^\circ\text{C}]$   
Length/cord : 1.8m / 3x0.75mm<sup>2</sup>  
Approvals : IRAM, VDE, CEBEC, KEMA-KEUR, DEMKO, Intertek, Nemko, NCS/FI, ÖVE, IMQ, NF, SEV

| Application      | For Class I. Appliances |                        |
|------------------|-------------------------|------------------------|
| WEIGHT / PACKING | 1pc                     | N.W.: 179g / pc        |
|                  | Box                     | 0.55 x 0.36 x 0.20 [m] |
|                  |                         | 90pcs / 1box           |
|                  |                         | G.W.: 18.0 kg / box    |



**IEC320-C13 (Italy)**

Country of Origin : China  
Operating Temperature :  $0 \div 40[^\circ\text{C}]$   
Length/cord : 1.8m / 3x0.75mm<sup>2</sup>  
Approvals : VDE, KEMA-KEUR, CEBEC, DEMKO, Intertek, Nemko, ENEC/FI, SEV, ÖVE, IMQ, NF

| Application      | For Class I. Appliances |                        |
|------------------|-------------------------|------------------------|
| WEIGHT / PACKING | 1pc                     | N.W.: 158g / pc        |
|                  | Box                     | 0.36 x 0.20 x 0.55 [m] |
|                  |                         | 100pcs / 1box          |
|                  |                         | G.W.: 16.9 kg / box    |



# Mouser Electronics

Authorized Distributor

Click to View Pricing, Inventory, Delivery & Lifecycle Information:

[Advantech:](#)

[BB-PWRCORD-EU](#)