PART NUMBER		REV	ECO	DATE
138-0407-021		1	INITIAL RELEASE	05MAR2021
NOTES:				
1. MATERIAL AND FINISH:				
 1.1 BODY: BRASS, NICKEL PLATE 1.2 CONTACT: BRASS, GOLD PLATE 1.3 INSULATOR: PTFE 1.4 GASKET: SILICONE RUBBER, RED 1.5 RETENTION SPRING: PHOSPHOR BRONZE 1.6 COUPLING NUT: BRASS, NICKEL PLATE 1.7 FERRULE: BRASS, NICKEL PLATE 2. ELECTRICAL SPECIFICATIONS: 2.1 IMPEDANCE: 50 OHMS NOMINAL 2.2 FREQUENCY RANGE: DC~4.0 GHz 2.3 VSWR: 1.30 MAX 2.4 INSERTION LOSS: 0.1 dB MAX 2.5 VOLTAGE RATING: 500 VRMS MAX 2.6 DIELECTRIC WITHSTANDING VOLTAGE: 1000 VRMS MIN 2.7 INSULATION RESISTANCE: 5000 MEGOHM MIN 2.8 CONTACT RESISTANCE: 5000 MEGOHM MIN 2.8.1 CENTER CONTACT - 3.0 MILLIOHM MAX 2.8.2 OUTER CONDUCTOR - 1.0 MILLIOHM MAX 	500	¢.443 ¢.352 ¢.126 • .311	748 H	
 3. MECHANICAL SPECIFICATIONS: 3.1 ENGAGE/DISENGAGE: 2.0 LBS MAX 3.2 COUPLING NUT TORQUE: 12–15 IN.LBS 3.3 DURABILITY: 500 CYCLES MIN 		ſ	\frown	
4. ENVIRONMENTAL:	327-+		\checkmark	
(MEETS OR EXCEEDS THE APPLICABLE PARAGRAPH OF MIL-PRF-39012)	.098366	-		
 4.1 THERMAL SHOCK: MIL-STD-202, METHOD 107, CONDITION B EXEPT 200°C HIGH TEMP 4.2 OPERATING TEMPERATURE: -65°C TO 165°C 4.3 MOISTURE RESISTANCE: MIL-STD-202, METHOD 106, LESS STEP 7b 4.4 MECHANICAL SHOCK: MIL-STD-202, METHOD 213, CONDITION I 4.5 VIBRATION: MIL-STD-202, METHOD 204, CONDITION D 4.6 CORROSION: MIL-STD-202, METHOD 101, CONDITION B 	RECOMMENDED CABLE STRIPPING DIMENSIONS		ENDED CRIMPING NNS FOR FERRULE	
	Concentry Sources Model No: 138-	-0407-021/030	JOHNS	ON
	This PROPRIETARY Document is property Clonb Connectivity Solutional II is confidential in notice, non-transferedia, CUMPLIANT	Cage Code	N-TYPE STRIGHT F	PLUG
	in nature, non-transferable, ULIMPLIANI and lasaed with the dom understanding that it is not transfer dom and is returnable permission and is returnable	1960 UT DENIC	FOR RG58 CABLE wing No. 138-0407-021	· · · ·
	INTERPRET DRAWING IN ASME Y14.5-2009. ANGLES ±5°	04 Date: 03/05/2021 Size	B DO NOT SCALE Workmanship S DRAWING NON	E 1 OF 1

Mouser Electronics

Authorized Distributor

Click to View Pricing, Inventory, Delivery & Lifecycle Information:

Cinch Connectivity Solutions: 138-0407-021