

### Right Angle SMA Male Plug to SMA Female Jack

#### Model Number

**ADT-8000-MF-SMA-02**


#### SPECIFICATIONS

**Frequency:** DC - 18.0 GHz

**VSWR:** 1.05 + .010 f (GHz)

**Impedance:** 50 Ohms

**Finish:** Passivated Stainless Steel



Formerly SMA-028-8000 and SMA-8000-28-000-02

### Right Angle SMA Female Jack to SMA Female Jack

#### Model Number

**ADT-8000-FF-SMA-02**


#### SPECIFICATIONS

**Frequency:** DC - 18.0 GHz

**VSWR:** 1.05 + .010 f (GHz)

**Impedance:** 50 Ohms

**Finish:** Passivated Stainless Steel



Formerly SMA-026-8000 and SMA-8000-26-000-02

### Right Angle SMA Male Plug to SMA Male Plug

#### Model Number

**ADT-8000-MM-SMA-02**


#### SPECIFICATIONS

**Frequency:** DC - 18.0 GHz

**VSWR:** 1.05 + .010 f (GHz)

**Impedance:** 50 Ohms

**Finish:** Passivated Stainless Steel



### SMA Female Jack to SMA Female Jack - Bkhd Mount - Hermetic

#### Model Number

**ADT-2824-FF-SMA-02**


#### SPECIFICATIONS

**Frequency:** DC - 18.0 GHz

**VSWR:** 1.10 + .010 f (GHz)

**Impedance:** 50 Ohms

**Finish:** Passivated Stainless Steel



Standard finish is passivated stainless steel, for gold plating change -02 suffix to -00.

# Mouser Electronics

Authorized Distributor

Click to View Pricing, Inventory, Delivery & Lifecycle Information:

[Cinch Connectivity Solutions:](#)

[ADT-2824-FF-SMA-02](#)